

Two-dimensional face image classification for distinguishing children from adults based on anthropometry

Grd, Petra

Doctoral thesis / Disertacija


2015

Degree Grantor / Ustanova koja je dodijelila akademski / stručni stupanj: **University of Zagreb, Faculty of Organization and Informatics Varaždin / Sveučilište u Zagrebu, Fakultet organizacije i informatike Varaždin**

Permanent link / Trajna poveznica: <https://urn.nsk.hr/urn:nbn:hr:211:517258>

Rights / Prava: [In copyright](#) / [Zaštićeno autorskim pravom.](#)

Download date / Datum preuzimanja: **2025-01-24**



Repository / Repozitorij:

[Faculty of Organization and Informatics - Digital Repository](#)





University of Zagreb

Faculty of Organization and Informatics

Petra Grd

**TWO-DIMENSIONAL FACE IMAGE
CLASSIFICATION FOR DISTINGUISHING
CHILDREN FROM ADULTS BASED ON
ANTHROPOMETRY**

DOCTORAL THESIS

Varaždin, 2015.

DOCTORAL THESIS INFORMATION

I. AUTHOR

| | |
|--|---|
| Name and surname | Petra Grd |
| Place and date of birth | Kutina, February 14 th 1986 |
| Faculty name and graduation date for level VII/I | Faculty of Organization and Informatics, June 8 th 2009 |
| Faculty name and graduation date VII/II | |
| Current employment | University of Zagreb, Faculty of Organization and Informatics, Varaždin |

II. DOCTORAL THESIS

| | |
|---|--|
| Title | Two-dimensional face image classification for distinguishing children from adults based on anthropometry |
| Number of pages, figures, tables, appendixes, bibliographic information | 151 pages, 23 figures, 39 tables, 3 appendixes and 131 bibliographic information |
| Scientific area and field in which the title has been awarded | Social Sciences, Information and Communication Sciences |
| Mentors | Full Professor Miroslav Bača, PhD |
| Faculty where the thesis was defended | Faculty of Organization and Informatics, Varaždin |
| Mark and ordinal number | |

III. GRADE AND DEFENSE

| | |
|--|--|
| Date of doctoral thesis topic acceptance | November 25 th 2014 |
| Date of doctoral thesis submission | April 21 st 2015 |
| Date of doctoral thesis positive grade | May 26 th 2015 |
| Grading committee members | Assistant Professor Markus Schatten, PhD Full Professor Miroslav Bača, PhD Associate Professor Arun Ross, PhD Associate Professor Kornelije Rabuzin, PhD Assistant Professor Sandro Gerić, PhD |
| Date of doctoral thesis defense | June 16 th 2015 |
| Defense committee members | Assistant Professor Markus Schatten, PhD Full Professor Miroslav Bača, PhD Associate Professor Arun Ross, PhD Associate Professor Kornelije Rabuzin, PhD Assistant Professor Sandro Gerić, PhD |
| Date of promotion | |



University of Zagreb

Faculty of Organization and Informatics

PETRA GRD

**TWO-DIMENSIONAL FACE IMAGE
CLASSIFICATION FOR DISTINGUISHING
CHILDREN FROM ADULTS BASED ON
ANTHROPOMETRY**

DOCTORAL THESIS

Thesis adviser: Full Professor Bača Miroslav, PhD

Varaždin, 2015.



Sveučilište u Zagrebu

Fakultet organizacije i informatike

Petra Grd

**KLASIFIKACIJA DVODIMENZIONALNIH
SLIKA LICA ZA RAZLIKOVANJE DJECE
OD ODRASLIH OSOBA NA TEMELJU
ANTROPOMETRIJE**

DOKTORSKA DISERTACIJA

Varaždin, 2015.

ABSTRACT

Classification of face images can be done in various ways. This research uses two-dimensional photographs of people's faces to detect children in images. Algorithm for classification of images into children and adults is developed and existing algorithms are analysed. This algorithm will also be used for age estimation. Through analysis of the state of the art research on facial landmarks for age estimation and combination with changes that occur in human face morphology during growth and aging, facial landmarks needed for age classification and estimation of humans are identified. Algorithm is based on ratios of Euclidean distances between those landmarks. Based on these ratios, children can be detected and age can be estimated.

Keywords: Biometrics, face aging, anthropometric ratios, craniofacial morphology, face changes

SAŽETAK

Slike lica mogu biti klasificirane na različite načine. Ovo istraživanje koristi dvodimenzionalne fotografije ljudskih lica za detekciju djece na slikama. Kreiran je novi algoritam za klasifikaciju fotografija ljudskih lica u dvije grupe, djeca i odrasli. Algoritam će se također koristiti za procjenu dobi osoba na slici te će biti analizirani postojeći algoritmi. Kroz analizu literature o karakterističnim točkama korištenih u procjeni dobi i kombinacijom dobivenih karakterističnih točaka s morfološkim promjenama tokom odrastanja i starenja, definirane su karakteristične točke potrebne za klasifikaciju i procjenu dobi. Algoritam se bazira na omjerima Euklidskih udaljenosti između identificiranih karakterističnih točaka.

Ključne riječi: Biometrija, starenje lica, antropometrijski omjeri, kraniofacijalna morfologija, promjene na licu

Contents

| | |
|---|-----|
| Contents | I |
| List of Figures..... | III |
| List of Tables | IV |
| List of Abbreviations | VI |
| List of Appendixes | X |
| Chapter 1: Introduction..... | 1 |
| 1.1. Objective and Hypotheses | 3 |
| 1.2. Methodology..... | 4 |
| 1.3. Ethical Aspects | 7 |
| Chapter 2: Literature Review | 8 |
| 2.1. Aging Face..... | 25 |
| 2.2. Types of Age..... | 28 |
| 2.3. Face Representation Models | 29 |
| 2.3.1. Anthropometric Model | 29 |
| 2.3.2. Active Appearance Model..... | 31 |
| 2.3.3. Aging Pattern Subspace..... | 32 |
| 2.3.4. Age Manifold..... | 33 |
| 2.3.5. Biologically-Inspired Models | 33 |
| 2.3.6. Discussion..... | 34 |
| 2.4. Aging Function Learning Methods..... | 35 |
| 2.4.1. Classification | 35 |
| 2.4.2. Regression | 36 |
| 2.4.3. Hybrid..... | 37 |

| | |
|---|-----|
| Chapter 3: New Algorithm for Age Classification | 38 |
| 3.1. Face Representation | 38 |
| 3.1.1. Facial Landmarks | 39 |
| 3.1.2. Ratios | 47 |
| 3.2. Classification | 52 |
| Chapter 4: Experimental Results | 55 |
| 4.1. Datasets..... | 55 |
| 4.1.1. Public Databases..... | 55 |
| 4.1.2. Private Database | 58 |
| 4.2. Performance Measurement | 62 |
| 4.2.1. Age Classification | 62 |
| 4.2.2. Age Estimation | 67 |
| 4.3. Comparison with State of the Art Algorithms | 76 |
| Chapter 5: Application | 82 |
| Chapter 6: Conclusion | 84 |
| Bibliography | 87 |
| APPENDIX A New algorithm results for Fg-net database | 101 |
| APPENDIX B Anthropometric model results for Fg-net database | 114 |
| APPENDIX C New algorithm results for Private database..... | 124 |
| Curriculum Vitae | 133 |
| List of Publications..... | 134 |

List of Figures

| | |
|---|----|
| Figure 2.1. Head shape changes caused by craniofacial growth (Geng, Yun and Smith-Miles, 2010)..... | 26 |
| Figure 2.2. Craniofacial changes during growth and aging from Fg-net database (Fg-net, 2014)..... | 27 |
| Figure 2.3. Anthropometric ratio 1 on human face (Kwon and Lobo, 1999)..... | 30 |
| Figure 2.4. Anthropometric ratio 2 on human face (Kwon and Lobo, 1999)..... | 30 |
| Figure 2.5. Anthropometric ratio 3 on human face (Kwon and Lobo, 1999)..... | 30 |
| Figure 2.6. Anthropometric ratio 4 on human face (Kwon and Lobo, 1999)..... | 30 |
| Figure 2.7. Anthropometric ratio 5 on human face (Kwon and Lobo, 1999)..... | 31 |
| Figure 2.8. Anthropometric ratio 6 on human face (Kwon and Lobo, 1999)..... | 31 |
| Figure 2.9. Classification of aging function learning methods..... | 35 |
| Figure 3.1. Block diagram of the new algorithm..... | 38 |
| Figure 3.2. Landmark points as identified by Kleinberg and Siebert (2012) | 39 |
| Figure 3.3. Landmark points as identified by Takimoto et al. (2007)..... | 40 |
| Figure 3.4. Landmark points as identified by Txia and Huang (2009) | 40 |
| Figure 3.5. Landmark points as identified by Ramanathan and Chellapa (2006) | 41 |
| Figure 3.6. Landmark points as identified by Kostinger et al. (2011)..... | 41 |
| Figure 3.7. Landmark points as identified by Izadpanhi and Toygar (2012) | 42 |
| Figure 3.8. All landmark points as identified in literature | 43 |
| Figure 3.9. Landmark points used in this research | 45 |
| Figure 3.10. Correlation between years and ratio $d(\text{MFL}, \text{LAML})/d(\text{MFL}, \text{MFR})$ | 50 |
| Figure 3.11. Correlation between years and ratio $d(\text{MFL}, \text{PHR})/d(\text{PHL}, \text{LAML})$ | 50 |
| Figure 4.1. Cumulative score curve of the new algorithm tested on the Fg-net database | 70 |
| Figure 4.2. Comparison of cumulative score curves of the new algorithm and anthropometric model tested on the Fg-net database | 73 |
| Figure 4.3. Cumulative score curve of the new algorithm tested on the private database | 75 |

List of Tables

| | |
|--|----|
| 2.1. Methods used in state of the art age classification and estimation algorithms..... | 18 |
| 2.2. State of the art papers by sources | 23 |
| 2.3. State of the art papers by year of publication | 24 |
| 2.4. Face shape changes caused by growth or aging | 27 |
| 2.5. Advantages and disadvantages of face representation models | 34 |
| 3.1. Landmark points identified in literature | 43 |
| 3.2. Landmark points used in this research | 46 |
| 3.3. Spearman coefficients | 51 |
| 3.4. MLP case processing summary | 53 |
| 3.5. MLP information | 54 |
| 3.6. Trained MLP results | 54 |
| 4.1. Face age databases..... | 56 |
| 4.2. Face age databases by number of papers..... | 57 |
| 4.3. Subjects and images by sex in Fg-net database..... | 57 |
| 4.4. Images per person in Fg-net database..... | 58 |
| 4.5. Images per age in Fg-net database..... | 58 |
| 4.6. Information collected for the private database | 60 |
| 4.7. Subjects per sex collected for the private database | 60 |
| 4.8. Images per person collected for the private database | 61 |
| 4.9. Images per age collected for the private database | 61 |
| 4.10. Subjects per sex left in the private database after preprocessing | 62 |
| 4.11. Images per age left in the private database after preprocessing | 62 |
| 4.12. General confusion matrix (Lecture Notes, 2015) | 63 |
| 4.13. Confusion matrix for the new algorithm tested on the Fg-net database..... | 64 |
| 4.14. Classification accuracy of the new algorithm by age tested on the Fg-net database | 65 |
| 4.15. MAE per age results of the new algorithm tested on the Fg-net database | 68 |
| 4.16. MAE per decade results of the new algorithm tested on the Fg-net database..... | 69 |

| | |
|--|----|
| 4.17. CS results of the new algorithm tested on the Fg-net database | 69 |
| 4.18. Face ratios used in anthropometric model | 70 |
| 4.19. Comparison of MAE per age results of the new algorithm and anthropometric model tested on the Fg-net database | 71 |
| 4.20. Comparison of MAE per decade results of the new algorithm and anthropometric model tested on the Fg-net database | 72 |
| 4.21. Comparison of CS results of the new algorithm and anthropometric model tested on the Fg-net database | 73 |
| 4.22. MAE per age results of the new algorithm tested on the private database..... | 74 |
| 4.23. MAE per decade results of the new algorithm tested on the private database | 74 |
| 4.24. CS results of the new algorithm tested on the private database | 75 |
| 4.25. Current research results for age classification | 76 |
| 4.26. Research results for age classification comparable to this research..... | 77 |
| 4.27. Current research results for age estimation | 78 |
| 4.28. Comparison of state of the art research results for age estimation with the new algorithm results | 80 |

List of Abbreviations

MAE - Mean Absolute Error
CS - Cumulative Score
NN - Neural Network
AGES - Agging Pattern Subspace
CDLPP - Class Distance Weighted Locality Preserving Projection
PCA - Principal Component Analysis
LPP - Locality Preserving Projection
HMM - Hidden Markov Model
PFA - Probabilistic Fusion Approach
SVR - Support Vector Regression
SVM - Support Vector Machines
ICA - Independent Component Analysis
AAM - Active Appearance Model
LAR - Least Angle Regression
LDA - Linear Discriminant Analysis
LTP - Local Ternary Patterns
MTWGP - Multi-Task Warped Gaussian Process
EBIF - Enhanced Biologically Inspired Features
BIF - Biologically Inspired Features
ASM - Active Shape Model
RBF - Radial Basis Function
HOG - Histogram of Oriented Gradients
CCA - Canonical Correlation Analysis
MPCA - Multilinear Principal Component Analysis
OHRANK - Ordinal Hyperplane Ranking
NMF - Non-negative Matrix Factorization
SFM - Supervised Facial Model
PLS-R - Partial Least Squares Regression
CAM - Contourlet Appearance Model

NSCT - Nonsubsampled Contourlet Transform
GLOH - Gradient Location and Orientation Histogram
MTL - Multi-task Learning
DCT - Discrete Cosine Transform
OLS-R - Orthogonal Least Square Regression
MFA - Multilinear Subspace Analysis
MFOR - Multi-feature Ordinal Ranking
SRC - Sparse Representation-based Classification
DFT - Discrete Fourier Transform
GP - Gaussian Process
TP - T process
CPNN - Conditional Probability Neural Network
ART - Adaptive Resonance Network
KDE - Kernel Density Estimate
LAG - Lie Algebrized Gaussians
GMM - Gaussian Mixture Models
ACM - Active Contour Model
MLP - Multilayer Perceptron
kNN - K Nearest Neighbours
OLPP - Age Manifold
ALR - Age Group Specific Linear Regression
SFM - Supervised Facial Model
ML-SVM - Multi-label Support Vector Machines
MTSVR - Multi-task Support Vector Regression
GC - Global Classification
LCC - Local Classification
LBPKDE - Local Binary Pattern Kernel Density Estimate
CM - Craniofacial Morphology
AM - ANthropometric Model
EM - Expectation-Maximization
HH - Highest point of the head
MFL - Middle point of the forehead (left)

PHL - Most protruded point of the head (left)
MPL - Midpoint between PHL and LAML
LAML - Most lateral point at the angle of the mandible (left)
PMTL - Protrusion of the mental tubercle (left)
LMLC - Lowest point in the midline on the lower border of the chin
PMTR - Protrusion of the mental tubercle (right)
LAMR - Most lateral point at the angle of the mandible (right)
MLP - Midpoint between LAMR and PHR
PHR - Most protruded point of the head (right)
MFR - Middle point of the forehead (right)
LEBL - Most lateral point of the eyebrow (left)
HUMEL - Highest point on the upper margin of the midline portion of the eyebrow (left)
MBHML - Midpoint between HUMEL and MHEL (left)
MHEL - Medial hinge of the eyebrow (left)
LEL - Lateral hinge of the eyelid (left)
HEL - Highest point of the eyelid (left)
MPEL - Middle point of the eye (left)
LMLEL - Lowest point in the middle of the margin of the lower eyelid (left)
MEL - Medial hinge of the eyelid (left)
LPMEL - Lowest point in the middle of eyesocket (left)
MNS - Midpoint of the nasofrontal suture
FMN - Point of the nose where forehead meets the nose
MHER - Medial hinge of the eyebrow (right)
MBHMR - Midpoint between HUMER and MHER (right)
HUMER - Highest point on the upper margin of the midline portion of the eyebrow (right)
LEBR - Most lateral point of the eyebrow (right)
LER - Lateral hinge of the eyelid (right)
HER - Highest point of the eyelid (right)
MPER - Middle point of the eye (right)
LMLER - Lowest point in the middle of the margin of lower eyelid (right)

MER - Medial hinge of the eyelid (right)
LPMER - Lowest point in the middle of eyesocket (right)
NB - Nose bridge
MBNP - Midpoint between NB and PNT
MUNAL - Most upper point of the nasal ala (left)
MUNAR - Most upper point of the nasal ala (right)
MNAOL - Medial point of the nasal ala outer margin (left)
PNT - Most protruded point of the nasal tip
MNAOR - Medial point of the nasal ala outer margin (right)
LNAL - Most lateral point of the nasal ala (left)
LNAR - Most lateral point of the nasal ala (right)
LNL - Most lateral point of the nose (left)
LNAIL - Lowest lateral point of the nasal ala inner margin (left)
INTUL - Most inner point between the nose tip and upper lip
LNAIR - Lowest lateral point of the nasal ala inner margin (right)
LNR - Most lateral point of the nose (right)
HULR - Highest point of the upper lip (right)
MVUL - The midpoint of the vermilion border of the upper lip
HULL - Highest point of the upper lip (left)
LULML - Most lateral point where the upper and the lower lip meet (left)
MULLM - Midline point where upper and lower lip meet
LULMR - Most lateral point where the upper and the lower lip meet (right)
MLLL - Midpoint of the lower margin of the lower lip
MPLL - Midpoint of the pogonion and lower lip
AC - Most anterior point of the chin
ANN - Artificial Neural Network
ID - Identifier of the subject
IM_ID - Image identifier
IM_AGE - Age of subject in image
DOB - Date of birth
DOA - Date of Acquisition
ECRM - Electronic Customer Relationship Management

List of Appendixes

APPENDIX A New Algorithm Results for Fg-net Database

APPENDIX B Anthropometric Model Results for Fg-net Database

APPENDIX C New Algorithm Results for Private Database

Chapter 1: Introduction

Age estimation and age classification of humans using their face images are a part of a field of biometric. Biometric systems use behavioral and physiological characteristics to recognize individuals. Soft biometric traits like age, gender, ethnicity, height, weight in combination with hard biometric traits can be used to enhance the performance of biometric systems. This research concentrates on age classification and estimation.

Age estimation is an important task in classifying face images. It can be defined as the determination of the age of the person or his/her age group (Scholarpedia, 2013), (Grd, 2013). Human age classification and estimation can be defined in many ways, but this research is concerned with the age estimation and classification based on two-dimensional images of people's faces. Age estimation and classification is done using face anthropometry.

For the purposes of this research definitions of basic terms are given. Age classification is used to classify images in those of children and adults. Children are defined as people from age 0 to 17 and adults are defined as people from age 18 and above. Age estimation in this research is defined as determining the age of a person based on biometric features, more precise on the basis of two-dimensional images of human face (Scholarpedia, 2013). Facial landmarks can be defined as the standard reference points on the face used by scientists to recognize the face, or in this case, predict the age of a person (Face and Emotion, 2013). Anthropometry is the science dealing with measurements of the size, weight, and proportions of the human body (Medical Dictionary, 2015). Therefore, facial anthropometry deals with measurements of the size and proportions of human face.

The aging process affects the structure and appearance of face in many ways. The changes that occur are related to facial morphology, and changes in the face texture. Some characteristics of facial morphology appear only in people of a certain age and change during the aging process (Koruga, Bača and Schatten, 2011). Changes in skin

texture usually occur in adulthood. According to Geng, Fu and Smith-Miles (2010) changes in the face that occur during aging and growth are: chin becomes more prominent, cheeks spread over a larger area, facial characteristics increase and cover the interstitial spaces, head falls backwards, reducing the free space on the surface of the skull, facial hair becomes thicker and changes color, skin color changes, skin becomes thinner, darker, less elastic and more leathery, wrinkles appear, underchin appears, cheeks sag and bags under the eyes appear. Based on all these changes, the age of a person can be determined.

The main motivation of this research is to create an algorithm for classification of humans into minors and adults, for use in detecting illegal content, especially for detection of potential paedophile images. This research will identify the characteristic points of the face necessary to classify face images, it will identify the most appropriate model for age estimation, private database with normalized facial images will be created and a new algorithm for age classification will be developed. Accuracy of the algorithm will be calculated and compared with the accuracy of existing algorithms.

The scientific contribution of this research is as follows:

- Systematization of knowledge on age classification,
- Identification of facial landmarks relevant for age classification and estimation,
- A novel data mining based approach for ratios identification that are important for the age classification and estimation processes
- Creation of a new algorithm for age classification,
- Evaluation of anthropometric model on a large database.

In addition to scientific, this research has a social contribution also. Human age estimation is widely applicable and has great potential: determining the age of immigrants or asylum seekers in situations where there are no documents proving the age of the person, for websites where entrance is allowed only for persons over the age of 18, in order to improve the system for face recognition (most of them are sensitive to changes during aging), searching for missing persons over the years, in human-computer interaction based on age, for the purpose of predicting a persons aging, in the fight against pedophilia (removing images of minors from various portals or personal

computers), etc. These are just some of the possible uses of human age estimation, and with further development of new technologies, there will be more.

The second chapter of the thesis gives a literature review of the field of biometric age estimation and classification. A systematic review of state of the art research is done and an overview of research papers is given. Next, the papers are categorized according to face representations model and aging function learning methods. After that, a description of the most often used face representation models and aging function learning methods, along with their advantages and disadvantages is given. In this chapter, changes on human face during growth and aging are identified. Chapter three describes the new algorithm for age classification and estimation. The algorithm is divided into two parts: face representation and classification. First, facial landmarks needed for ratios calculation are identified. These ratios are used for face representation. After that, the neural network, more accurately a multi layer perceptron, as a classification method is described. Chapter four describes experimental results. This chapter is divided into three parts. First part is a description of databases used for algorithm training and testing. The second part is performance measurement where the hypotheses have been confirmed. The last part of this chapter compares the new algorithm results with existing algorithms. Chapter five describes the possible applications of the algorithm and in conclusion overview of the research, answers to the research questions and confirmed hypotheses are given.

1.1. Objective and Hypotheses

The main objective of this research is to develop an algorithm for human age classification and estimation which can classify humans into minors and adults. This new algorithm will be based on the model proposed in this research.

More specific objectives, to be achieved in order to realize the main objective are:

- Identify changes on the face that occur during growth and aging
- Identify facial landmarks necessary for algorithm creation
- Identify ratios needed for the new algorithm

- Create a new age estimation algorithm
- Compare the new algorithm accuracy with the accuracy of existing algorithms

Based on the defined goals, the research questions are set:

RESEARCH QUESTION 1

What changes occur on human face during growth and aging?

RESEARCH QUESTION 2

Which facial landmarks are important for age classification and estimation?

RESEARCH QUESTION 3

Which facial ratios are important for age classification and estimation?

Other than research questions there are two hypothesis:

HYPOTHESIS 1

The newly developed algorithm distinguishes children from adults based on facial anthropometric ratios with an accuracy of more than 80% when used on the publicly available Fg-net database.

HYPOTHESIS 2

Usage of different facial anthropometric ratios than those used in existing anthropometric model, increases the accuracy of the algorithm when used for age estimation.

1.2. Methodology

This research combines both qualitative and quantitative methods, which means that it uses a combined research design. According to Creswell (2008), combined research design is useful when neither qualitative nor quantitative approach separately are not suitable to best understand the research problem, or when the power of qualitative and quantitative research together can offer the best understanding of the problem. More specifically, in this study, it is first necessary to identify changes in human face during growth and aging, then it is necessary to identify facial landmarks needed to describe these changes. Regarding to the applicability of research, this

research is an applied research because it relates to the acquisition of new knowledge for the purpose of finding practical solutions for immediate application (Tkalec Verčič, Sinčić Ćorić and Pološki Vokić, 2010).

The first step of this research will be a review of scientific literature on human age estimation on the basis of two-dimensional images of the face. For this purpose following scientific methods will be used (Kulenović and Slišković, 2015):

- Description is used in the initial phase of this research. It is a simple way of describing facts, objects, processes and connections between them without scientific interpretation
- Compilation is overtaking others' results of scientific research, their observations, opinions and conclusions.
- Analysis is the breakdown of complex thought creations to their simpler component parts and study each part separately and in relation to other parts.
- Synthesis is connecting simple creations to complex thought, linking them together and parts are connected to each other.
- Generalization takes individual observations and draws generalized conclusions.
- Specialization takes a general idea and comes up with a new idea, narrower in scope and richer in content.

This is followed by one of the most important steps, and that is collecting data for the research. This step is divided into two parts. The first part is listing, analysis and acquisition of existing and publicly available databases of face images. The only database publicly available and appropriate for this research is Fg-net (Fg-net, 2014) face database containing 1002 images of 82 different people with marked age. In addition to the aforementioned database private face database will be created. All participants whose photos are collected to create this database are informed about the purpose for which the images will be used, the personal data protection law, the privacy policy on the protection of personal data and they signed the consent for the use of their personal data in this research. Once the images are collected, they have to be normalized, which means that the images need to be reviewed, all images have to be face images, and they have to be larger than the minimum size defined.

The next step is to define the differences in the structure of the human face during growth and aging. Literature on human face changes will be consulted in this step. To this end, the methods of comparison and generalization will be used:

- Comparison is comparing the same or related facts, phenomena, processes or relationships, and establishing their similarities and differences.
- Generalization derives generalized conclusions from observations in the previous step.

After this, it is easy to define changes on human face during growth and aging and facial landmarks relevant for age estimation. The method that will be used for this is abstraction. Abstraction is a thought process that separates irrelevant and highlights important element or traits of specific objects or phenomena research, or in this case, separate the important from the unimportant facial landmarks (Kulenović and Slišković, 2015).

After the previous steps, it is necessary to develop an algorithm for age classification. The basis of the algorithm are ratios on human face. It needs to be determined which face ratios are important. To this end, non-linear correlation will be used. Spearman coefficient will determine the correlation between each ratio and human age. After that, the algorithm needs to be implemented using programming languages (Python). After the implementation of the algorithm, it needs to be tested. There are various algorithms for facial landmark detection, but manual detection is still the most accurate so manually selected facial landmarks will be used as algorithm input. The algorithm gives a class value and age estimate as outputs. To evaluate the classification part of the algorithm confusion matrix will be created and accuracy, precision, recall and specificity will be calculated. Accuracy is the proportion of the total number of predictions that were correct. Precision is the proportion of positive cases that were correctly identified. Recall is the proportion of actual positive cases which are correctly identified. Specificity is the proportion of negative cases that were correctly identified. To evaluate estimation part of the algorithm, the output from the algorithm (estimated age) is compared to real age of a person (chronological age). Measures that are commonly used in literature to evaluate the performance of the age estimation algorithms are Mean Absolute Error (MAE) and Cumulative Score (CS) (Geng, Zhou

and Smith-Miles, 2007), (Guo et al., 2008), (Lanitis, Taylor and Cootes, 2002), (Lanitis, Draganova and Christodoulou, 2004). MAE is defined as the average absolute error between the estimated and chronological age (Guo et al., 2008). CS shows the percentage of cases in the test set where the estimated age error is less than the threshold. Based on the above measures algorithm accuracy will be assessed.

At the end of the research, the analysis and interpretation of results will be done, and conclusions will be given. For this, various tables and diagrams will be used.

1.3. Ethical Aspects

In this research, personal data are collected and processed. Collection and processing of such data has to be in accordance with the Croatian Law on Personal Data Protection (Narodne Novine, 2013).

During data collection, respondent was aware of the fact that he/she is giving personal information, aware of the purpose for which the information is collected, and that they can withdraw their data at any time.

Respondent received a Privacy policy for review, which describes the duration of the Privacy policy, all the data collected, the purpose for which the data is collected, and whom to contact in case of any questions. In addition to this policy, all participants signed a statement of consent, with which they give their consent for use of their personal data for this research, and confirm that they received the Privacy policy mentioned earlier. Since this research collects personal data of minors, their parents/guardians gave consent for the use of their data.

Chapter 2: Literature Review

In order to better position this research, review of existing papers on age estimation algorithms is given.

First algorithm for human age estimation was proposed by Kwon and Lobo (1994). They proposed a theory and practical calculation for the age classification of face images. Their calculations are based on the craniofacial morphology of the person and wrinkle analysis. They distinguish between primary and secondary facial characteristics, and during the implementation of the theory they first use the primary characteristics of the face (eyes, nose, mouth, chin, top of the head and the left and right ends of the head), and then the secondary. From primary characteristic ratios are calculated based on which humans are classified into three classes (children, young adults and older adults). In the analysis of secondary characteristics wrinkle map is used for detection and measurement of wrinkles on the face. By combining the analysis of ratios of the primary characteristics and analysis of facial wrinkles, images are classified in the above mentioned three classes.

Hornig, Lee and Chen (2001) propose a system which classifies humans into four classes: babies, young adults, middle-aged adults and old adults. Facial features are obtained using a Sobel edge operator and two back-propagation neural networks are used to classify images into age groups. The first neural network uses the geometric features to distinguish whether the facial image is a baby. If it is not, then the second network uses the wrinkle features to classify the image into one of three adult groups. The identification rate achieves the accuracy of 90.52% for the training images and 81.58% for the test images.

Lanitis, Draganova and Christodoulou (2004) describe the performance of different classifiers for age estimation. Classifiers used are based on quadratic functions, a shortest distance classifier and neural network based classifier. They were evaluated using single step classification method and hierarchical age estimation approach. According to their results, hierarchical age estimation based on quadratic function and neural networks achieves better age estimation results. The authors also recognize that

for algorithm improvement, fine details of the face need to be taken into consideration for age estimation.

Kalamani and Balasubramanie (2006) apply the fuzzy lattice neural network for age classification of humans into six age groups: tiny tots, blooming buds, brimming youth, midsummer dreamers, steady goers and senior citizens. Nine features are used for this classification, all of them are wrinkle features. The main difference between this approach and the earlier ones is that each image belongs to every group with a certain degree. The resulting group is the one where the image has a maximum degree.

Geng, Zhou and Smith-Miles (2007) presented aging pattern subspace (AGES) method for age estimation. The basic idea is to model the aging pattern, which is defined as a sequence of images sorted chronologically, by constructing a representative subspace. The proper aging pattern for a previously unseen face is determined by the projection in the subspace that can reconstruct the face image with minimal error, while the position of the face image in that aging pattern indicate age.

Another important research is one by Fu, Xu and Huang (2007) who classify existing methods for age estimation into three categories: anthropometric model, aging pattern subspace and age regression. They develop a new framework for age estimation which integrates three modules: face detection, manifold learning and multiple linear regression. Using age manifold a lower-dimensional representation of the image is obtained, and age estimation is defined as the problem of multiple linear regression in the manifold space.

Ueki et al. (2008) compare their Class Distance Weighted Locality Preserving Projection (CDLPP) method for dimensionality reduction for age estimation with most often used methods: Principal Component Analysis (PCA), Locality Preserving Projection (LPP) and Locality Preserving Projection with Local Scaling. The method is based on the extension of LPP method by adding weights to the data with close class labels.

Zhuang et al. (2008) propose using a patch-based Hidden Markov Model (HMM) supervector for face image patches representation. This way, they capture the spatial

structure of human faces and loosen the assumption of identical face patch distribution. Euclidean distance is used as a similarity measurement.

Shen and Ji (2008) propose a geometric feature based age classification system. This system classifies images into two age groups: babies and adults. They also developed an algorithm for eyes, nose and mouth location invariant to pose, background and illumination. The problem with this algorithm is that it uses only one ratio (eye-eye distance and eye-nose distance), and if a subject looks down or up the algorithm is not accurate.

Ben, Su and Wu (2008) use the fact that different facial regions mature at different ages, and use the most significant region for facial age estimation. Their framework consists of two steps: age range prediction and usage of selected region in the predicted age range to make final age estimation.

Guo et al. (2008) say that current age estimation approaches are still not good enough for practical application. In their paper they present age manifold learning scheme for facial aging characteristics extraction, and they design a locally adjusted robust regressor for learning and age estimation. Their approach improves the accuracy with respect to other methods. The same authors (Guo et al., 2008) propose another algorithm for human age estimation based on facial images. The Probabilistic Fusion Approach (PFA) framework fuses a regressor and a classifier. It is derived based on the conditioned Bayes' rule, and by transforming the Support Vector Regression (SVR) and Support Vector Machines (SVM) outputs to probabilities, a serial probabilistic fusion scheme has been developed. This method yields better results than all the previous methods.

Suo et al. (2008) say that the key point in age estimation is defining the feature set essential to age perception. For that reason, they built a hierarchical face model for faces appearing at low, middle and high resolution.

Qi and Zhang (2009) developed an age classification system that automatically separates kid faces from adult faces in real time. The system consists of three steps: face

detection, face normalization and age classification. They use Independent Component Analysis (ICA) to extract local facial features and SVM to train the age classifier.

Geng and Smith-Miles (2009) propose an age estimation method based on multilinear subspace analysis where the aging images are organized in a third-order tensor without pre-assumptions.

Guo et al. (2009) investigated bio-inspired features for facial age estimation. First step is the extraction of biologically inspired features, then feature dimension reduction using PCA and statistical learning for age estimation, and the last step is the estimated age output using SVM.

Ricanek et al. (2009) developed the first multi-ethnic age estimator. They used Active Appearance Model (AAM) to capture aging features, Least Angle Regression (LAR) for dimensionality reduction and SVR for function modeling. The age estimation framework consists of five modules: face detection, face encoding, feature selection using LAR, model fitting using SVR and age estimation.

Long (2009) proposes a new framework where age is predicted based on the learned metric as opposed to Euclidean distance used in most research. Unlike the manifold learning, which is nonlinear, in this framework a full metric is learned and expressed as a linear transformation, which makes it easy to project novel data into it.

Research by Gao and Ai (2009) refers to the use of Gabor filters and fuzzy Linear Discriminant Analysis (LDA) method for the classification of humans in four groups: baby, child, adult and elderly. The paper gives a mathematical basis of belonging to groups.

Luu et al. (2009) present a new technique for age estimation that combines the AAM and SVM to improve the accuracy of age estimation.

Turaga, Biswas and Chellapa (2010) describe the role of geometric attributes on human face, described by a set of facial landmarks for age estimation. They also show that the landmark space can be interpreted as a Grassmann manifold.

Chen et al. (2010) propose age classification of people based on facial image into three groups: children, adults and the elderly. After face detection, face is extracted and 52 characteristic points are located. These characteristic points are used to build the AAM model. Texture characteristics are sent to the SVM to estimate the age group.

Luu et al. (2010) proposed an age estimation technique that combines holistic and local facial features. Holistic features are AAM linear encoding of each face, and local features are extracted using Local Ternary Patterns (LTP). They use these features to classify faces into one of two age groups.

Zhang and Yeung (2010) proposed a multi-task warped Gaussian process (MTWGP) based on a variant of the Gaussian process called warped gaussian process. As authors state, unlike previous age estimation methods which need to specify the form of the regression functions or determine many parameters in the functions, the form of the regression functions in MTWGP is implicitly defined by the kernel function and all its model parameters can be learned from data automatically.

The most accurate algorithm up to date is the Enhanced Bio-Inspired Features (EBIF) by El Dib and El-Saban (2010). They extend the algorithm based on biologically inspired features (BIF) by adding fine detailed facial features, automatic initialization using Active Shape Model (ASM) and analyzing the complete facial area (including forehead).

Zhai, Qing and Ji-Xiang (2010) use improved non-negative matrix factorization algorithm to obtain a linear representation of data under non-negativity constraints. This algorithm avoids the singularity of within-class scatter matrix, and solves the small samples problem of LDA. For age prediction a Radial Basis Function (RBF) neural network has been used.

Duong et al. (2011) propose an advanced approach for age estimation by combining global and local characteristics derived from face images. AAM technique is used to construct the global characteristics of the face, while the local facial characteristics are obtained by Local Binary Patterns (LBP) coding, and SVR is used to train the initial and refined aging function.

Hajizadeh and Ebrahimnezhad (2011) propose a new algorithm to classify people according to age using Histogram of Oriented Gradients (HOG) for description of the face. Their method classifies subjects into four different age groups. The system is divided into three main parts: pre-processing, feature extraction and classification in the age group.

Lu and Tan (2011) proposed a novel method for age estimation by using multiple feature fusion via facial image analysis. They fused shape and texture information of the same image by the Canonical Correlation Analysis (CCA). Multiple linear regression function with a quadratic model was used for age estimation.

Selvi and Vani (2011) developed a system for age estimation of a person in three steps: face detection, extraction of characteristic points and age estimation. In their system age estimation is carried out using Multilinear Principal Component Analysis (MPCA).

Chang, Chen and Hung (2011) propose a new algorithm for age estimation - Ordinal Hyperplane Ranking (OHRank). The algorithm design is based on the relative order of age information. Each ordinal hyperplane separates all the facial images into two groups depending on the relative order and price sensitivity. They convert the age estimation problem into a series of K subproblems of binary classifications according to the ordering property.

Zhan, Li and Ogunbona (2011) extend the Non-negative Matrix Factorization (NMF) to learn a localized non-overlapping subspace representation for age estimation. One individual extended NMF subspace is learned for each age or age group. The age is estimated based on its reconstruction error after being projected into the learned age subspaces.

Chen et al. (2011) studied age estimation in a multiethnic environment using 39 combinations of four feature normalization methods, two simple feature fusion methods, two feature selection methods and three face representation methods (Gabor, AAM and LBP). The results of the research were that Gabor outperforms AAM and LBP with single face representation.

Nkengne, Tenenhaus and Fertil (2011) used a Supervised Facial Model (SFM) for age estimation. SFM combines shape model and texture model information. These two models are combined using Partial Least Squares Regression (PLS-R) to build the SFM.

Yang et al. (2011) proposed a feature fusion method to estimate the face age via SVR. SVR uses global features from AAM and local features from Gabor wavelet transformation. First they perform AAM on the image to get global features and shape-free image, then they do a Gabor wavelet transformation on that shape-free image and get Gabor feature representation. They employ PCA to reduce the dimensionality of Gabor representation. After that, they did a regression analysis on AAM features and Gabor features to estimate the age of a face.

Luo et al. (2011) in order to improve the accuracy of age estimation, proposed applying Multi-Label Learning to the age features. They treat each facial image as an example associated with the origin label as well as its neighbouring ages. Their results show that this approach outperforms single-label approaches.

Luu et al. (2011) propose a facial landmarks localization method which is more accurate and faster than AAM. Their Contourlet Appearance Model (CAM) doesn't only extract global information, but also local texture information using the Nonsubsampled Contourlet Transform (NSCT). They apply this model to face age estimation, and get more accurate results.

Liang et al. (2011) base their method on Gradient Location and Orientation Histogram (GLOH) descriptor and Multi-task Learning (MTL). They use GLOH to get age related local and spatial information, and MTL is used to select the most informative GLOH bins for age estimation. The corresponding weights are determined by ridge regression. The important thing in this approach is that it decreases the computation time because of reduced dimensionality.

Choi et al. (2011) proposed a new age estimation method combining global and local facial features and a hierarchical classifier. They propose a new extraction methods for wrinkles and skin and a new hierarchical method for age estimation. Region specific Gabor filter is used to extract wrinkle features, and LBP is used to

extract skin features. The hierarchical age estimation is designed to overlap the age classes to reduce classification errors of the boundary data.

Guo, Liou and Nguyen (2011) in their research combine shape feature, texture feature and frequency feature using Active Shape Model (ASM), Radon transform and Discrete Cosine Transform (DCT) to get robust hybrid features for classification. They use SVM for hierarchical classification.

Kohli, Prakash and Gupta (2011) use AAM and ensemble of classifiers for age estimation. They extract features from face images using AAM and then use a global classifier to distinguish between child/teen-hood and adulthood, before age estimation. After that they use different aging functions to model the aging process.

Li et al. (2012) propose a new method for age estimation based on ordinal discriminative feature learning. The idea is to preserve local manifold structure, but also to keep ordinal information among aging faces. They also try to remove redundant information from locality information and ordinal information by minimizing nonlinear correlation and rank correlation.

Cao et al. (2012) base their research on the premise that face images from the same age vary too much to estimate the age accurately. First step is that rank relationships of ages is learned from various face images, then the age is estimated based on those rank relationships and the age information of a reference set. They use Gabor features for face representation.

Lu and Tan (2012) propose an ordinary preserving manifold analysis for facial age estimation to find a low-dimensional subspace so that the samples with similar label values are projected to be as close as possible, and those with different label values as far as possible. They applied ordinary preserving manifolds to LDA and Multilinear Subspace Analysis (MFA).

Li et al. (2012) look at age estimation as a problem of distance-based ordinal regression, where facial aging trend can be discovered by a learned distance metric. Using this metric, both ordinal information of age groups and local geometry structure of target neighbourhoods can be preserved.

Gao (2012) bases his research on the fact that the high variability of aging patterns and the sparsity of available data present challenges for model training. Instead of training one global aging function, he trains an individual function for each person using a multi-task learning approach. He also proposes a similarity measure for clustering these aging functions. This algorithm is called Clustered Multi-task Support Vector Regression Machine.

Weng et al. (2012) propose a Multi-feature Ordinal Ranking (MFOR) method for facial age estimation. They formulate the problem of face age estimation as a group of ordinal ranking subproblems, and each of these subproblems derives a separating hyperplane to divide face instances into two groups: age larger than k and age not larger than k . They construct multiple ordinal ranking models, each corresponding to a feature set and aggregate them into an age estimator.

Li, Wang and Zhang (2012) propose a hierarchical framework for age estimation using weighted and OHRanked Sparse Representation-based Classification. Because of the similar aging features of humans of the same age, Sparse Representation-based Classification (SRC) can be used. Adding weights and OHRank improves the results of the algorithm.

Kou, Du and Zhai (2012) combine global and local facial features for age estimation. They extract these features by using Discrete Fourier Transform (DFT) and PCA.

Zhang (2012) uses Gaussian Process (GP) and T Process (TP) for age estimation. In this method, the form of regression function is defined by kernel function and almost all parameters can be learnt automatically from the data using efficient gradient methods.

Yin and Geng (2012) propose a Conditional Probability Neural Network (CPNN), a new label distribution learning algorithm for facial age estimation. CPNN is a three layer neural network whose inputs are both the target variable and conditional feature vector, and the output is the conditional probability of the target variable given the feature vector.

Nithyashri and Kulanthaivel (2012) use wavelet transform to extract facial features. Then they calculate the Euclidean distances between each of the features. These values become inputs into Adaptive Resonance Network (ART). The output of this network is the age group (child, adolescence, adult, senior adult).

Kilinc and Akgul (2013) use the fusion of geometric and textural features for facial age estimation. They first calculate the probability that face image belongs to each overlapping age group. After that, an interpolation based technique is used for final age estimation.

Ylioinas et al. (2013) use Kernel Density Estimate (KDE) for facial representation and SVR for age estimation. The important aspect of their algorithm is its computational lightness and algorithmic simplicity.

Chao, Liu and Ding (2013) combine distance metric learning and dimensionality reduction to explore the connection between facial features and age labels. They exploit the intrinsic ordinal relationship among human ages and overcome the data imbalance problem. Also, they present an age-oriented local regression to capture the aging process.

Gunay and Nabiyev (2013) propose a method based on Radon features. This method consists of four modules: preprocessing, feature extraction with radon transform, dimensionality reduction with PCA and age estimation with multiple linear regression.

Hu et al. (2013) propose a new discriminative feature Lie Algebrized Gaussians (LAG). They built LAG on Gaussian Mixture Models (GMM) and it can capture the aging manifold of an image by preserving the Lie group manifold structure information embedded in the feature space. The age estimation is done in two steps. The first step is to obtain an adaptive age group for each image, and the second step is to learn a local classifier from selected age classes to determine the final age.

An overview of state of the art research according to feature extraction method and age estimation method can be seen in Table 2.1. Methods used in state of the art age classification and estimation algorithms.

Table 2.1. Methods used in state of the art age classification and estimation algorithms

| Algorithm | Feature extraction method | Age estimation method | Estimation | Classification (Number of classes) |
|---|---|---|-------------------|---|
| Kwon and Lobo (1994) | Active Contour Model | - | No | Yes (3) |
| Horng, Lee and Chen (2001) | Sobel Edge Detector | Back Propagation Neural Networks | No | Yes (4) |
| Lanitis, Draganova and Christodoulou (2004) | Principal Component Analysis | Quadratic Function Shortest Distance Multilayer Perceptron Self-Organizing Map | Yes | No |
| Kalamani and Balasubramanie (2006) | Sobel Edge Detector | Fuzzy Lattice Neural Network | No | Yes (6) |
| Geng, Zhou and Smith-Miles (2007) | Active Appearance Model | Aging Pattern Subspace | Yes | No |
| Fu, Xu and Huang (2007) | Age Manifold | Regression Model Fitting | Yes | No |
| Ueki et al. (2008) | Class Distance Weighted Locality Preserving Projection | K Nearest Neighbours | Yes | No |
| Zhuang et al. (2008) | Patch-based Hidden Markov Model | Nearest Centroid Classifier | Yes | No |
| Shen and Ji (2008) | Sobel Edge Detector Haar-like Features | Gaussian Modeling Based Classification | No | Yes (2) |
| Ben, Su and Wu (2008) | Active Appearance Model | Linear Aging Function | Yes | No |
| Guo et al. (2008) | Age Manifold | Locally Adjusted Robust Regression Function | Yes | No |
| Guo et al. (2008) | Active Appearance Model | Support Vector Machine and Support Vector Regression | Yes | No |

| | | | | |
|------------------------------------|---|---|-----|---------|
| Suo et al. (2008) | Active Appearance Model and Hierarchical Face Model | Age Group Specific Linear Regression, Multi-layer Perceptron, Support Vector Regression and Logistic Regression | Yes | No |
| Qi and Zhang (2009) | Independent Component Analysis and Principal Component Analysis | Support Vector Machine | No | Yes (2) |
| Geng and Smith-Miles (2009) | Active Appearance Model | Multilinear Subspace Analysis | Yes | No |
| Guo et al. (2009) | Principal Component Analysis | Support Vector Machine and Support Vector Regression | Yes | No |
| Ricanek et al. (2009) | Active Appearance Model and Least Angle Regression | Support Vector Regression | Yes | No |
| Long (2009) | Active Appearance Model | Metric Learning | Yes | No |
| Gao and Ai (2009) | Gabor Feature | | | |
| Luu et al. (2009) | Active Appearance Model | Support Vector Machine and Support Vector Regression | Yes | No |
| Turaga, Biswas and Chellapa (2010) | Active Appearance Model | Support Vector Machine, Support Vector Regression and Ridge Regression | Yes | No |
| Chen et al. (2010) | | | | |
| Luu et al. (2010) | Active Appearance Model and Local Ternary Patterns | Support Vector Machine and Support Vector Regression | Yes | No |
| Zhang and Yeung (2010) | | Multi-Task Warped Gaussian Process | Yes | No |
| El Dib and Saban (2010) | Active Shape Model and Gabor | RBF Support Vector Regression | Yes | No |

| | | | | |
|--------------------------------------|--|---|-----|---------|
| | | and Support Vector Machine | | |
| Zhai, Qing and Ji-Xiang (2010) | Improved Non-negative Matrix Factorization | Radial Basis Function | Yes | No |
| Duong et al. (2011) | Active Appearance Model and Local Binary Pattern | Support Vector Regression | Yes | No |
| Hajizedah and Ebrahimnezhad (2011) | Histogram of Oriented Gradients | K Nearest Neighbour | No | Yes (4) |
| Lu and Tan (2011) | Manual and Canonical Correlation Analysis | Quadratic Function | Yes | No |
| Selvi and Vani (2011) | Gabor Filter | Multilinear Principal Component Analysis | Yes | No |
| Chang, Chen and Hung (2011) | Active Appearance Model | Ordinal Hyperplane Ranking | Yes | No |
| Zhan, Li and Ogunbona (2011) | Extended Non-negative Matrix Factorization | Coarse to fine | Yes | Yes (4) |
| Chen et al. (2011) | Gabor, Active Appearance Model, Principal Component Analysis | Support Vector Regression | Yes | No |
| Nkengne, Tenenhaus and Fertil (2011) | Partial Least Squares Regression | Supervised Facial Model | Yes | No |
| Yang et al. (2011) | Active Appearance Model and Gabor | Support Vector Regression | Yes | No |
| Luo et al. (2011) | Multi-task Learning | Multi-label - Support Vector Machine | Yes | No |
| Luu et al. (2011) | Contourlet Appearance Model | Support Vector Regression and Support Vector Machine with Radial Basis Function | Yes | No |

| | | | | |
|---------------------------------|--|--|-----|---------|
| Lian et al. (2011) | Gradient Location and Orientation Histogram | Support Vector Regression and Ridge regressor | Yes | No |
| Choi et al. (2011) | Manual, Gabor and Local Binary Pattern | Support Vector Machine and Support Vector Regression | Yes | No |
| Guo, Liou and Nguyen (2011) | Active Shape Model, Radon and Discrete Cosine Transform | Support Vector Machine and Support Vector Regression | Yes | No |
| Kohli, Prakash and Gupta (2011) | Active Appearance Model | Classifiers based on different dissimilarities | Yes | No |
| Li et al. (2012) | Preserving Locality and Ordinal Information | Ordinal Hyperplane Ranking | Yes | Yes (7) |
| Cao et al. (2012) | Gabor | Ranking Support Vector Machine | Yes | No |
| Lu and Tan (2012) | Linear Discriminant Analysis and Multilinear Subspace Analysis | Ordinary Preserving Manifold Analysis | Yes | No |
| Li et al. (2012) | Active Appearance Model | K Nearest Neighbour Regression Model | Yes | No |
| Gao (2012) | Active Appearance Model | Multi-task Support Vector Regression | Yes | No |
| Weng et al. (2012) | Active Appearance Model and Biologically Inspired Features | Multi-feature Ordinal Ranking | Yes | No |
| Li, Wang and Zhang (2012) | Active Appearance Model, Active Shape Model and Local Binary Pattern | Sparse Representation-based Classification | Yes | No |
| Kou, Du and Zhai (2012) | Discrete Fourier Transform and Principal Component Analysis | Global and Local Classification | Yes | No |

| | | | | |
|------------------------------------|--|---|-----|---------|
| Zhang (2012) | Active Appearance Model | Gaussian Process and T Process | Yes | No |
| Yin and Geng (2012) | Active Appearance Model | Conditional Probability Neural Network | Yes | No |
| Nithyashri and Kulanthaivel (2012) | Wavelet Transformation | Adaptive Resonance Network | No | Yes (4) |
| Kilinc and Akgul (2013) | Local Binary Pattern, Gabor | AdaBoost | Yes | No |
| Ylioinas et al. (2013) | Local Binary Pattern Kernel Density Estimate | Support Vector Regression | Yes | No |
| Chao, Liu and Ding (2013) | Active Appearance Model | K Nearest Neighbour - Support Vector Regression | Yes | No |
| Gunay and Nabiyevev (2013) | Radon and Principal Component Analysis | Multiple Linear Regression | Yes | No |
| Hu et al. (2013) | Lie Algebrized Gaussians | Improved Hierarchical Estimation | Yes | No |

According to literature review, changes in texture of human face (skin changes, wrinkles, skin elasticity etc.) are mostly influenced by external factors and are individual and change from person to person. Since in this research, global age estimation is considered, these changes are not appropriate. Also, in nowadays makeup has become an important factor in every day life for most women, and some men which influences the age estimation systems based on changes in texture of the face (Chen, Dantcheva and Ross, 2014). Other than this, more and more people use plastic surgery, botox or some other way to remove wrinkles and aging effects on their faces. This also influences age estimation systems. If an age estimation system with good accuracy, based only on facial shape changes, was to be developed, it would be a great improvement in this field.

Table 2.2. State of the art papers by sources

| Name of the source | No. of papers |
|--|----------------------|
| IC on Automatic Face and Gesture Recognition | 2 |
| IC on Computer Vision and Pattern Recognition | 3 |
| IC on Biometrics: Theory, Applications and Systems | 3 |
| IC on Image Processing | 2 |
| IC on Pattern Recognition | 3 |
| Transactions on Pattern Analysis and Machine Intelligence | 1 |
| IC on Intelligent Computing | 4 |
| Computer Society Conference on Computer Vision and Pattern Recognition | 3 |
| IC on Acoustics, Speech and Signal Processing | 4 |
| IC on Control, Automation, Robotics and Vision | 1 |
| IC on Machine Learning and Cybernetics | 1 |
| IC on Multimedia and Expo | 1 |
| Pattern Recognition | 2 |
| Transactions on Image Processing | 1 |
| Transactions on Systems, Man and Cybernetics | 2 |
| IC on Biometrics | 2 |
| IC on System Science and Engineering | 2 |
| ISNN | 2 |
| Multimedia Tools Application | 1 |

| | |
|--|---|
| Computer and Information Sciences | 1 |
| IC on Advanced Computing | 1 |
| IC on Image Analysis and Processing | 1 |
| IC on Intelligent Systems Design and Applications | 1 |
| IC on Recent Trends in Information Technology | 1 |
| IS on Biomedical Imaging: From Nano to Macro | 1 |
| International Workshop on Multimedia Signal Processing | 1 |
| Iranian Machine Vision and Image Processing | 1 |
| Pacific-Asia Conference on knowledge Discovery and Data Mining | 1 |
| Tamkang Journal of Science and Engineering | 1 |
| IC on Computer Graphics, Imaging and Visualization | 1 |
| Advances in Biometrics | 1 |
| Chinese Conference on Biometric Recognition | 4 |
| International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications | 1 |
| Multimedia Tools and Applications | 1 |

It can be seen in Table 2.2. State of the art papers by sources, that most of the papers on age estimation algorithms were published in conference proceedings. The conferences are international conferences from different parts of the world, specialized in image processing, computer vision and biometrics, which ensures the quality of research. Also, the largest number of research on age estimation has been published in 2011 as can be seen in Table 2.3. State of the art papers by year of publication.

Table 2.3. State of the art papers by year of publication

| Year of publication | No. of papers | Year of publication | No. of papers |
|----------------------------|----------------------|----------------------------|----------------------|
| 2013 | 5 | 2007 | 2 |
| 2012 | 11 | 2006 | 1 |
| 2011 | 15 | 2004 | 1 |
| 2010 | 6 | 2001 | 1 |
| 2009 | 7 | 1994 | 1 |
| 2008 | 7 | | |

2.1. Aging Face

Human face goes through different changes during growth and aging. One of the changes during a persons aging process is the change in craniofacial morphology (CM). Different craniofacial characteristics appear at different age and change during the aging process. One of the most important researches in this field is the one conducted by Farkas (1994) and Farkas and Munro (1987). Farkas (1994) took measurements from 57 facial landmarks. There were three kinds of measurements: projective measurements (defined as the shortest distance between two landmarks), tangential measurements (defined as the distance between two landmarks measured along skin surface) and angular measurements. In this research Farkas also identified landmarks that can be estimated from photographs of human faces. According to Ramanathan and Chellapa (2006) only projective measurements can be estimated accurately using photogrammetry of frontal face images. That is the reason this research uses these measurements as its basis.

According to Fu, Guo and Huang (2010) there are two main stages of facial changes. First stage is early growth and development of the face. In this stage the face size is getting larger during the craniofacial growth. Because of that growth, other facial features change also. Forehead slopes back, shrinks and releases spaces on the surface of the cranium. Eyes, ears, nose and mouth expand and cover interstitial spaces. Cheeks extend to larger areas and the chin becomes more protrusive. In this stage, the skin does not change much. The second stage is adult aging, where the most changes are skin aging and changes in texture. There are some changes in shape, but not as big as in the first stage.

Many studies related to CM of individuals from different aspects have been conducted. One of these studies was conducted by Coleman and Grover (2006) which refers to changes in the three-dimensional human face geometry during the aging process. Coleman and Grover conducted their research in terms of plastic surgery, in order to cancel the results of aging. They have focused on adults and unwanted changes on the face during the aging process. Some of the changes they stated, and according to which it is possible to discern the age of people are: reduction in the height of the face,

increase in the width and depth of the face, and facial features (nose, chin) become more distinct. They also divide the face into thirds and claim that human beauty is contained in the central part of the face. Ricanek (2008) researched the craniofacial characteristics of aging in terms of building more robust systems for face recognition in biometrics. He provides an overview of changes in facial structure and soft tissues over the years.

Geng, Yun and Smith-Miles (2010) in their work on automatic age estimation recognize two phases of facial aging. The first phase is the early years, defined as the years from birth to adulthood. At this stage, most of the changes are changes in craniofacial growth, as shown in Figure 2.1. Head shape changes caused by craniofacial growth (Geng, Yun and Smith-Miles, 2010):

- Beard becomes more prominent
- Cheeks are spread over a larger area
- Facial characteristics increase and cover the interstitial spaces
- Forehead falls backwards, reducing the free space on the surface of the skull




Figure 2.1. Head shape changes caused by craniofacial growth (Geng, Yun and Smith-Miles, 2010)

In addition to changes caused by craniofacial growth, minor skin changes occur (Geng, Yun and Smith-Miles, 2010):

- Facial hair become thicker and change color
- Skin color changes

The second phase of facial aging recognized by Geng, Yun and Smith-Miles (2010) is during adulthood. Adulthood is defined as the time from the end of growth to old age. The main changes in this stage are skin changes. The skin becomes thinner, darker, less

elastic and more leathery. Also, there are wrinkles, underchin, cheeks sag and bags under the eyes appear. But there is also some small craniofacial growth at this stage, mainly changes in the shape of the face, but most of craniofacial growth occurs at an early age of the individual, which can be seen in Figure 2.2 Craniofacial changes during growth and aging from Fg-net database.



Figure 2.2. Craniofacial changes during growth and aging from Fg-net database (Fg-net, 2014)

Nakai, Okakura and Arakawa (2010) and Okakura and Arakawa (2011) define five ways in which human face shape changes: the face becomes longer, eyebrow become thicker, eyes become thinner, nose becomes longer and ridge sharper and wings of nose become wider.

To summarize all this research, Table 2.4. Face shape changes caused by growth or aging, gives an overview of changes during growth and aging.

Table 2.4. Face shape changes caused by growth or aging

| Paper | Growth or aging | Change |
|---|-----------------|---|
| Fu, Guo and Huang (2010), Geng, Yun and Smith-Miles (2010) | growth | Forehead slopes back, shrinks and releases spaces on the surface of the cranium |
| Fu, Guo and Huang (2010), Geng, Yun and Smith-Miles (2010) | growth | Eyes, ears, nose and mouth expand and cover interstitial spaces |
| Fu, Guo and Huang (2010), Geng, Yun and Smith-Miles (2010) | growth | Cheeks extend to larger areas |
| Fu, Guo and Huang (2010), Geng, Yun and Smith-Miles (2010) | growth | Chin becomes more protrusive |

| | | |
|--|--------|---|
| Coleman and Grover (2006) | aging | Reduction in the height of the face |
| Coleman and Grover (2006) | aging | Increase in the width and depth of the face |
| Nakai, Okakura and Arakawa (2010), Okakura and Arakawa (2011) | growth | Face becomes longer |
| Nakai, Okakura and Arakawa (2010), Okakura and Arakawa (2011) | growth | Eyebrows become thicker |
| Nakai, Okakura and Arakawa (2010), Okakura and Arakawa (2011) | growth | Eyes become thinner |
| Nakai, Okakura and Arakawa (2010), Okakura and Arakawa (2011) | growth | Nose becomes longer |
| Nakai, Okakura and Arakawa (2010), Okakura and Arakawa (2011) | growth | Ridge becomes sharper |
| Nakai, Okakura and Arakawa (2010), Okakura and Arakawa (2011) | growth | Wings of nose become wider |

2.2. Types of Age

According to Geng, Yun and Smith-Miles (2010) there are several types of age:

- Chronological age is defined as the number of years a person has lived.
- Appearance age is the age information defined by appearance of the person.
- Perceived age is defined by people based on the appearance of the person.
- Estimated age is an age defined by the computer from the way person a looks.

Appearance age is usually very close to the chronological age. The objective of age estimation is that estimated age is as close to chronological or appearance age as possible.

2.3. Face Representation Models

There are a large number of different face representation models described in the introduction of this chapter. The most important models recognized in literature are (Geng, Yun and Smith-Miles, 2010), (Guo, Fu and Huang, 2009), (Fu, Guo and Huang, 2010), (Guo, 1994):

- Anthropometric Model,
- Active Appearance Model,
- Aging Pattern Subspace,
- Age Manifold,
- Biologically-Inspired Models.

2.3.1. *Anthropometric Model*

Facial Anthropometry is the science of measuring the size and proportions of the human face (Montagu, 1960).

The main idea of this model is to consult research related to craniofacial growth and development. Craniofacial research theory uses a mathematical model for description of head from birth to adulthood:

$$\Theta' = \Theta, R' = R(1 + k(1 - \cos\Theta)) \quad (1)$$

where Θ is the angle formed by the vertical axis, R is the radius of the head circle, k is a parameter which increases with time, and (R', Θ') circuit growth over time (Alley, 1998).

Farkas (1994) gave an overview of facial anthropometry. He defined facial anthropometric as measures taken from 57 characteristic points of the face taken over years. For age estimation, distances and ratios between characteristic points are commonly used, instead of using a mathematical model, because it is difficult to measure face profile on the two-dimensional face images (Fu, Guo and Huang, 2010).

Computations in this model are based on the craniofacial development theory. Changes in the appearance of face caused by growth are sufficient to categorize faces in several age groups. This model is suitable for a rough age estimation, but not for detailed classification (Fu, Xu and Huang, 2007). This is the main reason why Kwon and Lobo (1999) used wrinkle analysis to do the separation between young adults and seniors.

The anthropometric model is based on human face ratios, as shown on Figures 2.3 to 2.8.




Figure 2.3. Anthropometric ratio 1 on human face (Kwon and Lobo, 1999)




Figure 2.4. Anthropometric ratio 2 on human face (Kwon and Lobo, 1999)




Figure 2.5. Anthropometric ratio 3 on human face (Kwon and Lobo, 1999)




Figure 2.6. Anthropometric ratio 4 on human face (Kwon and Lobo, 1999)




Figure 2.7. Anthropometric ratio 5 on human face (Kwon and Lobo, 1999)




Figure 2.8. Anthropometric ratio 6 on human face (Kwon and Lobo, 1999)

In practice, anthropometric model can only be used for en face images for measuring facial geometry, because the distances and ratios are calculated from two-dimensional images of individuals that are sensitive to the positions (Fu, Guo and Huang, 2010). This model takes into account only geometry of face, without information about the texture.

2.3.2. *Active Appearance Model*

This model was proposed by Cootes, Edwards and Taylor (1998). Using facial images, statistical shape model and intensity model are learned separately. It is an algorithm for matching a statistical model of object shape and appearance to a new image. They are built during a training phase and by taking advantage of the least squares techniques, it can match to new images easily. The active appearance model is related to the active shape model. One disadvantage of active shape model is that it only uses shape constraints and does not take advantage of all the available information, especially the texture across the target object. This can be modeled using an active appearance model (Cootes, Edwards and Taylor, 1998).

In 2002 The AAM has been expanded to facial aging (Lanitis, Taylor and Cootes, 2002) suggesting an aging function defined by $age = f(b)$, to explain the variation in years. Age is the age of a person in the picture, b is a vector containing 50 parameters learned from AAM, and f is an aging function. The function defines the relationship between person's age and facial description parameters (Fu, Guo and Huang, 2010).

There are different forms of an aging function. Some examples of such functions are: quadratic aging function, linear aging function, cubic aging function and other.

Unlike anthropometric model, AAM is not oriented only to younger people, but deals with assessment of the age of people of all ages. It works in a way that takes into consideration not only the geometry of human face, but its texture also. In this way the age of a person can be estimated more accurately (Fu, Guo and Huang, 2010).

2.3.3. *Aging Pattern Subspace*

Instead of using every face image separately, aging pattern subspace model uses a sequence of facial aging images to model the aging process. This model was developed by Geng, Zhou and Smith-Miles (2007) and named Aging Pattern Subspace (AGES). Aging pattern is defined as a sequence of facial image of a person, sorted by time.

AGES works in two steps. The first step is a learning step, the second step is the age estimation step (Fu, Guo and Huang, 2010). In the first step, PCA is used to obtain the subspace representation. The difference from the standard PCA approach is that there are probably no images for each year for each aging pattern. So Expectation-Maximization (EM) is used as a method of iterative learning to minimize error in reconstruction. Error while reconstruction is defined as the difference between the available images of the face and the face reconstructed images (Fu, Guo and Huang, 2010). In the second step, the test face image needs to find a pattern of aging that suits that image, and the exact position of the year in the sample. Position year returned is the estimated age of a person in the test image (Fu, Guo and Huang, 2010).

To cope with incomplete data, due to difficulties in data collection, the aging pattern subspace models the sequence of a person's aging face images by learning subspaces. Age of the person being tested is determined by the projection in the subspace that can best reconstruct the face image (Fu, Xu and Huang, 2007).

Methods based on aging functions view age estimation as a classification problem: face images are data, and the goal is the age of a person in the picture. According to

Geng, Zhou and Smith-Miles (2007) aging pattern is a sequence of images sorted by age.

The emphasis of this model is the use of facial images of a person at different ages to define the aging pattern.

2.3.4. *Age Manifold*

Instead of learning the specific aging pattern for each person, it is possible to learn the common pattern of aging for more than one person at different ages. For each age, more than one facial image is used for age representation. Each person can have several face images at one age or in an age range (Fu, Guo and Huang, 2010). Therefore, this model is more flexible than AGES model, and it is much easier to collect a larger number of samples (facial images) and create a larger database.

This model uses a manifold embedding technique for learning a low-dimensional aging trend for many facial images of the same age. The only requirement of this model is that the sample size for learning is large enough so that embedded manifold can be taught with statistical sufficiency (Fu and Huang, 2008).

2.3.5. *Biologically-Inspired Models*

One of the most accurate age estimation algorithms to date is the EBIF algorithm based on biologically inspired models. The idea for biologically inspired model (BIF) came from human vision system. It showed good results in object recognition, so Guo et al. (2009) adapted this model to human age estimation based on face images. In object category recognition, prototypes are randomly selected from learning images and stored for template matching in S2 units (Guo, 1994). Guo et al. (2009) found that these features from pre-learned prototypes do not do well in age estimation, so they proposed a new model that has S1 and C1 units and a STD operation in C1 feature extraction (Guo, 1994).

BIF can deal with small changes in rotation, scale and image translation, so it is good to combine BIFs with manifold learning which is sensitive to image alignment (Guo, 1994).

2.3.6. Discussion

Each of the described models has its advantages and disadvantages. The overview of these characteristics can be seen in Table 2.5. Advantages and disadvantages of face representation models.

Table 2.5. Advantages and disadvantages of face representation models

| Model | Advantages | Disadvantages |
|-----------------------------|---|--|
| Anthropometric Model | Useful for age group classification Useful for younger people age estimation | Considers shape only Sensitive to head poses |
| Active Appearance Model | Considers shape and texture Deals with any age Robust against head poses | Has problems with incomplete data |
| Aging Pattern Subspace | Copes with incomplete data | Learning aging pattern for each person separately Hard to collect sufficient data |
| Age Manifold | More flexible Easier to collect data | Sensitive to image alignment |
| Biologically Inspired Model | Deals with changes in rotation, scale and alignment | |

Since anthropometric model is the only model that separates facial texture from facial ratios and is specialized in age classification of young people, this model is chosen for facial representation. Also, anthropometric model has not yet been evaluated on a large database so this is another contribution to the field of age estimation.

2.4. Aging Function Learning Methods

All of the research on age estimation can be grouped in (Guo et al., 2009): multiclass classification problem, regression problem and hybrid approach as a combination of these two (Figure 2.9. Classification of aging function learning method).




Figure 2.9. Classification of aging function learning methods

2.4.1. *Classification*

If age estimation is viewed as a classification problem each age label is treated as a single class (Fu, Guo and Huang, 2010). There are a large number of classifiers used in age estimation (Guo, 1994), (Choi et al., 2011):

- Artificial Neural Networks
- Support Vector Machines
- Nearest Neighbour
- Quadratic function
- Fuzzy Linear Discriminant Analysis
- Hierarchical estimation
- Support Vector Regression
- Multilayer Perceptron

Some of the researchers who have studied the problem of age estimation as a classification problem are Lanitis, Draganova and Christodoulou (2004), Guo et al. (2008), Ueki, Hayashida and Kobayashi (2006) and many other.

Age classification can further be divided into three approaches (Choi et al., 2011): Classification into age groups, single-level age estimation or hierarchical age estimation.

Age group classification is an approach that roughly estimates the age group. It is suitable for coarse classification, but it is not so good for detailed age estimation. Single-level and hierarchical age estimation focus on a detailed assessment of the age. Single-level age estimation finds age label in full dataset using a single estimator (Choi et al., 2011). Hierarchical age estimation is a rough-fine method for finding age labels in a smaller data set. First, age group in which an image belongs to is estimated. Then, based on the age group, detailed age is estimated. It improves the performance by considering the differences of age feature values according to age group. If there is an error in age group estimation step it transfers to detailed age estimation step (Choi et al., 2011).

2.4.2. *Regression*

There is another way in which age estimation can be observed. Age is a sequential set of values and the age estimation can be viewed as a regression problem (Fu, Guo and Huang, 2010).

Regressors used for age estimation (Guo, 1994):

- Quadratic Function
- Multiple Linear Regressor
- Support Vector Regression
- Semi-definite Programming Technique
- Expectation-Maximization
- Robust Multi-instance Regression
- Least Angle Regression

Age estimation as a regression problem has been researched by Lanitis, Draganova and Christodoulou (2004), Fu, Xu and Huang (2007), Yan et al. (2007), Zhou et al. (2005), Ni, Song and Yan (2009) and other.

2.4.3. *Hybrid*

The third view is a hybrid approach. This approach raises the question of which of the above approaches is better to estimate the age (Fu, Guo and Huang, 2010). Some of the researchers compared the above approaches on multiple databases. For example, Guo et al. (2008) concluded that SVM performs better on YGA database, and SVR performs better on Fg-net database. So there is no universal conclusion which is better because it depends on the database used.

Chapter 3: New Algorithm for Age Classification

There are a lot of problems in age classification and estimation and this is why it's such a challenging field of research. One major problem is the lack of quality images, and since the research involves minors, there is a problem of collecting photographs of minors. Other constraint is the correct facial landmark determination. There are various algorithms for facial landmark detection, but manual detection is still the most accurate.

All of the algorithms in previous research have two basic steps: feature extraction and classification. In the newly developed algorithm in this research, facial landmarks are manually selected and they serve as an input to the algorithm. Classification in the algorithm is done using multilayer perceptron. An overview of the algorithm is shown as a block diagram in Figure 3.1. Block diagram of the new algorithm.




Figure 3.1. Block diagram of the new algorithm

3.1. Face Representation

As explained in previous chapters, there are many face representation models used in literature. This research uses anthropometric model as a starting point. Next chapters

describe facial landmarks and ratios used for age classification and estimation in this algorithm.

3.1.1. *Facial Landmarks*

In order to calculate the ratios on human face, important facial landmarks need to be selected. Next six images show facial landmarks used for age estimation by different authors (Figure 3.2. to Figure 3.7.).



Figure 3.2. Landmark points as identified by Kleinberg and Siebert (2012)



Figure 3.3. Landmark points as identified by Takimoto et al. (2007)



Figure 3.4. Landmark points as identified by Txia and Huang (2009)



Figure 3.5. Landmark points as identified by Ramanathan and Chellapa (2006)



Figure 3.6. Landmark points as identified by Kostinger et al. (2011)



Figure 3.7. Landmark points as identified by Izadpanhi and Toygar (2012)

Based on literature analysed, 57 facial landmark points are defined. From all landmarks used in previous researches, landmarks used at least two times are selected as relevant in this research. All of these landmark points are shown in Figure 3.8. All landmark points as identified in literature. The abbreviations of the landmarks and their names are shown in Table 3.1. Landmark points identified in literature




Figure 3.8. All landmark points as identified in literature

Table 3.1. Landmark points identified in literature

| No. | Abbreviation | Description |
|-----|--------------|---|
| 1 | HH | Highest point of the head |
| 2 | MFL | Middle point of the forehead (left) |
| 3 | PHL | Most protruded point of the head (left) |
| 4 | MPL | Midpoint between PHL and LAML |
| 5 | LAML | Most lateral point at the angle of the mandible (left) |
| 6 | PMTL | Protrusion of the mental tubercle (left) |
| 7 | LMLC | Lowest point in the midline on the lower border of the chin |
| 8 | PMTR | Protrusion of the mental tubercle (right) |
| 9 | LAMR | Most lateral point at the angle of the mandible (right) |
| 10 | MLP | Midpoint between LAMR and PHR |

| | | |
|----|-------|---|
| 11 | PHR | Most protruded point of the head (right) |
| 12 | MFR | Middle point of the forehead (right) |
| 13 | LEBL | Most lateral point of the eyebrow (left) |
| 14 | HUMEL | Highest point on the upper margin of the midline portion of the eyebrow (left) |
| 15 | MBHML | Midpoint between HUMEL and MHEL (left) |
| 16 | MHEL | Medial hinge of the eyebrow (left) |
| 17 | LEL | Lateral hinge of the eyelid (left) |
| 18 | HEL | Highest point of the eyelid (left) |
| 19 | MPEL | Middle point of the eye (left) |
| 20 | LMLEL | Lowest point in the middle of the margin of the lower eyelid (left) |
| 21 | MEL | Medial hinge of the eyelid (left) |
| 22 | LPMEL | Lowest point in the middle of eyesocket (left) |
| 23 | MNS | Midpoint of the nasofrontal suture |
| 24 | FMN | Point of the nose where forehead meets the nose |
| 25 | MHER | Medial hinge of the eyebrow (right) |
| 26 | MBHMR | Midpoint between HUMER and MHER (right) |
| 27 | HUMER | Highest point on the upper margin of the midline portion of the eyebrow (right) |
| 28 | LEBR | Most lateral point of the eyebrow (right) |
| 29 | LER | Lateral hinge of the eyelid (right) |
| 30 | HER | Highest point of the eyelid (right) |
| 31 | MPER | Middle point of the eye (right) |
| 32 | LMLER | Lowest point in the middle of the margin of lower eyelid (right) |
| 33 | MER | Medial hinge of the eyelid (right) |
| 34 | LPMER | Lowest point in the middle of eyesocket (right) |
| 35 | NB | Nose bridge |
| 36 | MBNP | Midpoint between NB and PNT |
| 37 | MUNAL | Most upper point of the nasal ala (left) |
| 38 | MUNAR | Most upper point of the nasal ala (right) |
| 39 | MNAOL | Medial point of the nasal ala outer margin (left) |
| 40 | PNT | Most protruded point of the nasal tip |
| 41 | MNAOR | Medial point of the nasal ala outer margin (right) |
| 42 | LNAL | Most lateral point of the nasal ala (left) |
| 43 | LNAR | Most lateral point of the nasal ala (right) |
| 44 | LNL | Most lateral point of the nose (left) |
| 45 | LNAIL | Lowest lateral point of the nasal ala inner margin(left) |
| 46 | INTUL | Most inner point between the nose tip and upper lip |
| 47 | LNAIR | Lowest lateral point of the nasal ala inner margin(right) |
| 48 | LNR | Most lateral point of the nose (right) |
| 49 | HULR | Highest point of the upper lip (right) |

| | | |
|----|-------|---|
| 50 | MVUL | The midpoint of the vermillion border of the upper lip |
| 51 | HULL | Highest point of the upper lip (left) |
| 52 | LULML | Most lateral point where the upper and the lower lip meet (left) |
| 53 | MULLM | Midline point where upper and lower lip meet |
| 54 | LULMR | Most lateral point where the upper and the lower lip meet (right) |
| 55 | MLLL | Midpoint of the lower margin of the lower lip |
| 56 | MPLL | Midpoint of the pogonion and lower lip |
| 57 | AC | Most anterior point of the chin |

If changes that happen during facial growth and aging are taken into consideration, some of these landmarks can be omitted. The second step of purification occurs and new set of landmarks is defined (Figure 3.9. Landmark points used in this research and Table 3.2. Landmark points used in this research).



Figure 3.9. Landmark points used in this research

Table 3.2. Landmark points used in this research

| No. | Abbreviation | Description |
|-----|--------------|---|
| 1 | HH | Highest point of the head |
| 2 | MFL | Middle point of the forehead (left) |
| 3 | PHL | Most protruded point of the head (left) |
| 5 | LAML | Most lateral point at the angle of the mandible (left) |
| 7 | LMLC | Lowest point in the midline on the lower border of the chin |
| 9 | LAMR | Most lateral point at the angle of the mandible (right) |
| 11 | PHR | Most protruded point of the head (right) |
| 12 | MFR | Middle point of the forehead (right) |
| 17 | LEL | Lateral hinge of the eyelid (left) |
| 18 | HEL | Highest point of the eyelid (left) |
| 20 | LMLEL | Lowest point in the middle of the margin of the lower eyelid (left) |
| 21 | MEL | Medial hinge of the eyelid (left) |
| 24 | FMN | Point of the nose where forehead meets the nose |
| 29 | LER | Lateral hinge of the eyelid (right) |
| 30 | HER | Highest point of the eyelid (right) |
| 32 | LMLER | Lowest point in the middle of the margin of lower eyelid (right) |
| 33 | MER | Medial hinge of the eyelid (right) |
| 40 | PNT | Most protruded point of the nasal tip |
| 43 | LNAR | Most lateral point of the nasal ala (right) |
| 46 | INTUL | Most inner point between the nose tip and upper lip |
| 49 | HULR | Highest point of the upper lip (right) |
| 51 | HULL | Highest point of the upper lip (left) |
| 53 | MULLM | Midline point where upper and lower lip meet |
| 54 | LULMR | Most lateral point where the upper and the lower lip meet (right) |
| 55 | MLLL | Midpoint of the lower margin of the lower lip |
| 56 | MPLL | Midpoint of the pogonion and lower lip |

In the end, there are 26 facial landmarks used in this research. As it was mentioned earlier, facial landmarks are detected manually. To this end, a Python script that records mouse click positions was created.

Landmark_annotatation.py

```
import os
import Tkinter
import Image, ImageTk

root=Tkinter.Tk()
def button_click_exit_mainloop (event):
    event.widget.quit()
```

```

logfile=open("landmarks.csv", "a")
logfile.write("\n")

def callback(event):
    logfile=open("landmarks.csv", "a")
    logfile.write(str(event.x))
    logfile.write(";")
    logfile.write(str(event.y))
    logfile.write(";")

root.bind("<Button-2>", button_click_exit_mainloop)
root.bind("<Button-1>", callback)
root.geometry('+%d+%d' % (200,200))
dirlist=os.listdir(".")
old_label_image=None
for f in dirlist:
    try:
        logfile=open("landmarks.csv", "a")
        logfile.write(str(f))
        images=Image.open(f)
        root.geometry('%dx%d' % (images.size[0],images.size[1]))
        tkpi=ImageTk.PhotoImage(images)
        label_image=Tkinter.Label(root, image=tkpi)
        label_image.place(x=0,y=0,width=images.size[0],height=images.size[1])
        root.title(f)
        if old_label_image is not None:
            old_label_image.destroy()
        old_label_image=label_image
        root.mainloop()
    except:
        pass
logfile.close("landmarks.csv")

```

Input to the script is an image, and output is a file with coordinates of selected landmarks (landmarks.csv). This file is later saved as *fg-net_coordinates.xlsx*.

3.1.2. Ratios

After defining facial landmarks important for age estimation, important ratios need to be defined. In this research, important ratios are defined based on statistical analysis of correlation between all ratios on human face and age of a person.

In order to define these ratios, Euclidean distances between specific landmarks need to be calculated using the formula for Euclidean distance (2).

If A and B are points in two-dimensional space with coordinates (x_1, y_1) and (x_2, y_2) respectively, Euclidean distance between those two points is defined as

$$d(A, B) = \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2}. \quad (2)$$

All possible distances between facial landmarks (d_n) are calculated using the formula for number of diagonals of an n sided polygon and adding the number of sides of a polygon (Artrea, 2015):

$$d_n = \frac{n(n-3)}{2} + n \quad (3)$$

There are 325 possible distances on human face based on previously determined facial landmarks.

Next step is to define ratios important for age estimation. First, all possible ratios are calculated. Number of ratios is calculated by:

$$NPR \text{ (Number of Possible Ratios)} = \binom{n}{r} = \frac{n!}{r!(n-r)!} \quad (4)$$

where n is the number of elements (in this case 325) and r is number of classes (in this case 2).

Ratios are calculated using Python. Excel table with landmark position is given to the Python script and excel table with all possible ratios is the output. *Distances.py* script calculates distances between landmarks from *fg-net_coordinates.xlsx*.

Distances.py

```

from xlrd import open_workbook
from xlwt import Workbook
import math

wb = open_workbook('fg-net_coordinates.xlsx')
sheet=wb.sheet_by_index(0)
coordinates=[0]*52
distance=0
for row in range(2,sheet.nrows):
    for col in range(3,sheet.ncols):
        coordinates[col-3]=sheet.cell(row,col).value
print coordinates
for i in range(0,len(coordinates),2):
    for j in range(0,len(coordinates),2):
        if j>i:

```

```

        distance=math.sqrt(((coordinates[j]-coordinates[i])*(coordinates[j]-
coordinates[i]))+((coordinates[j+1]-coordinates[i+1])*(coordinates[j+1]-coordinates[i+1])))
        logfile=open("distances.csv", "a")
        logfile.write(str(distance) + ";")
        logfile.close()
    logfile=open("distances.csv", "a")
    logfile.write("\n")
    logfile.close()

```

Ratios.py script calculates the ratios from distances given in *distances.xlsx*.

Ratios.py

```

from xlrd import open_workbook
from xlwt import Workbook
import math

wb = open_workbook('distances.xlsx')
sheet=wb.sheet_by_index(1)
distances=[0]*326
ratio=0

for row in range(2,sheet.nrows):
    for col in range(1,sheet.ncols):
        distances[col-1]=float(sheet.cell(row,col).value)
    print distances
    for i in range(0,30):
        for j in range(0,len(distances)):
            if j>i:
                ratio=distances[i]/distances[j]
                logfile=open("ratios.csv", "a")
                logfile.write(str(ratio) + ";")
                logfile.close()
    logfile=open("ratios.csv", "a")
    logfile.write("\n")
    logfile.close()

```

The number of ratios is 52650. It is obvious that this is too large a number to do computations with, so only the important ratios need to be selected. These ratios are defined by using correlation between ratios and age of a person. First, scatter matrices are plotted (Figure 3.10. Correlation between years and ratio $d(\text{MFL}, \text{LAML})/d(\text{MFL}, \text{MFR})$ and Figure 3.11. Correlation between years and ratio $d(\text{MFL}, \text{PHR})/d(\text{PHL}, \text{LAML})$) using IBM SPSS Statistics software. It can be seen that correlation between ratios and age is non-linear.




Figure 3.10. Correlation between years and ratio $d(\text{MFL}, \text{LAML})/d(\text{MFL}, \text{MFR})$




Figure 3.11. Correlation between years and ratio $d(\text{MFL}, \text{PHR})/d(\text{PHL}, \text{LAML})$

In order to calculate the correlation between ratios and age, Spearman coefficient is used.

Table 3.3. Spearman coefficients

| Ratio | Spearman coefficient |
|--------------------------|----------------------|
| d(MFL, LAML)/d(MFL,PHR) | 0.653 |
| d(MFL, LAML)/d(MLF,MFR) | 0.669 |
| d(MFL, LAML)/d(PHL,PHR) | 0.612 |
| d(MFL, LAML)/d(PHL,MFR) | 0.639 |
| d(MFL,LMLC)/d(MFL,MFR) | 0.627 |
| d(MFL,PHR)/d(LMLC,LMLEL) | 0.609 |
| d(MFL,PHR)/d(LAMR,PHR) | 0.630 |
| d(MFL,PHR)/d(LAMR,MFR) | 0.641 |
| d(MFL,PHR)/d(PHL,LAML) | 0.667 |
| d(MFL,MFR)/d(LMLC,LMLEL) | 0.634 |
| d(MFL,MFR)/d(LMLC,MEL) | 0.608 |
| d(MFL,MFR)/d(LAMR,PHR) | 0.648 |
| d(MFL,MFR)/d(LAMR,MFR) | 0.667 |
| d(MFL,MFR)/d(PHR,MFR) | 0.659 |
| d(MFL,MFR)/d(PHL,LAML) | 0.682 |
| d(MFL,MFR)/d(LMLC,PHR) | 0.623 |
| d(MFL,MFR)/d(LMLC,MFR) | 0.625 |
| d(PHL,LAML)/d(PHL,PHR) | 0.629 |
| d(PHL,LAML)/d(PHL,MFR) | 0.656 |
| d(PHL,PHR)/d(LAMR,MFR) | 0.606 |
| d(PHL,MFR)/d(LAMR,MFR) | 0.641 |
| d(LMLC,LEL)/d(LEL,LER) | 0.626 |
| d(LMLC,LEL)/d(LEL,HER) | 0.602 |
| d(LMLC,LEL)/d(HEL,LER) | 0.625 |
| d(LMLC,LEL)/d(LMLEL,LER) | 0.601 |
| d(LMLC,LEL)/d(MEL,LER) | 0.633 |
| d(LMLC,HEL)/d(LEL,LER) | 0.608 |
| d(LMLC,HEL)/d(HEL,LER) | 0.609 |
| d(LMLC,HEL)/d(MEL,LER) | 0.609 |
| d(LMLC,LMLEL)/d(LEL,LER) | 0.646 |
| d(LMLC,LMLEL)/d(LEL,HER) | 0.630 |

| Ratio | Spearman coefficient |
|----------------------------|----------------------|
| d(LMLC,LMLEL)/d(LEL,LMLER) | 0.614 |
| d(LMLC,LMLEL)/d(LEL,MER) | 0.609 |
| d(LMLC,LMLEL)/d(HEL,LER) | 0.653 |
| d(LMLC,LMLEL)/d(HEL,HER) | 0.628 |
| d(LMLC,LMLEL)/d(HEL,LMLER) | 0.620 |
| d(LMLC,LMLEL)/d(LMLEL,LER) | 0.631 |
| d(LMLC,LMLEL)/d(LMLEL,HER) | 0.616 |
| d(LMLC,LMLEL)/d(MEL,LER) | 0.666 |
| d(LMLC,LMLEL)/d(MEL,HER) | 0.629 |
| d(LMLC,LMLEL)/d(MEL,LMLER) | 0.611 |
| d(LMLC,MEL)/d(LEL,LER) | 0.617 |
| d(LMLC,MEL)/d(LEL,HER) | 0.608 |
| d(LMLC,MEL)/d(HEL,LER) | 0.613 |
| d(LMLC,MEL)/d(MEL,LER) | 0.629 |
| d(LMLC,MEL)/d(MEL,HER) | 0.600 |
| d(LMLC,LER)/d(LEL,HER) | 0.610 |
| d(LMLC,HER)/d(LEL,HER) | 0.610 |
| d(LMLC,LMLER)/d(LEL,LER) | 0.619 |
| d(LMLC,LMLER)/d(LEL,HER) | 0.637 |
| d(LMLC,LMLER)/d(LEL,LMLER) | 0.620 |
| d(LMLC,LMLER)/d(LEL,MER) | 0.627 |
| d(LMLC,LMLER)/d(HEL,HER) | 0.606 |
| d(LMLC,LMLER)/d(LMLEL,HER) | 0.601 |
| d(LMLC,LMLER)/d(MEL,LER) | 0.605 |
| d(LMLC,LMLER)/d(MEL,HER) | 0.618 |
| d(LMLC,MER)/d(LEL,LER) | 0.614 |
| d(LMLC,MER)/d(LEL,HER) | 0.623 |
| d(LMLC,MER)/d(LEL,LMLER) | 0.605 |
| d(LMLC,MER)/d(LEL,MER) | 0.610 |
| d(LMLC,MER)/d(MEL,LER) | 0.605 |
| d(LMLC,MER)/d(MEL,HER) | 0.606 |

After calculation of Spearman coefficient, only 62 ratios with high correlation are selected for further calculation. Other ratios have medium or low correlation. The selected ratios and their correlation coefficient can be seen in Table 3.3. Spearman coefficients.

3.2. Classification

Classification in the algorithm is done with neural networks. More precisely, multi layer perceptron is used. Classification is done in IBM SPSS Statistics software.

An Artificial Neural Network (ANN) is an information processing paradigm that is inspired by the way biological nervous systems, such as the brain, process information. The key element of this paradigm is the structure of the information processing system. The system is composed of a large number of highly interconnected processing elements (neurones) working in unison to solve specific problems (Neural Networks, 2015).

The most common type of artificial neural network consists of three layers of units (Neural Networks, 2015):

- Input unit represents the raw information that is fed into the network.
- Each hidden unit is determined by the activities of the input units and the weights on the connections between the input and the hidden units.
- Output units depend on the activity of the hidden units and the weights between the hidden and output units.

Dependent variable in this research is variable Class. This variable is predicted using 62 covariates (ratios defined in previous chapter). Covariates are rescaled using Standardized method. The distribution mean and standard deviation for each feature need to be calculated. Then the mean is subtracted from each covariate and values of each feature are divided by its standard deviation:

$$x' = \frac{x - \text{mean}}{s} \quad (5)$$

Where x is a starting covariate value, x' is a new covariate value, mean is a distribution mean value and s is the standard deviation of distribution.

*Multilayer Perceptron Network.

```
MLP Class (MLEVEL=N) WITH @100178 @2730 @2731 @2754 @30116 @3050 @30117 @3150
@3197 @31116 @31117 @31136 @5054 @54117 @98177 @98193 @98222 @99177 @100177
@100179 @100180 @100193 @100194 @100195 @100208 @100222 @100223 @100224 @101177
@101222 @105177
```

```

@105178 @105179 @105180 @106177 @106178 @106180 @2753 @2831 @30100 @3196 @31100
@31101 @5053 @53117 @98178 @98208 @99193 @99222 @100209 @101178 @101193 @101223
@103178 @104178 @105194 @105209 @105222 @105223 @106179 @106222 @106223
/RESCALE COVARIATE=STANDARDIZED
/PARTITION TRAINING=7 TESTING=3 HOLDOUT=0
/ARCHITECTURE AUTOMATIC=YES (MINUNITS=1 MAXUNITS=50)
/CRITERIA TRAINING=BATCH OPTIMIZATION=SCALEDCONJUGATE
LAMBDAINITIAL=0.0000005 SIGMAINITIAL=0.00005 INTERVALCENTER=0
INTERVALOFFSET=0.5 MEMSIZE=1000
/PRINT CPS NETWORKINFO SUMMARY CLASSIFICATION SOLUTION IMPORTANCE
/PLOT NETWORK ROC GAIN LIFT PREDICTED
/SAVE PREDVAL
/STOPPINGRULES ERRORSTEPS= 1 (DATA=AUTO) TRAININGTIMER=ON (MAXTIME=15)
MAXEPOCHS=AUTO ERRORCHANGE=1.0E-4 ERRORRATIO=0.0010
/MISSING USERMISSING=EXCLUDE .

```

In order to train the neural network, 70% (689) of cases are used. The other 30% (313) are used for testing. The cases were assigned randomly. All the cases were valid and none were excluded (Table 3.4. MLP case processing summary).

Table 3.4. MLP case processing summary

| | | N | Percent |
|----------|----------|------|---------|
| Sample | Training | 689 | 68,8% |
| | Testing | 313 | 31,2% |
| Valid | | 1002 | 100,0% |
| Excluded | | 0 | |
| Total | | 1002 | |

The network has 62 units in the input layer. There is only one hidden layer with 8 units. Output layer has 2 units. Activation function for hidden layers is Hyperbolic tangent. This function is defined as the ratio between the hyperbolic sine and the cosine functions or expanded as the ratio of the half-difference and half-sum of two exponential functions in the points x and $-x$ as follows (Karlik and Olgac, 2010):

$$\tanh(x) = \frac{\sinh(x)}{\cosh(x)} = \frac{e^x - e^{-x}}{e^x + e^{-x}} \quad (6)$$

Activation function for output layer is softmax (Shimodaira, 2015):

$$y_k = \frac{\exp(a_k)}{\sum_l \exp a_l}, a_k = \sum_{i=0}^d w_{ki} x_i \quad (7)$$

According to Karlik and Olgac (2010) hyperbolic tangent function has better recognition accuracy than other functions. The same results have been obtained in this research (Table 3.5. MLP information).

Table 3.5. MLP information

| | | | |
|-----------------|--|--------------------|-------|
| | Number of Units ^a | | 62 |
| | Rescaling Method for Covariates | Standardized | |
| | Number of Hidden Layers | | 1 |
| Hidden Layer(s) | Number of Units in Hidden Layer 1 ^a | | 8 |
| | Activation Function | Hyperbolic tangent | |
| | Dependent Variables | 1 | Manje |
| Output Layer | Number of Units | | 2 |
| | Activation Function | Softmax | |
| | Error Function | Cross-entropy | |

The results of the trained neural network can be seen in Table 3.6. Trained MLP results.

Table 3.6. Trained MLP results

| Sample | Observed | Predicted | | |
|----------|-----------------|-----------|-------|-----------------|
| | | 1 | 2 | Percent Correct |
| Training | 1 | 373 | 68 | 84,6% |
| | 2 | 53 | 195 | 78,6% |
| | Overall Percent | 61,8% | 38,2% | 82,4% |
| Testing | 1 | 164 | 35 | 82,4% |
| | 2 | 31 | 83 | 72,8% |
| | Overall Percent | 62,3% | 37,7% | 78,9% |

Chapter 4: Experimental Results

This chapter shows the results got after testing the algorithm on various datasets. First part of the chapter describes datasets used, and the second part of the chapter gives performance measurements.

4.1. Datasets

In order to create an accurate algorithm for age classification, appropriate datasets for training and testing are required. There is only one publicly available dataset that can be used for this research (Fg-net) (Lanitis, 2008) and it is described in detail. In order to develop a more accurate algorithm, a private database with facial images is created for algorithm training.

4.1.1. *Public Databases*

There is a large number of databases available for human age estimation research: Fg-net Aging Database (Fg-net, 2014), MORPH Database (Morph, 2014), YGA Database (Fu and Huang, 2008), WIT-DB Database (Ueki, Hayashida and Kobayashi, 2006), AI&R Asian Face Database (Fu and Zheng, 2006), Burt's Caucasian Face Database (Burt and Perrett, 1995), LHI Face Database (Yao, Yang and Zhu, 2007), HOIP Face Database (Nakano and Fukumi, 2005), Iranian Face Database (Bastanfard, Nik and Deshibi, 2007), Gallagher's Web-Collected Database (Gallagher and Chen, 2008), Ni's Web-Collected Database (Ni, Song and Yan, 2009) and PAL database (Pal database, 2014). An overview of these databases can be seen in Table 4.1. Face age databases.

Some of these databases are not appropriate for this research. YGA, WIT-DB, AI&R, and LHI database are databases of Asian subjects, and population for this research is caucasians. HOIP database has age labels distributed in 10 groups with five year intervals and Gallagher's Web-collected database has age labels in seven

categories, which is not accurate enough. Burt's Caucasian Face Database and MORPH database have subjects aged respectively, between 20 and 62 and between 16 and 77, which is not the age range interesting for this research.

The only two databases appropriate for this research are Fg-net database and Ni's web collected database.

Table 4.1. Face age databases

| Database name | No. of subjects | No. of images | Age | Race | Labels |
|----------------------|------------------------|----------------------|------------|----------------------------------|---------------|
| Fg-net | 82 | 1002 | 0-69 | Caucasoid | 70 categories |
| MORPH Public Release | 13000 | 55000 | 16-77 | Caucasoid, Negroid and Mongoloid | 62 categories |
| YGA | 1600 | 8000 | 0-93 | Mongoloid | - |
| WIT-DB | 5500 | 12008 | 3-85 | Mongoloid | 11 categories |
| AI&R | 17 | 34 | 22-61 | Mongoloid | - |
| BURT'S | 147 | 147 | 20-62 | Caucasoid | - |
| LHI | 8000 | 8000 | 9-89 | Mongoloid | - |
| HOIP | 300 | 306600 | 15-64 | - | 10 categories |
| IRANIAN | 616 | 3600 | 2-85 | Mongoloid | - |
| GALLAGHER'S | N/A | 28231 | - | - | 7 categories |
| NI'S | - | 219892 | 1-80 | - | - |
| PAL | 575 | - | 18-93 | Caucasoid, Negroid and Mongoloid | - |

Only Fg-net database will be used for algorithm testing because the majority of state of the art research use this database (Table 4.2. Face age database by number of papers). Ni's database will not be used for testing because there are no results to compare the algorithm with.

Table 4.2. Face age databases by number of papers

| Database | No. of papers |
|-------------------|----------------------|
| Fg-net | 60 |
| MORPH | 16 |
| PAL | 9 |
| Private databases | 17 |
| Other | 20 |

The Fg-net (Face and Gesture Recognition Research Network) ageing database (Fg-net, 2014) is a publicly available ageing database that has been extensively used for evaluation by researchers. The database is composed of 1,002 images of 82 subjects. There are 607 images of male subjects and 395 images of female subjects from 34 female subjects and 48 male subjects (Table 4.3. Subjects and images by sex in Fg-net database) in the age range 0–69 years (Ricanek et al.).

Table 4.3. Subjects and images by sex in Fg-net database

| | Number of subjects | Number of images |
|---------------|---------------------------|-------------------------|
| Female | 34 | 395 |
| Male | 48 | 607 |
| Total | 82 | 1002 |

The database predominantly includes images in the age range 0–18 years. The images are manually annotated with 68-landmark features and include information on image size, age, gender, presence of facial hair and eyeglasses, horizontal pose, and vertical pose. Many of the images are scanned from photographs and these images exhibit common noise errors associated with old photographs (Ricanek et al.).

Most subjects provided from 10 to 13 images of themselves, 6 subjects provided less than 10 images, and 20 subjects provided more than 13 images (Table 4.4. Images per person in Fg-net database).

Table 4.4. Images per person in Fg-net database

| | 6 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 18 |
|---------------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Male | 1 | 3 | 1 | 7 | 8 | 7 | 11 | 6 | 1 | 3 | 0 |
| Female | 0 | 0 | 1 | 3 | 7 | 7 | 6 | 3 | 3 | 3 | 1 |
| Total | 1 | 3 | 2 | 10 | 15 | 14 | 17 | 9 | 4 | 6 | 1 |

Regarding number of images per age, the largest number of images is of age of 18, the smallest number is of age 46 and above. Some ages don't have images associated with them (age 56, 57 59, 64, 65, 66 and 68) (Table 4.5. Images per age in Fg-net database).

Table 4.5. Images per age in Fg-net database

| Age | Number of images | Age | Number of images | Age | Number of images | Age | Number of images |
|------------|-------------------------|------------|-------------------------|------------|-------------------------|------------|-------------------------|
| 0 | 43 | 16 | 37 | 32 | 4 | 48 | 3 |
| 1 | 27 | 17 | 28 | 33 | 9 | 49 | 3 |
| 2 | 39 | 18 | 47 | 34 | 8 | 50 | 2 |
| 3 | 42 | 19 | 23 | 35 | 11 | 51 | 3 |
| 4 | 42 | 20 | 20 | 36 | 8 | 52 | 3 |
| 5 | 40 | 21 | 16 | 37 | 3 | 53 | 2 |
| 6 | 41 | 22 | 17 | 38 | 5 | 54 | 2 |
| 7 | 41 | 23 | 22 | 39 | 6 | 55 | 2 |
| 8 | 31 | 24 | 9 | 40 | 9 | 58 | 1 |
| 9 | 25 | 25 | 17 | 41 | 6 | 60 | 1 |
| 10 | 40 | 26 | 11 | 42 | 5 | 61 | 3 |
| 11 | 33 | 27 | 11 | 43 | 4 | 62 | 1 |
| 12 | 37 | 28 | 12 | 44 | 4 | 63 | 1 |
| 13 | 32 | 29 | 9 | 45 | 7 | 67 | 1 |
| 14 | 32 | 30 | 19 | 46 | 3 | 69 | 1 |
| 15 | 30 | 31 | 6 | 47 | 2 | | |

4.1.2. Private Database

Apart from the databases described in the previous chapter, private database for this research has been created. This database will be used for testing of the algorithm.

Since personal data is collected and used in this research, collection and processing of such data must be in accordance with the Croatian Law on Personal Data Protection. Some of the basic concepts recognized by this Law are (Narodne Novine, 2013):

- Personal information is any information relating to an identified natural person or a natural person who can be identified (respondent); a person who can be identified is the person whose identity can be determined directly or indirectly, in particular on the basis of one or more factors specific to his/her physical, physiological, mental, economic, cultural or social identity.
- Personal data processing is any operation or set of operations which is performed upon personal data, whether or not by automatic means, such as collection, recording, organization, storage, adaptation or alteration, retrieval, consultation, use, disclosure by transmission, dissemination or otherwise made available, alignment or combination, blocking, erasure or destruction, and the implementation of logical, mathematical and other operations on the data.
- Personal data collection is each set of personal data available by specific criteria, whether centralized, decentralized or dispersed on a functional or geographical basis and irrespective of whether it is contained in computer databases or other technical aids or manually.
- Personal data collection director is natural or legal person, public or other body which determines the purposes and means of processing personal data. Once the purpose and method of treatment is prescribed by law, the same law also determines the personal data collection director.
- User is a natural or legal person, public or other body which may use personal data to perform regular activities within its statutory activity.
- Subjects consent is freely given and specific manifestation of the will of the subjects with which he/she expresses consent to the processing of their personal data for specific purposes.

During data collection, respondent was aware of the fact that he/she is giving personal information, aware of the purpose for which the information is collected, and that they can withdraw their data at any time.

Respondent received a Privacy policy for review, which describes the duration of the Privacy policy, all the data collected, the purpose for which the data is collected, and whom to contact in case of any questions. In addition to this policy, all participants signed a statement of consent, with which they give their consent to use their personal data for this research, and confirm that they received for review the Privacy policy mentioned earlier. Since this research collects personal data of minors, their parents/guardians gave consent for the use of these data.

Images were collected during two years. Subjects were asked to provide images of themselves from childhood to adulthood. Every subject had to provide a minimum of 4 images. Images of all subjects have been collect according to Privacy policy described earlier, and all subjects signed the Declaration of conformity with which they stated that their images may be used for this research.

The basic information collected is shown in Table 4.6. Information collected for the private database.

Table 4.6. Information collected for the private database

| Field | Field definition |
|--------------|---------------------------|
| ID | Identifier of the subject |
| IM_ID | Image identifier |
| IM_AGE | Age of subject in image |
| DOB | Date of birth |
| DOA | Date of Acquisition |
| Gender | Male or female |

During data collection, images of 287 subjects have been collected, 151 female and 136 male subjects (Table 4.7. Subjects per sex collected for the private database). In total, 1655 images have been collected.

Table 4.7. Subjects per sex collected for the private database

| | Number of subjects |
|---------------|---------------------------|
| Female | 151 |
| Male | 136 |
| Total | 287 |

The subjects were asked to provide a minimum of four images. Most of the subjects provided five images, but some of them provided more than eleven (Table 4.8. Images per person collected for the private database). Only six subjects provided a minimum of four images.

Table 4.8. Images per person collected for the private database

| | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11+ |
|---------------|----------|----------|----------|----------|----------|----------|-----------|------------|
| Male | 6 | 101 | 9 | 12 | 5 | 2 | 1 | 0 |
| Female | 0 | 112 | 15 | 11 | 3 | 2 | 7 | 1 |
| Total | 6 | 213 | 24 | 33 | 8 | 4 | 8 | 1 |

Regarding number of images per age, the largest number of images is of age of twenty, the smallest number is of age 21 and above. All other age have similar number of images (Table 4.9. Images per age collected for the private database).

Table 4.9. Images per age collected for the private database

| Age | Number of images | Age | Number of images | Age | Number of images |
|------------|-------------------------|------------|-------------------------|------------|-------------------------|
| 0 | 21 | 9 | 67 | 18 | 87 |
| 1 | 81 | 10 | 77 | 19 | 74 |
| 2 | 131 | 11 | 48 | 20 | 136 |
| 3 | 78 | 12 | 87 | 21 | 1 |
| 4 | 56 | 13 | 49 | 22 | 8 |
| 5 | 73 | 14 | 93 | 23 | 3 |
| 6 | 84 | 15 | 56 | 24 | 2 |
| 7 | 99 | 16 | 113 | 25 | 4 |
| 8 | 55 | 17 | 72 | | |

All of the images provided cannot be used for age classification and estimation. Some of the images are of low quality, some have face images from different angles and some have bad lighting. So selection of these images needs to be done. The next step was to crop only faces from the images. After that, images with at least 100 pixels width and height were selected. After this selection 867 images from 242 subjects are left and 788 images have been left out (Table 4.10. Subjects per sex left in the private database after preprocessing).

Table 4.10. Subjects per sex left in the private database after preprocessing

| | Number of subjects left |
|---------------|-------------------------|
| Female | 121 |
| Male | 121 |
| Total | 242 |

Regarding number of images per age, the largest number of images is still of age of twenty and the smallest number is of age 21 and above (Table 4.11. Images per age left in the private database after preprocessing).

Table 4.11. Images per age left in the private database after preprocessing

| Age | Number of images | Age | Number of images | Age | Number of images |
|-----|------------------|-----|------------------|-----|------------------|
| 0 | 11 | 9 | 43 | 18 | 50 |
| 1 | 54 | 10 | 54 | 19 | 43 |
| 2 | 51 | 11 | 26 | 20 | 65 |
| 3 | 47 | 12 | 28 | 21 | 1 |
| 4 | 25 | 13 | 15 | 22 | 3 |
| 5 | 47 | 14 | 41 | 23 | 0 |
| 6 | 40 | 15 | 43 | 24 | 0 |
| 7 | 59 | 16 | 59 | 25 | 2 |
| 8 | 31 | 17 | 29 | | |

In order to apply the algorithm to this database, positions of characteristic points need to be determined. The positions are selected manually using a script explained earlier.

4.2. Performance Measurement

The performance is evaluated in two parts. First, the performance evaluation of classification algorithm is done. Next, the performance evaluation of age estimation algorithm is done. Fg-net database and private database are used for testing.

4.2.1. Age Classification

In order to assess the performance of the classifier different measures are used. Confusion matrix will be created and accuracy, precision, recall and specificity will be

calculated. Confusion matrix (Kohavi and Provost, 1998) contains information about actual and predicted classifications done by a classification system. Performance of such systems is commonly evaluated using the data in the matrix. The confusion matrix shows how algorithm makes predictions. The rows correspond to the actual class of the data. The columns correspond to the predicted values. The value of each of element in the matrix is the number of predictions made with the class corresponding to the column for examples with the correct value as represented by the row (Table 4.12. General confusion matrix (Lecture Notes, 2015)). The diagonal elements show the number of correct classifications made for each class, and the off-diagonal elements show the errors made (Lecture Notes, 2015).

Table 4.12. General confusion matrix (Lecture Notes, 2015)

| | | Predicted | |
|--------|---------|-----------|---------|
| | | Class 1 | Class 2 |
| Actual | Class 1 | TP | FN |
| | Class 2 | FP | TN |

True positives (TP) is the number of correct predictions that an instance is positive. True negative (TN) is the number of correct predictions that an instance is negative. False positives (FP) is the number of incorrect predictions that an instance is positive. False negatives (FN) is the number of incorrect predictions that an instance is negative (Lecture Notes, 2015).

Accuracy is the proportion of the total number of predictions that were correct (Lecture Notes, 2015):

$$Accuracy = \frac{TP+TN}{N} * 100\% \quad (8)$$

It is actually a measure of how often the classifier is correct.

Precision is the proportion of positive cases that were correctly identified:

$$Precision = \frac{TP}{TP+FP} * 100\% \quad (9)$$

Recall is the proportion of actual positive cases which are correctly identified (Lecture Notes, 2015):

$$Recall = \frac{TP}{TP+FN} * 100\% \quad (10)$$

Specificity is the proportion of negative cases that were correctly identified (Lecture Notes, 2015):

$$Specificity = \frac{TN}{FP+TN} * 100\% \quad (11)$$

If the algorithm is applied to samples from Fg-net database, confusion matrix is created based on results of the algorithm (Appendix A) and is as shown in Table 4.13. Confusion matrix for the new algorithm tested on the Fg-net database.

Table 4.13. Confusion matrix for the new algorithm tested on the Fg-net database

| | | Predicted | |
|--------|-------|-----------|-------|
| | | Child | Adult |
| Actual | Child | 537 | 103 |
| | Adult | 84 | 278 |

The child in this case is defined as a person from age of 0 to age 17. A person from age of 18 and above is defined as an adult.

The value of TP is 537, TN is 278, FP is 84 and FN is 103. Using these values, accuracy, precision, recall and specificity are calculated.

$$Accuracy = \frac{TP + TN}{N} * 100\% = \frac{537 + 278}{1002} * 100\% = 81.34\%$$

$$Precision = \frac{TP}{TP + FP} * 100\% = \frac{537}{537 + 84} * 100\% = 86.47\%$$

$$Recall = \frac{TP}{TP + FN} * 100\% = \frac{537}{537 + 103} * 100\% = 83.91\%$$

$$Specificity = \frac{TN}{FP + TN} * 100\% = \frac{278}{84 + 278} * 100\% = 76.80\%$$

The overall accuracy is **81.34%** which confirms the first hypothesis:

HYPOTHESIS 1

The newly developed algorithm distinguishes children from adults based on facial anthropometric ratios with an accuracy of more than 80% when used on the publicly available Fg-net database.

Table 4.14. Classification accuracy of the new algorithm by age tested on the Fg-net database gives a detailed accuracy for each age. The accuracy decreases when nearing the age 17 which is a threshold for classification. This is logical, because 17 is the threshold age, and closer the age of a person gets to the threshold, the accuracy decreases.

Table 4.14. Classification accuracy of the new algorithm by age tested on the Fg-net database

| Age | No. of photos | Correctly classified | Wrongly classified | Accuracy (%) |
|-----|---------------|----------------------|--------------------|--------------|
| 0 | 43 | 43 | 0 | 100.00 |
| 1 | 27 | 26 | 1 | 96.30 |
| 2 | 39 | 38 | 1 | 97.44 |
| 3 | 42 | 42 | 0 | 100.00 |
| 4 | 42 | 36 | 6 | 85.71 |
| 5 | 40 | 39 | 1 | 97.50 |
| 6 | 41 | 40 | 1 | 97.56 |
| 7 | 41 | 38 | 3 | 92.68 |
| 8 | 31 | 29 | 2 | 93.55 |
| 9 | 25 | 20 | 5 | 80.00 |
| 10 | 40 | 36 | 4 | 90.00 |
| 11 | 33 | 28 | 5 | 84.85 |
| 12 | 37 | 30 | 7 | 81.08 |
| 13 | 32 | 22 | 10 | 68.75 |
| 14 | 32 | 23 | 9 | 71.88 |
| 15 | 30 | 19 | 11 | 63.33 |
| 16 | 37 | 15 | 22 | 40.54 |
| 17 | 28 | 13 | 15 | 46.43 |
| 18 | 47 | 36 | 11 | 76.60 |
| 19 | 23 | 17 | 6 | 73.91 |
| 20 | 20 | 13 | 7 | 65.00 |
| 21 | 16 | 13 | 3 | 81.25 |

| | | | | |
|----|----|----|---|--------|
| 22 | 17 | 11 | 6 | 64.71 |
| 23 | 22 | 16 | 6 | 72.73 |
| 24 | 9 | 8 | 1 | 88.89 |
| 25 | 17 | 13 | 4 | 76.47 |
| 26 | 11 | 8 | 3 | 72.73 |
| 27 | 11 | 8 | 3 | 72.73 |
| 28 | 12 | 11 | 1 | 91.67 |
| 29 | 9 | 9 | 0 | 100.00 |
| 30 | 19 | 14 | 5 | 73.68 |
| 31 | 6 | 5 | 1 | 83.33 |
| 32 | 4 | 3 | 1 | 75.00 |
| 33 | 9 | 5 | 4 | 55.56 |
| 34 | 8 | 6 | 2 | 75.00 |
| 35 | 11 | 10 | 1 | 90.91 |
| 36 | 8 | 6 | 2 | 75.00 |
| 37 | 3 | 2 | 1 | 66.67 |
| 38 | 5 | 5 | 0 | 100.00 |
| 39 | 6 | 4 | 2 | 66.67 |
| 40 | 9 | 7 | 2 | 77.78 |
| 41 | 6 | 4 | 2 | 66.67 |
| 42 | 5 | 3 | 2 | 60.00 |
| 43 | 4 | 3 | 1 | 75.00 |
| 44 | 4 | 4 | 0 | 100.00 |
| 45 | 7 | 5 | 2 | 71.43 |
| 46 | 3 | 1 | 2 | 33.33 |
| 47 | 2 | 1 | 1 | 50.00 |
| 48 | 3 | 2 | 1 | 66.67 |
| 49 | 3 | 3 | 0 | 100.00 |
| 50 | 2 | 2 | 0 | 100.00 |
| 51 | 3 | 3 | 0 | 100.00 |
| 52 | 3 | 3 | 0 | 100.00 |
| 53 | 2 | 1 | 1 | 50.00 |
| 54 | 2 | 2 | 0 | 100.00 |
| 55 | 2 | 2 | 0 | 100.00 |
| 58 | 1 | 1 | 0 | 100.00 |
| 60 | 1 | 1 | 0 | 100.00 |
| 61 | 3 | 3 | 0 | 100.00 |
| 62 | 1 | 1 | 0 | 100.00 |
| 63 | 1 | 1 | 0 | 100.00 |
| 67 | 1 | 1 | 0 | 100.00 |
| 69 | 1 | 1 | 0 | 100.00 |

4.2.2. Age Estimation

One of the important aspects of age estimation problem is finding the best metric for assessing the performance of age estimation algorithm. Two metrics most often used in literature for quantifying the performance of age estimation algorithms are mean absolute error (MAE) and cumulative score (CS) (Geng, Zhou and Smith-Miles, 2007).

The MAE is defined as the average of the absolute errors between the estimated age labels and the chronological age labels (Fu, Guo and Huang, 2010)

$$MAE = \frac{SAE}{N} = \frac{\sum_{i=1}^N |x_i - \hat{x}_i|}{N} \quad (12)$$

where x_i is the chronological age, \hat{x}_i is the estimated age, SAE is the sum of the absolute errors and N is the number of test images (Hamilton, 1994).

MAE has two other variations: MAE per age and MAE per decade. Both of these variations will be used in this research. MAE per age measures the mean absolute error at each age, and MAE per decade computes mean absolute error for every ten years (Guo, 2012).

The CS metric is defined as the proportion of test images such that the absolute error is not higher than an integer j :

$$CS(j) = \frac{N_{e \leq j}}{N_x} * 100\% \quad (13)$$

where $N_{e \leq j}$ is the number of test images on which the absolute error in age estimation is within j years (Turaga, Biswas and Chellapa, 2010), (Chen et al., 2011).

New algorithm tested on Fg-net database

When algorithm is used on Fg-net database the general MAE is 6.67. Other than general MAE measure, MAE per age and MAE per decade are also important measures. Table 4.15. MAE per age results of the new algorithm tested on the Fg-net database gives an overview of MAE per age. The results of MAE per age measure are consistent

with theories given in literature that say that anthropometric ratios are more accurate for younger ages. All the algorithm results for Fg-net database can be seen in Appendix A.

Table 4.15. MAE per age results of the new algorithm tested on the Fg-net database

| Age | No.of images | MAE per age | Age | No.of images | MAE per age |
|-----|--------------|-------------|-----|--------------|-------------|
| 0 | 43 | 3.81 | 32 | 4 | 10.00 |
| 1 | 27 | 3.11 | 33 | 9 | 12.89 |
| 2 | 39 | 3.82 | 34 | 8 | 14.63 |
| 3 | 42 | 3.62 | 35 | 11 | 12.00 |
| 4 | 42 | 6.05 | 36 | 8 | 13.25 |
| 5 | 40 | 4.95 | 37 | 3 | 18.33 |
| 6 | 41 | 4.37 | 38 | 5 | 14.80 |
| 7 | 41 | 4.46 | 39 | 6 | 18.33 |
| 8 | 31 | 4.52 | 40 | 9 | 17.44 |
| 9 | 25 | 4.72 | 41 | 6 | 22.00 |
| 10 | 40 | 4.75 | 42 | 5 | 18.00 |
| 11 | 33 | 4.94 | 43 | 4 | 17.50 |
| 12 | 37 | 5.30 | 44 | 4 | 19.75 |
| 13 | 32 | 5.31 | 45 | 7 | 25.29 |
| 14 | 32 | 5.31 | 46 | 3 | 24.67 |
| 15 | 30 | 4.90 | 47 | 2 | 20.00 |
| 16 | 37 | 5.89 | 48 | 3 | 26.33 |
| 17 | 28 | 4.43 | 49 | 3 | 25.67 |
| 18 | 47 | 4.91 | 50 | 2 | 27.50 |
| 19 | 23 | 5.57 | 51 | 3 | 26.00 |
| 20 | 20 | 4.15 | 52 | 3 | 27.67 |
| 21 | 16 | 3.56 | 53 | 2 | 30.00 |
| 22 | 17 | 5.41 | 54 | 2 | 32.50 |
| 23 | 22 | 4.64 | 55 | 2 | 29.00 |
| 24 | 9 | 3.00 | 58 | 1 | 29.00 |
| 25 | 17 | 3.94 | 60 | 1 | 39.00 |
| 26 | 11 | 5.00 | 61 | 3 | 34.00 |
| 27 | 11 | 6.91 | 62 | 1 | 40.00 |
| 28 | 12 | 5.33 | 63 | 1 | 36.00 |
| 29 | 9 | 6.56 | 67 | 1 | 38.00 |
| 30 | 19 | 8.95 | 69 | 1 | 36.00 |
| 31 | 6 | 5.67 | | | |

An overview of MAE per decade is given in Table 4.16. MAE per decade results of the new algorithm tested on the Fg-net database. The acceptable MAE per decade is for first three decades, whereas the MAE per decade for ages 30 and above is too large.

Table 4.16. MAE per decade results of the new algorithm tested on the Fg-net database

| Age range | No. of images | MAE per decade |
|------------------|----------------------|-----------------------|
| 0-9 | 371 | 4.37 |
| 10-19 | 339 | 5.12 |
| 20-29 | 144 | 4.74 |
| 30-39 | 79 | 12.08 |
| 40-49 | 46 | 21.20 |
| 50-59 | 15 | 28.53 |
| 60-69 | 8 | 36.38 |

The other measure used in most of the literature on age estimation is cumulative score.

Cumulative score for error levels of 0 to 20 is shown in Table 4.17. CS results of the new algorithm tested on the Fg-net database and Figure 4.10. Cumulative score curve of the new algorithm tested on the Fg-net database

Table 4.17. CS results of the new algorithm tested on the Fg-net database

| Error level | No. of samples | Cumulative score (CS) | Error level | No. of samples | Cumulative score (CS) |
|--------------------|-----------------------|------------------------------|--------------------|-----------------------|------------------------------|
| 0 | 66 | 6.59 | 11 | 26 | |
| 1 | 116 | 18.16 | 12 | 18 | |
| 2 | 115 | | 13 | 16 | |
| 3 | 104 | | 14 | 15 | |
| 4 | 90 | | 15 | 12 | 90.12 |
| 5 | 91 | 58.08 | 16 | 11 | |
| 6 | 68 | | 17 | 10 | |
| 7 | 50 | | 18 | 7 | |
| 8 | 41 | | 19 | 9 | |
| 9 | 36 | | 20 | 4 | 94.21 |
| 10 | 39 | 81.44 | | | |




Figure 4.10. Cumulative score curve of the new algorithm tested on the Fg-net database

These results will be compared with the results of age estimation using an anthropometric model on Fg-netdatabase.

Anthropometric model tested on Fg-net database

In order to compare the existing algorithm with the anthropometric model, the anthropometric model has to be evaluated on the Fg-net database.

The six ratios used in anthropometric model are different ratios than those used in the new algorithm (Table 4.18. Face ratios used in anthropometric model).

Table 4.18. Face ratios used in anthropometric model

| Ratio name | Ratio formula |
|------------|---------------------|
| Ratio 1 | LEYE-REYE/EYE-NOSE |
| Ratio 2 | LEYE-REYE/EYE-LIP |
| Ratio 3 | EYE-NOSE/EYE-CHIN |
| Ratio 4 | EYE-NOSE/EYE-LIP |
| Ratio 5 | LEYE-REYE/EYE-CHIN |
| Ratio 6 | THEAD-CHIN/EYE-CHIN |

The general MAE for anthropometric model is **7.03**. Compared with MAE for the new algorithm where MAE is **6.67**, it can be seen that ratios in the new algorithm give better results. All the anthropometric model results for Fg-net database can be seen in Appendix B.

Table 4.19. Comparison of MAE per age results of the new algorithm and anthropometric model tested on the Fg-net database shows the values of MAE per age of anthropometric model (AM) in comparison to MAE per age of the new algorithm. In most cases, MAE per age of the new algorithm is better than MAE per age of AM. The cases where MAE per age of AM is better than MAE per age of the new algorithm are for age of 45 and above, where the number of samples is small.

Table 4.19. Comparison of MAE per age results of the new algorithm and anthropometric model tested on the Fg-net database

| Age | No.of images | MAE new algorithm | MAE AM | Age | No.of images | MAE new algorithm | MAE AM |
|-----|--------------|-------------------|--------|-----|--------------|-------------------|--------|
| 0 | 43 | 3.81 | 4.02 | 32 | 4 | 10.00 | 19.00 |
| 1 | 27 | 3.11 | 5.44 | 33 | 9 | 12.89 | 19.22 |
| 2 | 39 | 3.82 | 6.92 | 34 | 8 | 14.63 | 20.25 |
| 3 | 42 | 3.62 | 6.48 | 35 | 11 | 12.00 | 24.82 |
| 4 | 42 | 6.05 | 10.48 | 36 | 8 | 13.25 | 24.13 |
| 5 | 40 | 4.95 | 10.03 | 37 | 3 | 18.33 | 20.67 |
| 6 | 41 | 4.37 | 10.02 | 38 | 5 | 14.80 | 23.60 |
| 7 | 41 | 4.46 | 12.56 | 39 | 6 | 18.33 | 21.50 |
| 8 | 31 | 4.52 | 11.00 | 40 | 9 | 17.44 | 25.78 |
| 9 | 25 | 4.72 | 14.60 | 41 | 6 | 22.00 | 23.00 |
| 10 | 40 | 4.75 | 16.00 | 42 | 5 | 18.00 | 22.40 |
| 11 | 33 | 4.94 | 16.09 | 43 | 4 | 17.50 | 23.75 |
| 12 | 37 | 5.30 | 16.16 | 44 | 4 | 19.75 | 21.75 |
| 13 | 32 | 5.31 | 17.06 | 45 | 7 | 25.29 | 22.14 |
| 14 | 32 | 5.31 | 18.78 | 46 | 3 | 24.67 | 21.00 |
| 15 | 30 | 4.90 | 19.30 | 47 | 2 | 20.00 | 19.50 |
| 16 | 37 | 5.89 | 20.00 | 48 | 3 | 26.33 | 22.00 |
| 17 | 28 | 4.43 | 19.50 | 49 | 3 | 25.67 | 24.67 |
| 18 | 47 | 4.91 | 19.98 | 50 | 2 | 27.50 | 19.50 |
| 19 | 23 | 5.57 | 20.87 | 51 | 3 | 26.00 | 27.00 |
| 20 | 20 | 4.15 | 20.55 | 52 | 3 | 27.67 | 22.00 |

| | | | | | | | |
|----|----|------|-------|----|---|-------|-------|
| 21 | 16 | 3.56 | 20.81 | 53 | 2 | 30.00 | 22.50 |
| 22 | 17 | 5.41 | 19.47 | 54 | 2 | 32.50 | 15.00 |
| 23 | 22 | 4.64 | 22.50 | 55 | 2 | 29.00 | 25.50 |
| 24 | 9 | 3.00 | 22.33 | 58 | 1 | 29.00 | 29.00 |
| 25 | 17 | 3.94 | 22.41 | 60 | 1 | 39.00 | 39.00 |
| 26 | 11 | 5.00 | 22.00 | 61 | 3 | 34.00 | 23.67 |
| 27 | 11 | 6.91 | 20.45 | 62 | 1 | 40.00 | 40.00 |
| 28 | 12 | 5.33 | 20.67 | 63 | 1 | 36.00 | 36.00 |
| 29 | 9 | 6.56 | 26.33 | 67 | 1 | 38.00 | 38.00 |
| 30 | 19 | 8.95 | 22.53 | 69 | 1 | 36.00 | 36.00 |
| 31 | 6 | 5.67 | 24.67 | | | | |

In MAE per decade table, the MAE per decade of anthropometric model is better in cases where there is a small number of samples (Table 4.20. Comparison of MAE per decade results of the new algorithm and anthropometric model tested on the Fg-net database).

Table 4.20. Comparison of MAE per decade results of the new algorithm and anthropometric model tested on the Fg-net database

| Age range | No. of images | MAE new algorithm | MAE AM |
|-----------|---------------|-------------------|--------|
| 0-9 | 371 | 4.37 | 8.99 |
| 10-19 | 339 | 5.12 | 18.29 |
| 20-29 | 144 | 4.74 | 21.56 |
| 30-39 | 79 | 12.08 | 22.30 |
| 40-49 | 46 | 21.20 | 23.07 |
| 50-59 | 15 | 28.53 | 22.47 |
| 60-69 | 8 | 36.38 | 25.38 |

If the cumulative score measure for both algorithms is compared, the cumulative score of the new algorithm is better on every error level. Most importantly, cumulative score for error level 0 is **6.59** for the new algorithm and **0** for anthropometric model. This means that anthropometric model predicts the correct age in 0 cases and the new algorithm predicts the correct age in 66 cases. The comparison of cumulative score curves can be seen in Figure 4.11. Comparison of cumulative score curves of the new algorithm and anthropometric model tested on the Fg-net database.

Table 4.21. Comparison of CS results of the new algorithm and anthropometric model tested on the Fg-net database

| Error level | No. of samples New algorithm | Cumulative score (CS) new algorithm | No. of samples AM | Cumulative score (CS) AM |
|-------------|------------------------------------|--|-------------------------|--------------------------------|
| 0 | 66 | 6.59 | 0 | 0.00 |
| 1 | 182 | 18.16 | 1 | 0.10 |
| 5 | 582 | 58.08 | 155 | 15.47 |
| 10 | 816 | 81.44 | 289 | 28.84 |
| 15 | 903 | 90.12 | 439 | 43.81 |
| 20 | 944 | 94.21 | 653 | 65.17 |




Figure 4.11. Comparison of cumulative score curves of the new algorithm and anthropometric model tested on the Fg-net database

These results confirm the second hypothesis:

HYPOTHESIS 2

Usage of different facial anthropometric ratios than those used in existing anthropometric model, increases the accuracy of the algorithm when used for age estimation.

Private database

As addition to this research, a private database of images is created. If the new algorithm is applied on this database, MAE is 3.25. All the algorithm results for private database can be seen in Appendix C.

MAE per age and MAE per decade values can be seen in Table 4.22. MAE per age results of the new algorithm tested on the private database and Table 4.23. MAE per decade results of the new algorithm tested on the private database. The results are similar to results where algorithm was tested on Fg-net database.

Table 4.22. MAE per age results of the new algorithm tested on the private database

| Age | No.of images | MAE | Age | No.of images | MAE |
|-----|--------------|------|-----|--------------|------|
| 0 | 11 | 3.55 | 13 | 15 | 2.00 |
| 1 | 54 | 2.33 | 14 | 41 | 2.10 |
| 2 | 51 | 2.12 | 15 | 43 | 2.35 |
| 3 | 47 | 3.13 | 16 | 59 | 2.36 |
| 4 | 25 | 3.08 | 17 | 29 | 2.86 |
| 5 | 47 | 4.19 | 18 | 50 | 3.94 |
| 6 | 40 | 3.53 | 19 | 43 | 4.84 |
| 7 | 59 | 3.71 | 20 | 65 | 5.25 |
| 8 | 31 | 3.52 | 21 | 1 | 7.00 |
| 9 | 43 | 2.37 | 22 | 3 | 7.00 |
| 10 | 54 | 3.07 | 23 | 0 | - |
| 11 | 26 | 3.12 | 24 | 0 | - |
| 12 | 28 | 2.52 | 25 | 2 | 9.50 |

Table 4.23. MAE per decade results of the new algorithm tested on the private database

| Age range | No. of images | MAE |
|-----------|---------------|------|
| 0-9 | 408 | 3.10 |
| 10-19 | 388 | 2.99 |
| 20-29 | 71 | 5.46 |

The cumulative score values are listed in Table 4.24. CS results of the new algorithm tested on the private database. These values are better than values got

when algorithm was tested on the Fg-net database. The reason for that is that the private database was preprocessed, and all images from different angles and with bad resolution were excluded from the database. Also, the private database has images from age 0 to 25 which makes estimation and classification easier. The resulting curve can be seen in Figure 4.12. Cumulative score curve of the new algorithm tested on the private database.

Table 4.24. CS results of the new algorithm tested on the private database

| Error level | No. of samples | Cumulative score (CS) |
|-------------|----------------|-----------------------|
| 0 | 93 | 10.73 |
| 1 | 262 | 30.22 |
| 5 | 700 | 80.74 |
| 10 | 859 | 99.08 |
| 15 | 867 | 100.00 |
| 20 | 867 | 100.00 |




Figure 4.12. Cumulative score curve of the new algorithm tested on the private database

4.3. Comparison with State of the Art Algorithms

In order to position this algorithm in state of the art research, comparison with existing age classification and age estimation algorithms is done. Table 4.25. Current research results for age classification shows the current research results for age classification.

Table 4.25. Current research results for age classification

| Algorithm | Database used | Classes | Accuracy |
|------------------------------------|---|---|--|
| Mohan, Kumar and Krishna (2010) | Part of Fg-net and 500 face images from Google images | 16-25, 26-35, 36-45, 46-55, 56-65, 66-75, 76-85 | Fg-net– 94.1% Google images – 90.8% |
| Kwon and Lobo (1999) | 47 images | Babies, young adults and senior adults | Not reported |
| Hornng, Lee and Chen (2001) | 230 images | 0-2, 3-39, 40-59, 60+ | 81.58% |
| Nithyashri and Kulanthaivel (2012) | Fg-net | 0-12, 13-18, 19-59, 60+ | 94.28% |
| Zhou, Miller and Zhang (2011) | Fg-net MORPH | Youths and adults | 76% 86% |
| Zhan, Li and Ogunbona (2011) | Fg-net MORPH | 4 groups (0-19, 20-29, 30-39, 40-69) | 60.9% |
| | | 2 groups (0-10, 11+) | 87.1% |
| | | 2 groups (0-14, 15+) | 85.9% |
| | | 2 groups (0-18, 19+) | 85.3% |
| | | 2 groups (0-20, 21+) | 84.0% |
| | | 2 groups (0-30, 31+) | 86.3% |
| Qi and Zhang (2009) | 7443 images | Kids and adults | 90.46% |
| Hajizadeh and Ebrahimnezhad (2011) | Iranian Face Database | 0-15, 16-30, 31-50, 50+ | 87.03% |
| Li et al. (2012) | 5080 images from | 0-2, 3-7, 8-12, 13- | 48.5% |

| | | | |
|------------------------------------|-------------------|--|--------|
| | Flickr | 19, 20-36, 37-65, 66+ | |
| Kalamani and Balasubramanie (2006) | 250 images | 0-2, 3-12, 13-24, 25-40, 41-55, 56+ | 95% |
| Shen and Ji (2008) | 179 images | Baby and adult | 49.72% |
| Ramesha, Raja and Patnaik (2010) | 58 images | 0-30, 30-40, 40+ | 89.65% |
| Gunay and Nabiyevev (2008) | FERET +350 images | 10+-5, 20+-5, 30+-5, 40+-5, 50+-5, 60+-5 | 80% |

As it can be seen from Table 4.25. Current research results for age classification, none of the algorithms divide samples in children (age 0 to 17) and adults (age 18 and above). The most similar algorithms that divide samples in two classes and have testing results on Fg-net database are listed in Table 4.26. Research results for age classification comparable to this research. The most accurate algorithm is by Zhan and Ogunbona (2011) where the closest class definition is for class 1 (age 0 to 18) and class 2 (age 19 and above). The accuracy of that algorithm is 85.30%. If the algorithm from this research is tested on the same classes, its accuracy is 79.90%. But if the algorithm from this research is tested on the four classes defined in algorithm by Zhan and Ogunbona, the algorithm from this research has an accuracy of 71.80%, as opposed to Zhan and Ogunbone algorithm accuracy which is 60.90%.

Table 4.26. Research results for age classification comparable to this research

| Algorithm | Database used | Classes | Accuracy |
|-------------------------------|-----------------|--------------------------------------|----------|
| Zhou, Miller and Zhang (2011) | Fg-net | Youths and adults | 76% |
| Zhan, Li and Ogunbona (2011) | Fg-net MORPH | 4 groups (0-19, 20-29, 30-39, 40-69) | 60.9% |
| | | 2 groups (0-10, 11+) | 87.1% |
| | | 2 groups (0-14, 15+) | 85.9% |
| | | 2 groups (0-18, 19+) | 85.3% |
| | | 2 groups (0-20, | 84.0% |

| | | | |
|--|--|---------------------------------|-------|
| | | 21+) 2 groups (0-30, 31+) | 86.3% |
|--|--|---------------------------------|-------|

If the algorithm is tested for age estimation, the result is MAE of 6.67, and CS(0) of 6.59%, CS(1) of 18.16%, CS(5) of 58.08383234%, CS(10) of 81.44%, CS(15) of 90.12% and CS(20) of 94.21%.

The MAE and CS results of the state of the art algorithms can be seen in Table 4.27. Current research results for age estimation.

Table 4.27. Current research results for age estimation

| Algorithm | Abbreviation | MAE | CS (1) | CS (5) | CS (10) |
|---------------------------------|---------------------|------|--------|--------|---------|
| El Dib and Saban (2010) | EBIF | 3.17 | 58 | 82 | 90 |
| Lian et al. (2011) | MTGLOH | 3.44 | 20 | 78 | 97 |
| Chao, Liu and Ding (2013) | LSL-AOR | 4.11 | - | - | - |
| Luu et al. (2011) | CAM | 4.12 | 23 | 74 | 90 |
| Weng et al. (2012) | MFOR | 4.25 | 36 | 75 | 88 |
| Li, Wang and Zhang (2012) | Weighte OHRanked | 4.32 | 30 | 74 | 90 |
| Luu et al. (2009) | HIE | 4.33 | - | - | - |
| Kohli, Prakash and Gupta (2011) | ECDC | 4.35 | - | - | - |
| Gao (2012) | CMTSVR | 4.37 | 34 | 76 | 90 |
| Chang, Chen and Hung (2011) | OHRank | 4.48 | 38 | 74 | 88 |
| Li et al. (2012) | LDMR | 4.51 | - | - | - |
| Hu et al. (2013) | LAGF | 4.54 | 41 | 75 | 88 |
| Choi et al. (2011) | HC | 4.66 | 33 | 73 | 87 |
| Chen et al. (2013) | CA | 4.67 | - | 75 | - |
| Duong et al. (2011) | GLFF | 4.74 | - | - | - |
| Yin and Geng (2012) | CPNN | 4.76 | 33 | 75 | 88 |
| Guo et al. (2009) | BIF | 4.77 | 20 | 68 | 90 |
| Li et al. (2012) | PLO | 4.82 | 33 | 72 | 92 |
| Zhang and Yeung (2010) | MTWGP | 4.83 | 10 | 34 | 54 |
| Qin et al. (2007) | MHR | 4.87 | 30 | 64 | 82 |
| Xiao et al. (2009) | mKNN | 4.93 | 25 | 75 | 85 |
| Zhang and Yeung (2010) | WGP | 4.95 | 31 | 72 | 88 |
| Guo et al. (2008) | PFA | 4.97 | 28 | 75 | 88 |

| | | | | | |
|---|-----------------------|------|----|----|----|
| Luo et al. (2011) | ML-SVM+BIF | 5.04 | - | - | - |
| Kilinc and Akgul (2013) | OAG | 5.05 | - | - | - |
| Guo et al. (2008) | LARR | 5.07 | 26 | 68 | 88 |
| Long (2009) | Metric Learning + GPR | 5.08 | 20 | 67 | 87 |
| Ylioinas et al. (2013) | LBP KDE | 5.09 | - | - | - |
| Zhang (2012) | TP | 5.23 | 28 | 68 | 88 |
| Chang, Chen and Hung (2010) | RED-SVM | 5.24 | 26 | 60 | 78 |
| Yan et al. (2007) | BM | 5.33 | 18 | 64 | 85 |
| Yan et al. (2007) | RUN2 | 5.33 | 19 | 65 | 88 |
| Geng and Smith-Miles (2009) | MSA | 5.36 | - | - | - |
| Luo et al. (2011) | ML-SVM+LGBP | 5.37 | - | - | - |
| Zhang and Yeung (2010) | GP | 5.39 | 26 | 64 | 88 |
| Selvi and Vani (2011) | MPCA | 5.41 | - | - | - |
| Kou, Du and Zhai (2012) | Global+Local | 5.72 | - | - | - |
| Luo et al. (2011) | ML-SVM+PCA | 5.73 | - | - | - |
| Lu and Tan (2012) | FSTI | 5.75 | 14 | 58 | 84 |
| Yan et al. (2007) | RUN1 | 5.78 | 26 | 68 | 86 |
| Guo et al. (2008) | SVR | 5.91 | 22 | 69 | 89 |
| Suo et al. (2008) | AO graph | 5.97 | - | - | - |
| Geng, Zhou and Smith-Miles (2007) | KAGES | 6.18 | 28 | 63 | 80 |
| Gunay and Nabyev (2013) | Radon | 6.18 | - | - | - |
| Lanitis, Draganova and Christodoulou (2004) | QM | 6.55 | 13 | 49 | 76 |
| Luu et al. (2011) | AAM | 6.77 | - | - | - |
| Geng, Zhou and Smith-Miles (2007) | AGES | 6.77 | 26 | 64 | 84 |
| Ju and Wang (2009) | LFR | 6.85 | - | - | - |
| Lanitis, Draganova and Christodoulou (2004) | MLP | 6.98 | 9 | 32 | 59 |
| Dahlan, Mashohor, and Mumtazah (2013) | SGF | 7.15 | - | - | - |
| Guo et al. (2008) | SVM | 7.25 | 28 | 62 | 78 |

| | | | | | |
|---|--------|-------|----|----|----|
| Zhai, Qing and Ji-Xiang (2010) | INMF | 7.26 | 12 | 53 | 78 |
| Lanitis, Taylor and (1999) | WAS | 8.06 | 10 | 40 | 78 |
| Geng, Zhou and Zhang (2006) | HumanA | 8.13 | - | - | - |
| Ju and Wang (2009) | C4.5 | 9.34 | 18 | 48 | 68 |
| Ju and Wang (2009) | BP | 11.85 | 12 | 34 | 56 |
| Lanitis, Draganova and Christodoulou (2004) | AAS | 14.83 | 8 | 35 | 52 |

If the algorithms are compared by MAE, there are many algorithm that yield better results than the algorithm from this research (Table 4.28. Comparison of state of the art research results for age estimation with the new algorithm results), but the difference is that they all take into consideration not only facial anthropometry, but also wrinkles and skin changes, all of which can be changed with a little makeup or corrective surgery.

Table 4.28. Comparison of state of the art research results for age estimation with the new algorithm results

| Abbreviation | MAE | Abbreviation | MAE |
|------------------|------|---------------|------|
| EBIF | 3.17 | RED-SVM | 5.24 |
| MTGLOH | 3.44 | BM | 5.33 |
| LSL-AOR | 4.11 | RUN2 | 5.33 |
| CAM | 4.12 | MSA | 5.36 |
| MFOR | 4.25 | ML-SVM+LGBP | 5.37 |
| Weighte OHRanked | 4.32 | GP | 5.39 |
| HIE | 4.33 | MPCA | 5.41 |
| ECDC | 4.35 | Global+Local | 5.72 |
| CMTSVR | 4.37 | ML-SVM+PCA | 5.73 |
| OHRank | 4.48 | FSTI | 5.75 |
| LDMR | 4.51 | RUN1 | 5.78 |
| LAGF | 4.54 | SVR | 5.91 |
| HC | 4.66 | AO graph | 5.97 |
| CA | 4.67 | KAGES | 6.18 |
| GLFF | 4.74 | Radon | 6.18 |
| CPNN | 4.76 | QM | 6.55 |
| BIF | 4.77 | New algorithm | 6.67 |
| PLO | 4.82 | AAM | 6.77 |

| | |
|-----------------------|------|
| MTWGP | 4.83 |
| MHR | 4.87 |
| mKNN | 4.93 |
| WGP | 4.95 |
| PFA | 4.97 |
| ML-SVM+BIF | 5.04 |
| OAG | 5.05 |
| LARR | 5.07 |
| Metric Learning + GPR | 5.08 |
| LBPKDE | 5.09 |
| TP | 5.23 |

| | |
|--------|-------|
| AGES | 6.77 |
| LFR | 6.85 |
| MLP | 6.98 |
| SGF | 7.15 |
| SVM | 7.25 |
| INMF | 7.26 |
| WAS | 8.06 |
| HumanA | 8.13 |
| C4.5 | 9.34 |
| BP | 11.85 |
| AAS | 14.83 |

According to cumulative score values, the new algorithm falls somewhere in the middle of state of the art algorithms. The results of state of the art algorithms have been taken from published papers and have not been verified. In some of the algorithms, all images from Fg-net database haven't been used, so this increases their accuracy. The quality of some images from Fg-net database is not appropriate for computer vision, biometric recognition and age estimation (Figure 4.4. Example of image from Fg-net database not appropriate for age estimation).



Figure 4.4. Example of images from Fg-net database not appropriate for age estimation

Chapter 5: Application

Application of age estimation can be divided into several groups. Fu, Guo and Huang (2010) distinguish between applications of age estimation in: forensic art, electronic customer relationship management (eCRM), security control and surveillance monitoring, biometrics, entertainment and cosmetology.

In forensic art, age estimation is used mostly as age progression for suspects, victims and lost person identification (Mancusi). Age progression can predict a person's appearance across age and thus help in finding missing individuals (Ramanathan, Chellapa and Biswas, 2009). Another problem, described by Schmeling et al. (2006), is the problem of age estimation of unaccompanied minors. The problem arises when foreigners entering the country have no documents for their date of birth. They often make false statements about their age as to avoid being criminally prosecuted. Current practice is to physically examine immigrants, radiographic examination of the hand, radiographic examination of the clavicles and dental examination (Schmeling, 2006). Physical examination includes anthropometric measures such as height, weight, type of constitution and visible signs of sexual maturity. All of the above mentioned measures and practices are intrusive and require experts. One other solution for the problem of unaccompanied minors is the use of computer algorithm that will determine their age based on photographs of their face. There is also a growing problem of pedopornography. With Internet expansion, the problem of child pornography has increased and experts need to evaluate images of victims (Cattaneo et al., 2009). Age estimation can be used to determine the age of victims in images.

Reponen and Tapio (2003) give the definition of eCRM: „The eCRM or electronic customer relationship management encompasses all the CRM functions with the use of the net environment i.e., intranet, extranet and internet. Electronic CRM concerns all forms of managing relationships with customers making use of information technology (IT). ECRM is enterprises using IT to integrate internal organization resources and external "marketing" strategies to understand and fulfill their customers' needs. Comparing with traditional CRM, the integrated information for eCRM

intraorganizational collaboration can be more efficient for communication with customers. Age estimation in eCRM is used as a part of gathering information about customers to establish customer relations. Different age groups have different needs and preferences and that is where age estimation can be used (Fu, Guo and Huang, 2010).

The most widely spread usage of age estimation is in security control and surveillance monitoring. It can stop minors from entering bars and to prevent underage drinking. It can also prevent minors from buying tobacco products from vending machines. Age estimation can also prevent older people from entering some rides in amusement parks. Another very important thing is using age estimation for denying minors access to web sites for adults (Guo et al., 2008), (Lanitis, Draganova and Christodoulou, 2004), (Ramanathan, Chellapa and Biswas, 2009). Secure internet access control is closely related with human computer interaction. Age estimation can be used to determine the age of users to adjust the type of interaction to their age (Lanitis, Draganova and Christodoulou, 2004). Game levels could be adjusted according to user's age.

In biometrics, age estimation is used as a soft biometric characteristic to improve the performance of biometric systems. It can improve robustness of face recognition systems to time gap (Wang et al., 2006), (Lanitis, 2009) and the task of periodically updating large face databases with recent images could be skipped (Ramanathan, Chellapa and Biswas, 2009), (Lanitis, Draganova and Christodoulou, 2004), (Patterson et al., 2007).

Entertainment and cosmetology are other areas where age estimation is used. Very common effects in movies are aging and rejuvenating of actors, where age estimation and progression are utilized (Blanz and Vetter, 1999). Another usage of age estimation is in age-based retrieval of face images from different databases that can be used for creating e-photoalbums by age-range (Lanitis, Draganova and Christodoulou, 2004).

People have the tendency to want to look younger. Important thing in looking younger is rejuvenating of the face. Age estimation helps to predict the rejuvenating results (Fu et al., 2004).

Chapter 6: Conclusion

Human age classification and estimation from facial images is a growing field of research. Face images contain various information and this research uses two-dimensional face images to classify images to those from children (age 0 to 17) or adults (age 18 and above). Other than this, the research uses face images to estimate the age of a person.

The main objective of this research was to develop an algorithm for human age classification and estimation which can classify humans into children and adults. This new algorithm is based on the model proposed in this research. More specific objectives identified to achieve the main objective are to identify changes on the face that occur during growth and aging, to identify facial landmarks necessary for algorithm creation, to identify ratios needed to create a new age classification and estimation algorithm and to compare the new algorithm accuracy with the accuracy of existing algorithms.

This research gives answers to the three research questions defined at the beginning of this research.

What changes occur on human face during growth and aging?

Analysis of the state of the art research on facial changes during growth and aging gives an answer to this question. To this end, scientific methods of description, compilation, analysis, synthesis, generalization and specialization are used. The answer to this research question is given in Table 2.4. Face shape changes caused by growth or aging in Chapter 2.1. Aging Face.

Which facial landmarks are important for age classification and estimation?

In Chapter 3.1.1. Facial Landmarks, analysis of state of the art research on facial landmarks used for age classification and estimation is given. First, all of the state of the art algorithms are analysed and an overview of landmarks used in those algorithms is given. After that, landmarks that appear at least twice are selected. Selected landmarks are combined with changes that happen on human face during growth and aging, and a

set of 26 landmarks used in this research is identified. These landmarks can be seen in Table 3.2. Landmark points used in this research.

Which facial ratios are important for age classification and estimation?

The answer to the last research question identified is given in Chapter 3.1.2. Ratios. First, all Euclidean distances between 26 facial landmarks identified are calculated. There are 325 possible distances. After that, all ratios between those distances are calculated. The number of possible ratios is 52650. This is too large a number to do classification with, so the number needs to be reduced. The correlation between every ratio and age is nonlinear, so Spearman coefficient is calculated. Only ratios that have high correlation coefficient are used for age classification and estimation. This leaves 62 ratios. The answer to this research question is given in Table 3.3. Spearman coefficients.

Other than research questions there are two hypothesis that need to be confirmed.

The newly developed algorithm distinguishes children from adults based on facial anthropometric ratios with an accuracy of more than 80% when used on the publicly available Fg-net database.

The newly developed algorithm uses Multi Layer Perceptron for classification. The 62 ratios identified as an answer to the third research question are used as a basis for the algorithm. Algorithm performance measurements used to test the classification part of the algorithm are explained in Chapter 4.2.1. Age Classification. The accuracy of the algorithm is 81.38% which confirms the first hypothesis. The table with complete results can be seen in Appendix A.

Usage of different facial anthropometric ratios than those used in existing anthropometric model, increases the accuracy of the algorithm when used for age estimation.

In order to compare the results of the ratios from the new algorithm with the results of anthropometric model ratios for age estimation, the anthropometric model needs to be tested on the same database (Fg-net). The MAE value of the new algorithm tested on the Fg-net database is 6.67. The MAE value of the anthropometric model tested on the Fg-net database is 7.03. CS values of the new algorithm for error levels 0, 1, 5, 10, 15 and 20 are as follows: CS(0)=6.59%, CS(1)=18.16%, CS(5)=58.08%, CS(10)=81.44%,

CS(15)=90.12% and CS(20)=94.21%. CS values of the anthropometric model for error levels 0, 1, 5, 10, 15 and 20 are as follows: CS(0)=0%, CS(1)=0.10%, CS(5)=15.47%, CS(10)= 28.84%, CS(15)= 43.81% and CS(20)= 65.17%. These values confirm the second hypothesis. The table with complete results can be seen in Appendix B.

The scientific contribution of this research has been explained in Introduction and can be seen in systematization of knowledge on age classification and estimation, identification of facial landmarks relevant for age classification and estimation, using data mining to identify ratios important for age classification and estimation, creation of a new algorithm for age classification and evaluation of anthropometric model on a large database.

Other than scientific, this research has a social contribution also: determining the age of immigrants or asylum seekers in situations where there are no documents proving the age of the person, for websites where entrance is allowed only for persons older than age of 18, in order to improve the system for face recognition (most of them are sensitive to changes during aging), searching for missing persons over the years, in human-computer interaction based on age, for the purpose of predicting a persons aging, in the fight against pedophilia (removing images of minors from various portals or personal computers), etc. The possible application of this research is described in detail in Chapter 5 Application.

Future work will concentrate on improving the algorithm for both classification and estimation. The facial landmarks in this research have been marked manually. Future research will deal with automatic landmark detection and incorporating it in this algorithm. The private database will be extended and algorithm training will be done on a larger sample. Other than that, application of the algorithm will be further researched and algorithm will be modified to adhere to different fields of application.

Bibliography

1. ALLEY, T.R. (1998) *Social and Applied Aspects of Perceiving Faces*. Psychology Press
2. ARTREA (2015) Mnogokuti. Available from: http://www.artrea.com.hr/skola/Podsjetnik_Mnogokut.pdf [Accessed 5th March 2015]
3. BASTANFARD, A., NIK, M.A., DESHIBI, M.M. (2007) Iranian Face Database with Age, Pose and Expression. In *Proceedings of the International Conference on Machine Vision*. Islamabad, December 28th to December 29th 2007. IEEE. pp. 50-55
4. BEN, S., SU, G., WU, Y. (2008) A Two-Step Selective Region Ensemble for Facial Age Estimation. *Advanced Intelligent Computing Theories and Applications. With Aspects of Artificial Intelligence, Lecture Notes in Computer Science*. 5227. pp. 622-632
5. BLANZ, V., VETTER T. (1999) A Morphable Model for the Synthesis of 3D Faces. *Proceedings of the 26th annual conference on Computer graphics and interactive techniques*. Los Angeles, August 8th to August 13th 1999. pp. 187-194
6. BURT, D.M. and PERRETT, D.I. (1995) Perception of Age in Adult Caucasian Male Faces: Computer Graphic Manipulation of Shape and Colour Information. *Proceedings of the Royal Society of London Series B Biological Sciences*, 259 (1355). pp. 137-143
7. CAO, D., LEI, Z., ZHANG, Z., FENG, J., LI, S.Z. (2012) Human Age Estimation Using Ranking SVM. *Proceedings of the 7th Chinese conference on Biometric Recognition*. pp. 324-331
8. CATTANEO, C., RITZ-TIMME, S., GABRIEL, P., GIBELLI, D., GIUDICI, E., POPPA, P., NOHRDEN, D., ASSMANN, S., SCHMITT, R., GRANDI, M. (2009) The difficult issue of age assessment on pedo-pornographic material. *Forensic Science International*. 183. pp.21-24
9. CHANG, K.Y., CHEN, C.S., HUNG, Y.P. (2010) A Ranking Approach for Human Age Estimation Based on Face Images. *International Conference on Pattern Recognition*. Istanbul, August 23rd to August 26th. IEEE. pp. 3396-3399

10. CHANG, K.Y., CHEN, C.S., HUNG, Y.P. (2011) Ordinal Hyperplanes Ranker with Cost Sensitivities for Age Estimation. *IEEE Conference on Computer Vision and Pattern Recognition*. Providence, June 20th to June 25th 2011. IEEE. pp.585-592
11. CHAO, W.L., LIU, J.Z., DING, J.J. (2013) Facial Age Estimation based on Label-Sensitive learning and Age-Oriented Regression. *Pattern Recognition*. 46. pp. 628-641
12. CHEN, C., DANTCHEVA, A., ROSS, A. (2014) Impact of Facial Cosmetics on Automatic Gender and Age Estimation. *Proceedings of the 9th International Conference on Computer Vision Theory and Applications*. Lisbon, January 2014.
13. CHEN, C., YANG, W., WANG, Y., SHAN, S., RICANEK, K. (2011) Learning Gabor Features for Facial Age Estimation. *Biometric Recognition Lecture Notes in Computer Science*. 7098. pp. 204-213
14. CHEN, K., GONG, S., XIANG, T., LOY, C.C. (2013) Cumulative Attribute Space for Age and Crowd Density Estimation. *IEEE Conference on Computer Vision and Pattern Recognition*. Portland, June 23rd to June 28th 2013. IEEE. pp. 2467-2474
15. CHEN, Y.W., HAN, M.J., SONG, K.T., HO, Y.L. (2010) Image-Based Age-Group Classification Design using Facial Features. *International Conference on System Science and Engineering*. Taipei, July 1st to July 3rd 2010. IEEE. pp. 548-552
16. CHOI, S.E., LEE, Y.J., LEE, S.J., PARK, K.R., KIM, J. (2011) Age Estimation Using a Hierarchical Classifier Based on Global and Local Facial Features. *Pattern recognition*. 44 (6). pp. 1261-1281
17. COLEMAN, S.R., GROVER, R. (2006) The Anatomy of the Aging Face: Volume Loss and Changes in 3-Dimensional Topography. *Aesthetic surgery journal*. January/February 2006. pp. 4-9
18. COOTES, T.F., EDWARDS, G.J., TAYLOR C.J. (1998) Active Appearance Models. *Proceedings of European Conference on Computer Vision*. 2. Springer. pp. 484-498
19. CRESWELL, J.W. (2008) *Research Design: Qualitative, quantitative and mixed methods approaches, Third Edition*, Sage Publications

20. DAHLAN, H.A., MASHOHOR, S., MUMTAZAH, S. (2013) Age Estimation Using Specific Gabor Filter on Upper Facial Area. Proceedings of the Fourth International Conference on Signal and Image Processing, Lecture Notes in Electrical Engineering. 221. pp.629-638
21. DUONG, C.N., QUACH, K.G., LUU, K., LE, H.B. RICANEK K. (2011) Fine Tuning Age-estimation with Global and Local Facial Features. *The 36th International Conference on Acoustics, Speech and Signal Processing*. Prague, May 2011
22. EL DIB, M.Y., AL-SABAN, M. (2010) Human Age Estimation Using Enhanced Bio-inspired Features (EBIF). *International Conference on Image Processing*. Hong Kong, September 26th to September 29th 2010. IEEE. pp. 1589-1592
23. FACE AND EMOTION. Facial landmarks. Available from: <http://face-and-emotion.com/dataface/anatomy/landmarks.jsp>. [Accessed 13th February 2013]
24. FARKAS, L.G. (1994) *Anthropometry of the Head nad Face*. Raven Press
25. FARKAS, L.G. and MUNRO, I.R. (1987) *Anthropometric Facial Proportions in Medicine*. Charles C. Thomas Publisher, Springfield
26. Fg-net. Fg-net database. Available from: <http://www-prima.inrialpes.fr/FGnet/html/benchmarks.html>. [Accessed 13th February 2013]
27. Fg-net. The Fg-net Aging Database. Available from: <http://www-prima.inrialpes.fr/FGnet/html/benchmarks.html>. [Accessed 19th March 2014]
28. FU, Y. and HUANG, T.S. (2008) Human Age Estimation with Regression on Discriminative Aging Manifold. *IEEE Transactions on Multimedia*. 10 (4). pp. 578-584
29. FU, Y. and ZHENG, N.(2006) M-Face: An Appearance-Based Photorealistic Model for Multiple Facial Attributes Rendering. *IEEE Transactions on Circuits and Systems for Video technology*. 16 (7). pp. 830-842
30. FU, Y., GUO, G., HUANG, T.S. (2010) Age Synthesis and Estimation via Faces: A Survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*. 32 (11). pp. 1955-1976
31. FU, Y., XU, Y., HUANG, T.S. (2007) Estimating human age by manifold analysis of face pictures and regression on aging features. *International*

- Conference on Multimedia and Expo*. Beijing, July 2nd to July 5th 2007. IEEE. pp. 1383-1386
32. FU, Y., ZHENG, N., LIU, J., ZHANG, T. (2004) Facetransfer: A System Model of Facial Image Rendering. *Proceedings of IEEE Conference on System, Man and Cybernetics*. October 10th to October 13th 2004. IEEE. pp. 2180-2185
 33. GALLAGHER, A. and CHEN, T. (2008) Clothing Cosegmentation for Recognizing People. *Conference on Computer Vision and Pattern Recognition*. Anchorage, June 23rd to June 28th. IEEE. pp. 1-8
 34. GAO, F. and AI, H. (2009) Face Age Classification on Consumer Images with Gabor Feature and Fuzzy LDA Method, *Advances in Biometrics*. Proceedings of the Third International Conference on Biometrics. Alghero, June 2nd to June 5th 2009. pp 132-141
 35. GAO, P.X. (2012) Facial Age Estimation Using Clustered Multi-task Support Vector Regression Machine. *21st International Conference on Pattern Recognition*. Tsukuba, November 11th to November 15th 2012. IEEE. pp. 541-544
 36. GENG, X. and SMITH-MILES, K. (2009) Facial Age Estimation by Multilinear Subspace Analysis, *International conference on Acoustics, Speech and Signal Processing*. Taipei, April 19th to April 24th 2009. IEEE. pp. 865-868
 37. GENG, X., FU, Y., SMITH-MILES, K. (2010) Automatic Facial Age Estimation. *Pacific Rim International Conferences on Artificial Intelligence*. Daegu, August 30th to September 2nd 2010
 38. GENG, X., ZHOU, Z.H., SMITH-MILES, K. (2007) Automatic age estimation based on facial aging patterns. *IEEE Transactions on pattern analysis and machine intelligence*. 29(12). pp. 2234-2240
 39. GENG, X., ZHOU, Z.H., ZHANG, Y. (2006) Learning from Facial Aging Patterns for Automatic Age Estimation. *Proceedings of the ACM International Conference on Multimedia*. pp. 307-316
 40. GRD, P. (2013) Introduction to Human Age Estimation Using Face Images. *Research papers Faculty of Materials Science and Technology Slovak University of Technology in Trnava*. Special number. pp. 35-41

41. GUNAY, A. and NABIYEV, V.V. (2013) Age Estimation Based on Local Radon Features of Facial Images. *Computer and Information Sciences III*. pp. 183-190
42. GUO, G. (1994) Human Age Estimation and Sex Classification. *Video Analytics for Business Intelligence*. pp. 101-131
43. GUO, G., FU, Y., DYER, C.R., HUANG, T.S. (2008) A Probabilistic Fusion Approach to Human Age Prediction. *Computer Society Conference on Computer Vision and Pattern Recognition Workshops*.
44. GUO, G., FU, Y., DYER, C.R., HUANG, T.S. (2008) Image-based Human Age Estimation by Manifold Learning and Locally Adjusted Robust Regression. *IEEE Transactions on Image Processing*. 17 (7). pp. 1178-1188
45. GUO, G., FU, Y., HUANG, T.S., DYER, C. (2008) Locally Adjusted Robust Regression for Human Age Estimation. *Proceedings of IEEE Workshop Applications of Computer Vision*. Copper Mountain, January 7th to January 9th 2008, pp. 1-6
46. GUO, G., MU, G., Fu, Y., HUANG, T.S. (2009) Human Age Estimation Using Bio-inspired Features. *Conference on Computer Vision and Pattern Recognition*. Miami, June 20th to June 25th 2009. IEEE. pp. 112-119
47. GUO, J.M., LIOU, Y.M. NGUYEN, H.S. (2011) Human Face Age Estimation with Adaptive Hybrid Features. *Proceedings of 2011 International Conference on System Science and Engineering*. Macao, June 8th to June 10th 2011. pp. 55-58
48. HAJIZEDAH, M.A., EBRAHIMNEZHAD, H. (2011) Classification of Age Groups from Facial Image Using Histograms of Oriented Gradients. *7th Iranian Machine Vision and Image Processing*. Tehran, November 16th to November 17th 2011. IEEE. pp. 1-5
49. HAMILTON, J.D. (1994) *Time Series Analysis*. Princeton University Press
50. HORNG, W.B., LEE, C.P., CHEN, C.W. (2001) Classification of Age Groups Based on Facial Features. *Tamkang Journal of Science and Engineering*. 4 (3). pp. 183-192
51. HU, C., GONG, L., WANG, T., FENG, Q. (2013) Effective Human Age Estimation Using a Two-Stage Approach Based on Lie Algebrized Gaussians Feature. *Multimedia Tools and Applications*. Springer US. pp. 1-21

52. IZADPANAHI, S. and TOYGAR, O. (2012) Geometric Feature Based Age Classification Using Facial Images. *IET Conference on Image Processing*. London, July 3rd to July 4th 2012. IET. pp. 1-5
53. JU, C.H. and WANG, Y.H. (2009) Automatic Age Estimation Based on Local Feature of Face Image and Regression. *International Conference on Machine Learning and Cybernetics*. Baoding, July 12th to July 15th 2009. IEEE. pp. 885-888
54. KALAMANI, D. and BALASUBRAMANIE, P. (2006) Age Classification using Fuzzy Lattice Neural Network. *Proceedings of the Sixth International Conference on Intelligent Systems Design and Application*. 3. October 2006. pp. 225-230
55. KARLIK, B. And OLGAC A.V. (2010) Performance Analysis of Various Activation Functions in Generalized MLP Architectures of Neural Networks. *International Journal of Artificial Intelligence and Expert Systems (IJAE)*. 1 (4). pp. 111-122
56. KILINC, M. and AKGUL, Y.S. (2013) Automatic Human Age Estimation Using Overlapped Age Groups. *Computer Vision, Imaging and Computer Graphics. Theory and Application, Communications in Computer and Information Science*. 359. pp 313-325
57. KLEINBERG, K.F. and SIEBERT, J.P. (2012) A Study of Quantitative Comparisons of Photographs and Video Images Based on Landmark Derived Feature Vectors. *Forensic Science International*. 219 (1–3). pp. 248–258
58. KOHAVI, R. and PROVOST, F. (1998) Glossary of Terms. Editorial for the Special Issue on Applications of Machine Learning and the Knowledge Discovery Process. 30(2/3).
59. KOHLI, S., PRAKASH, S., GUPTA, P. (2011) Age Estimation Using Active Appearance Models and Ensemble of Classifiers with Dissimilarity-Based Classification. *Advanced Intelligent Computing, Lecture Notes in Computer Science*. 6838. pp. 327-334
60. KORUGA, P., BAČA, M., SCHATTEN, M., (2011) Analysis of Craniofacial Morphology Changes during Aging and their Connection with Facial Age Estimation. *Proceedings of the 33rd International Conference on Information Technology Interfaces*. Cavtat, June 27th to June 30th 2011. IEEE. pp.481-485

61. KOSTINGER, M., WOHLHART, P., ROTH, P.M., BISCHOF, H. (2011) Annotated Facial Landmarks in the Wild a Largescale Realworld Database for Facial Landmark Localization. *IEEE International Conference on Computer Vision Workshops*. Barcelona, November 6th to November 13th 2011. pp. 2144 - 2151
62. KOU, J., DU, J.X., ZHAI, C.M. (2012) Integration of Global and Local Feature for Age Estimation of Facial Images. *Intelligent Computing Theories and Applications, Lecture Notes in Computer Science*. (7390). pp 455-462
63. KULENOVIĆ, Z. and SLIŠKOVIĆ, M. Metodologija znanstvenoistraživačkog rada, Pomorski fakultet u Splitu. Online: <https://www.pfst.hr/uploads/MZIR-Predavanje5.pdf>
64. KWON, Y.H. and LOBO, N.V. (1999) Age Classification from Facial Images. *IEEE Computer Society Conference on Computer Vision and Pattern Recognition*. Seattle, June 21st to June 23rd. IEEE. pp. 762-767
65. LANITIS A., DRAGANOVA C., CHRISTODOULOU, C. (2004) Comparing Different Classifiers for Automatic Age Estimation. *IEEE Transactions on Systems, Man and Cybernetics – Part B: Cybernetics*. 34 (1). pp. 621-628
66. LANITIS, A. (2008) Comparative Evaluation of Automatic Age Progression Methodologies. *EURASIP Journal on Advances in Signal Processing*. 2008. pp. 1-10
67. LANITIS, A. (2009) Facial Biometric Templates and Aging: Problems and Challenges for Artificial Intelligence. *Proceedings of the Workshops of the 5th IFIP Conference on Artificial Intelligence Applications & Innovations*. pp. 142-149
68. LANITIS, A., TAYLOR, C., COOTES, T. (2002) Toward Automatic Simulation of Aging Effects on Face Images. *IEEE Transactions on Pattern Analysis and Machine Intelligence*. 24 (4). pp. 442-455
69. LANITIS, A., TAYLOR, C.J., COOTES T.F. (1999) Modeling the Process of Ageing in Face Images. *The Proceedings of the Seventh IEEE International Conference on Computer Vision*. Kerkyra, 1999. pp. 131-136

70. LECTURE NOTES. Precision and Recall. Available from: <http://www.cs.odu.edu/~mukka/cs495s13/Lecturenotes/Chapter5/recallprecision.pdf>. [Accessed 12th February 2015]
71. LI, C., LIU, Q., LIU, J., LU, H. (2012) Learning Distance Metric Regression for Facial Age Estimation. *21st International Conference on Pattern Recognition*. Tsukuba, November 11th to November 15th 2012. IEEE. pp. 2327-2330
72. LI, C., LIU, Q., LIU, J., LU, H. (2012) Learning Ordinal Discriminative Features for Age Estimation. *IEEE Conference on Computer Vision and Pattern Recognition*. Providence, June 16th to June 21st. IEEE. pp.2570-2577
73. LI, W., WANG, Y., ZHANG, Z. (2012) A Hierarchical Framework for Image-based Human Age Estimation by Weighted and OHRanked Sparse Representation-based Classification. *International conference on Biometrics*. New Delhi, March 29th to April 1st 2012. IEEE. pp. 19-25
74. LIAN, Y., LIU, L., XU, Y., XIANG, Y., ZOU, B. (2011) Multi-Task Gloh Feature Selection for Human Age Estimation, *18th IEEE Conference on Image Processing*. Brussels, September 11th to September 14th 2011. IEEE. pp. 565-568
75. LONG, Y. (2009) Human Age Estimation by Metric Learning for Regression Problems. *Sixth International Conference on Computer Graphics, Imaging and Visualization*. Tianjin, August 11th to August 14th 2009. IEEE. pp. 343-348
76. LU, J. and TAN Y.P. (2011) Fusing Shape and Texture Information for Facial Age Estimation. *IEEE International Conference on Acoustics, Speech and Signal Processing*. Prague, May 22nd to May 27th 2011. pp. 1477-1480
77. LU, J. and TAN Y.P. (2012) Ordinary Preserving Manifold Analysis for Human Age and Head Pose Estimation. *IEEE Transactions on Systems, Man and Cybernetics-Part C: Applications and Reviews*. 43 (2). pp. 249-258
78. LUO, X., PANG, X, MA, B., LIU, F. (2011) Age Estimation Using Multi-Label Learning. *Biometric Recognition, Lecture Notes in Computer Science*. 7098. pp. 221-228
79. LUU, K., BUI, T.D., SUEN, C.Y., RICANEK, K. JR. (2010) Combined Local and Holistic Facial Features for Age-Determination. *11th International Conference on Control, Automation, Robotics and Vision*. Singapore, December 7th to December 10th. IEEE. pp. 900-904

80. LUU, K., RICANEK, K. JR., BUI, T.D., SUEN, C.Y. (2009) Age Estimation using Active Appearance Models and Support Vector Machine Regression. *3rd International Conference on Biometrics: Theory, Applications, and Systems*. Washington, September 28th to September 30th 2009. IEEE. pp. 1-5
81. LUU, K., SESHADRI, K., SAVVIDES, M., BUI, T.D., SUEN, C.Y. (2011) Contourlet Appearance Model for Facial Age Estimation. *International Joint Conference on Biometrics*. Washington, October 11th to October 13th 2011. IEEE. pp. 1-8
82. MANCUSI S. Image Modification, Aging Progression and Age Regression
83. MEDICAL DICTIONARY. Anthropometry. Available from: <http://medical-dictionary.thefreedictionary.com/anthropometry>. [Accessed 12th February 2015]
84. MOHAN, M.C., KUMAR, V.V., KRISHNA, V.V. (2010) Novel Method of Adult Age Classification Using Linear Wavelet Transforms. *International Journal of Computer Science and Network Security*. 10 (3). pp. 61-68
85. MONTAGU, A. (1960) *Handbook of Anthropometry*.
86. MORPH. Morph Face Database. Available from: <http://www.faceaginggroup.com/morph/>. [Accessed 19th March 2014]
87. NAKAI, T., OKAKURA, T., ARAKAWA, K. (2010) Face Recognition Across Age Progression Using Block Matching Method. *International Symposium on Communications and Information Technologies*. Tokyo, October 26th to October 29th 2010. IEEE. pp. 620-625
88. NAKANO, M. and FUKUMI, M. (2005) Age and Gender Recognition Using Facial Edge Information. *Proceedings of the First World Congress of the International Federation for Systems Research: The New Roles of Systems Sciences For a Knowledge-based Society*. Kobe, November 14th to November 17th 2005. JAIST Press.
89. NARODNE NOVINE. Zakon o zaštiti osobnih podataka. Available from: <http://narodne-novine.nn.hr/clanci/sluzbeni/305952.html>. [Accessed 12th February 2013]
90. NEURAL NETWORKS. Neural networks. Available from: http://www.doc.ic.ac.uk/~nd/surprise_96/journal/vol4/cs11/report.html#Introduction to neural networks. [Accessed 12th February 2015]

91. NI, B., SONG, Z., YAN, S. (2009) Web Image Mining towards Universal Age Estimator. *Proceedings of the 17th ACM international conference on Multimedia*. Beijing, October 19th to October 24th 2009. pp. 85-94
92. NITHYASHRI, J. and KULANTHAIVEL, G. (2012) Classification of Human Age based on Neural Network Using Fg-net Aging Database and Wavelet. *IEEE Fourth International Conference on Advanced Computing*. Chennai, December 13th to December 15th 2012. pp. 1-5
93. NKENGNE, A., TENENHAUS, A., FERTIL, B. (2011) Age Prediction Using a Supervised Facial Model. *International Symposium on Biomedical Imaging: From Nano to Macro*. Chicago, March 30th to April 2nd 2011. IEEE. pp. 1183 - 1188
94. OKAKURA, T. And ARAKAWA, K. (2011) Face Authentication Across Age Progression Using Shifted Block Matching. *International Symposium on Intelligent Signal Processing and Communication Systems*. Chiang Mai, December 7th to December 9th 2011. IEEE. pp. 1-6
95. PAL. Pal database. Available from: <http://agingmind.utdallas.edu/facedb>. [Accessed 19th March 2014]
96. PATTERSON, E., SETHURAM, A., ALBERT, M., RICANEK, K., KING, M. (2007) Aspects of Age Variation in Facial Morphology Affecting Biometrics. *IEEE Conference on Biometrics: Theory, Applications and Systems*. Crystal City, September 27th to September 29th 2007. IEEE. pp. 1-6
97. QI, H. and ZHANG L. (2009) Age Classification System with ICA Based Local Facial Features. *Advances in Neural Networks, Lecture Notes in Computer Science*. 5552. pp. 763-772
98. QIN, T., ZHANG, X., WANG, D., LIU, T., LAI, W., LI, H. (2007) Ranking with Multiple Hyperplanes. *Proceedings of the 30th annual international ACM SIGIR conference on Research and development in information retrieval*. pp. 279-286
99. RAMANATHAN, N. and CHELLAPPA, R. (2006) Modeling Age Progression in Young Faces. *IEEE Computer Society Conference on Computer Vision and Pattern Recognition*. June 17th to June 22nd 2006. IEEE. pp. 387-394
100. REPONEN, T. (2003) *Information Technology-Enabled Global Customer Service*. Idea Group Publishing

101. RICANEK, K. JR. (2008) *Craniofacial Aging*. Wiley Handbook of Science and Technology for Homeland Security
102. RICANEK, K. JR., MAHALINGAM, G., ALBERT, A.M., VORDER BRUEGGE, R.W. () Human face ageing: a perspective analysis from anthropometry and biometrics. Book Chapter in *Age Factors in Biometric Processing* Edited by Michael Fairhurst
103. RICANEK, K. JR., WANG, Y., CHEN, C., SIMMONS, S.J. (2009) Generalized Multi-Ethnic Face Age-Estimation. *International Conference on Biometrics: Theory, Applications and Systems*. Washington, September 28th to September 30th 2009. IEEE. pp. 1-6
104. SCHMELING, A., REISINGER, W., GESERICK, G., OLZE, A. (2006) Age estimation of unaccompanied minors Part I. General considerations. *Forensic Science International*. 159. pp. 61-64
105. SCHOLARPEDIA. Facial Age Estimation. Available from: http://www.scholarpedia.org/article/Facial_Age_Estimation. [Accessed 13th February 2013]
106. SELVI, V.T. and VANI, K. (2011) Age Estimation System using MPCA. *International Conference on Recent Trends in Information Technology*. Chennai, June 3rd to June 5th 2011. IEEE. pp. 1055-1060
107. SHEN, L.L. and JI, Z. (2008) Modelling Geometric Features for Face Based Age Classification. *Proceedings of the Seventh International Conference on Machine Learning and Cybernetics*. Kunming, July 12th to July 15th 2008. IEEE. pp. 2927-2931
108. SHIMODAIRA, H. (2015) Single Layer Neural Networks. *Learning and Data Note*.
109. SUO, J., WU, T., ZHU, S., SHAN, S., CHEN, X., GAO, W. (2008) Design Sparse Features for Age Estimation using Hierarchical Face Model. *8th IEEE International Conference on Automatic Face & Gesture Recognition*. Amsterdam, September 17th to September 19th 2008. IEEE. pp. 1-6
110. TAKIMOTO, H., KUWANO, T., MITSUKURA, Y., FUKAI, H., FUKUM, M. (2007) Appearance Age Feature Extraction from Facial Image Based on Age Perception. *International Conference on Instrumentation, Control and*

- Information Technology*. Kagawa, September 17th to September 20th 2007. pp. 2813-2818
111. TKALEC VERČIĆ, A., SINČIĆ ĆORIĆ, D., POLOŠKI VOKIĆ N. (2010) *Priručnik za metodologiju istraživačkog rada*. M.E.P. d.o.o.
 112. TURAGA, P., BISWAS, S., CHELLAPA, R. (2010) The Role of Geometry in Age Estimation. *IEEE International Conference on Acoustics Speech and Signal Processing*. Dallas, March 14th to March 19th 2010. IEEE. pp. 946-949
 113. TXIA, J.D., and HUANG, C.L. (2009) Age Estimation Using AAM and Local Facial Features. *Fifth International Conference on Intelligent Information Hiding and Multimedia Signal Processing*. Kyoto, September 12th to September 14th 2009. IEEE. pp. 885- 888
 114. UEKI, K., HAYASHIDA, T., KOBAYASHI, T. (2006) Subspace-based Age Group classification Using Facial Images under Various Lighting Conditions. *Proceedings of IEEE Conference on Automatic Face and Gesture Recognition*. Southampton, April 2nd to April 6th 2006. pp.43-48
 115. UEKI, K., MIYA, M., OGAWA, T., KOBAYASHI, T. (2008) Class Distance Weighted Locality Preserving Projection for Automatic Age Estimation. *2nd IEEE International Conference on Biometrics: Theory, Applications and Systems*. Arlington, September 29th to October 1st 2008. IEEE. pp. 1-5
 116. WANG, J., SHANG, Y., SU, G., Lin, X. (2006) Age Simulation for Face Recognition. *Proceedings of International Conference on Pattern Recognition*. Hong Kong. pp. 913-916
 117. WENG, R., LU, J., YANG, G., TAN, Y.P. (2012) Multi-Feature Ordinal Ranking for Facial Age Estimation. *International Conference and Workshops on Automatic Face and Gesture Recognition*. Shanghai, April 22nd to April 26th 2013. IEEE. pp. 1-6
 118. XIAO, B., YANG, X., XU, Y., ZHA, H. (2009) Learning Distance Metric for Regression by Semidefinite Programming with Application to Human Age Estimation. *Proceedings of the ACM international conference on multimedia*. pp. 451-460

119. YAN, S., WANG, H., HUANG, T., YANG, Q., XIAOOU, X.T. (2007) Ranking with Uncertain Labels. *International Conference on Multimedia and Expo*. Beijing, July 2nd to July 5th 2007. IEEE. pp. 96-99
120. YAN, S., WANG, H., TANG, X., HUANG, T.S. (2007) Learning Auto-Structured Regressor from Uncertain Nonnegative Labels. *Proceedings of IEEE Conference on Computer Vision*. Rio de Janeiro, October 14th to October 21st 2007. IEEE. pp. 1-8
121. YANG, W., CHEN, C., RICANEK, K., SUN, C. (2011) Ensemble of Global and Local Features for Face Age Estimation. *Advances in Neural Networks, Lecture Notes in Computer Science*. 6676. pp. 251-259
122. YAO, B., YANG, X., ZHU, S.C. (2007) Introduction to a large scale general purpose ground truth dataset: methodology, annotation tool, and benchmarks. *Proceedings of the 6th international conference on Energy minimization methods in computer vision and pattern recognition*. pp. 169-183
123. YIN, C. and GENG X. (2012) Facial Age Estimation by Conditional Probability Neural Network. *Pattern Recognition Communications in Computer and Information Science*. 321. pp. 243-250
124. YLIOINAS, J., HADID, A., HONG, X., PIETIKAINEN, M. (2013) Age Estimation Using Local Binary Pattern Kernel Density Estimate. *International Conference on Image Analysis and Processing*. Naples, September 9th to September 13th 2013. Springer. pp. 141-150, 2013
125. ZHAI, C.M., QING Y., JI-XIANG, D. (2010) Age Estimation of Facial Images Based on an Improved Non-negative Matrix Factorization Algorithms. *Advanced Intelligent Computing Theories and Applications. With Aspects of Artificial Intelligence*. pp. 670-676
126. ZHAN, C., LI, W., OGUNBONA, P. (2011) Age Estimation Based on Extended Non-negative Matrix Factorization. *International Workshop on Multimedia Signal Processing*. Hangzhou, October 17th to October 19th 2011. pp. 1-6
127. ZHANG, Y. (2012) Age Estimation Using Bayesian Process. *New Frontiers in Applied Data Mining, Lecture Notes in Computer Science*. 7104. pp. 447-458

128. ZHANG, Y. and YEUNG, D.Y. (2010) Multi-task Warped Gaussian Process for Personalized Age Estimation, *IEEE Conference on Computer Vision and Pattern Recognition*. San Francisco, June 13th to June 18th 2010. IEEE. pp. 2622-2629
129. ZHOU, H., MILLER, P. and ZHANG, J. (2011) Age classification using Radon transform and entropy based scaling SVM. *Proceedings of the British Machine Vision Conference*. September 2011. pp. 1-12
130. ZHOU, S.K., GEORGESCU, B., ZHOU, X.S., COMANICIU, D. (2005) Image Based Regression Using Boosting method. *Proceedings of IEEE International Conference on Computer Vision*. October 17th to October 21st 2005. IEEE. pp. 541-548
131. ZHUANG, X., ZHOU, X., HASEGAWA-JOHNSON, M., HUANG, T. (2008) Face Age Estimation Using Patch-based Hidden Markov Model Supervectors. *International Conference on Pattern Recognition*. Tampa, December 8th to December 11th 2008. IEEE. pp. 1-4

APPENDIX A New algorithm results for Fg-net database

| Image ID | Real Age | Real Class | Estimated Class | Estimated Age |
|----------|----------|------------|-----------------|---------------|
| 13_0 | 0 | 1 | 1 | 1 |
| 15_0 | 0 | 1 | 1 | 0 |
| 19_0 | 0 | 1 | 1 | 5 |
| 22_0 | 0 | 1 | 1 | 3 |
| 23_0 | 0 | 1 | 1 | 5 |
| 24_0 | 0 | 1 | 1 | 7 |
| 25_0 | 0 | 1 | 1 | 2 |
| 26_0 | 0 | 1 | 1 | 1 |
| 30_0 | 0 | 1 | 1 | 8 |
| 31_0 | 0 | 1 | 1 | 4 |
| 35_0 | 0 | 1 | 1 | 8 |
| 36_0 | 0 | 1 | 1 | 0 |
| 37_0 | 0 | 1 | 1 | 2 |
| 38_0 | 0 | 1 | 1 | 0 |
| 40_0 | 0 | 1 | 1 | 9 |
| 41_0 | 0 | 1 | 1 | 4 |
| 42_0 | 0 | 1 | 1 | 0 |
| 43_0 | 0 | 1 | 1 | 0 |
| 46_0 | 0 | 1 | 1 | 0 |
| 48_0 | 0 | 1 | 1 | 1 |
| 50_0 | 0 | 1 | 1 | 0 |

| Image ID | Real Age | Real Class | Estimated Class | Estimated Age |
|----------|----------|------------|-----------------|---------------|
| 66_8 | 8 | 1 | 1 | 14 |
| 70_8 | 8 | 1 | 1 | 3 |
| 73_8 | 8 | 1 | 1 | 13 |
| 74_8 | 8 | 1 | 1 | 6 |
| 75_8 | 8 | 1 | 1 | 3 |
| 76_8 | 8 | 1 | 1 | 7 |
| 77_8 | 8 | 1 | 1 | 7 |
| 78_8 | 8 | 1 | 2 | 22 |
| 79_8 | 8 | 1 | 1 | 13 |
| 8_8 | 8 | 1 | 1 | 11 |
| 80_8 | 8 | 1 | 1 | 18 |
| 81_8 | 8 | 1 | 1 | 9 |
| 10_9 | 9 | 1 | 2 | 17 |
| 15_9 | 9 | 1 | 1 | 16 |
| 23_9 | 9 | 1 | 1 | 8 |
| 31_9 | 9 | 1 | 2 | 23 |
| 35_9 | 9 | 1 | 1 | 10 |
| 37_9 | 9 | 1 | 1 | 10 |
| 40_9 | 9 | 1 | 1 | 19 |
| 41_9 | 9 | 1 | 1 | 16 |
| 47_9 | 9 | 1 | 1 | 14 |

| Image ID | Real Age | Real Class | Estimated Class | Estimated Age |
|----------|----------|------------|-----------------|---------------|
| 45_18 | 18 | 2 | 2 | 24 |
| 46_18 | 18 | 2 | 2 | 21 |
| 47_18 | 18 | 2 | 2 | 21 |
| 48_18 | 18 | 2 | 2 | 21 |
| 5_18 | 18 | 2 | 2 | 19 |
| 50_18 | 18 | 2 | 2 | 29 |
| 51_18 | 18 | 2 | 2 | 26 |
| 52_18 | 18 | 2 | 2 | 19 |
| 53_18 | 18 | 2 | 2 | 25 |
| 54_18 | 18 | 2 | 2 | 26 |
| 57_18 | 18 | 2 | 2 | 23 |
| 61_18 | 18 | 2 | 2 | 26 |
| 62_18 | 18 | 2 | 2 | 23 |
| 63_18 | 18 | 2 | 2 | 28 |
| 7_18 | 18 | 2 | 2 | 24 |
| 71_18 | 18 | 2 | 1 | 13 |
| 8_18 | 18 | 2 | 2 | 24 |
| 82_18 | 18 | 2 | 2 | 27 |
| 9_18 | 18 | 2 | 1 | 16 |
| 1_19 | 19 | 2 | 2 | 29 |
| 13_19 | 19 | 2 | 1 | 16 |

| | | | | |
|------|---|---|---|----|
| 51_0 | 0 | 1 | 1 | 4 |
| 53_0 | 0 | 1 | 1 | 15 |
| 54_0 | 0 | 1 | 1 | 13 |
| 57_0 | 0 | 1 | 1 | 3 |
| 58_0 | 0 | 1 | 1 | 13 |
| 63_0 | 0 | 1 | 1 | 2 |
| 66_0 | 0 | 1 | 1 | 4 |
| 68_0 | 0 | 1 | 1 | 6 |
| 69_0 | 0 | 1 | 1 | 1 |
| 70_0 | 0 | 1 | 1 | 0 |
| 71_0 | 0 | 1 | 1 | 2 |
| 73_0 | 0 | 1 | 1 | 11 |
| 74_0 | 0 | 1 | 1 | 0 |
| 75_0 | 0 | 1 | 1 | 4 |
| 76_0 | 0 | 1 | 1 | 1 |
| 77_0 | 0 | 1 | 1 | 0 |
| 78_0 | 0 | 1 | 1 | 9 |
| 79_0 | 0 | 1 | 1 | 2 |
| 80_0 | 0 | 1 | 1 | 5 |
| 81_0 | 0 | 1 | 1 | 3 |
| 82_0 | 0 | 1 | 1 | 1 |
| 9_0 | 0 | 1 | 1 | 5 |
| 10_1 | 1 | 1 | 1 | 1 |
| 15_1 | 1 | 1 | 1 | 0 |
| 16_1 | 1 | 1 | 1 | 0 |
| 29_1 | 1 | 1 | 1 | 12 |
| 35_1 | 1 | 1 | 1 | 2 |
| 36_1 | 1 | 1 | 1 | 3 |

| | | | | |
|-------|----|---|---|----|
| 48_9 | 9 | 1 | 1 | 16 |
| 54_9 | 9 | 1 | 2 | 22 |
| 63_9 | 9 | 1 | 2 | 20 |
| 65_9 | 9 | 1 | 1 | 8 |
| 66_9 | 9 | 1 | 1 | 16 |
| 68_9 | 9 | 1 | 2 | 11 |
| 69_9 | 9 | 1 | 1 | 16 |
| 70_9 | 9 | 1 | 1 | 10 |
| 73_9 | 9 | 1 | 1 | 7 |
| 74_9 | 9 | 1 | 1 | 7 |
| 76_9 | 9 | 1 | 1 | 9 |
| 77_9 | 9 | 1 | 1 | 10 |
| 78_9 | 9 | 1 | 1 | 15 |
| 79_9 | 9 | 1 | 1 | 9 |
| 80_9 | 9 | 1 | 1 | 13 |
| 9_9 | 9 | 1 | 1 | 9 |
| 1_10 | 10 | 1 | 1 | 16 |
| 10_10 | 10 | 1 | 1 | 5 |
| 15_10 | 10 | 1 | 1 | 6 |
| 16_10 | 10 | 1 | 1 | 9 |
| 24_10 | 10 | 1 | 1 | 15 |
| 29_10 | 10 | 1 | 1 | 16 |
| 30_10 | 10 | 1 | 1 | 21 |
| 32_10 | 10 | 1 | 1 | 11 |
| 33_10 | 10 | 1 | 1 | 12 |
| 38_10 | 10 | 1 | 1 | 7 |
| 39_10 | 10 | 1 | 1 | 8 |
| 40_10 | 10 | 1 | 1 | 11 |

| | | | | |
|-------|----|---|---|----|
| 15_19 | 19 | 2 | 1 | 14 |
| 16_19 | 19 | 2 | 2 | 21 |
| 17_19 | 19 | 2 | 2 | 26 |
| 24_19 | 19 | 2 | 2 | 22 |
| 25_19 | 19 | 2 | 2 | 24 |
| 26_19 | 19 | 2 | 2 | 22 |
| 31_19 | 19 | 2 | 2 | 28 |
| 36_19 | 19 | 2 | 2 | 21 |
| 37_19 | 19 | 2 | 1 | 16 |
| 39_19 | 19 | 2 | 1 | 13 |
| 4_19 | 19 | 2 | 2 | 17 |
| 40_19 | 19 | 2 | 2 | 30 |
| 41_19 | 19 | 2 | 1 | 12 |
| 43_19 | 19 | 2 | 2 | 20 |
| 45_19 | 19 | 2 | 2 | 24 |
| 52_19 | 19 | 2 | 2 | 29 |
| 54_19 | 19 | 2 | 2 | 31 |
| 60_19 | 19 | 2 | 1 | 9 |
| 61_19 | 19 | 2 | 2 | 21 |
| 64_19 | 19 | 2 | 2 | 27 |
| 72_19 | 19 | 2 | 2 | 17 |
| 11_20 | 20 | 2 | 2 | 27 |
| 2_20 | 20 | 2 | 2 | 23 |
| 20_20 | 20 | 2 | 1 | 15 |
| 21_20 | 20 | 2 | 2 | 26 |
| 22_20 | 20 | 2 | 1 | 12 |
| 27_20 | 20 | 2 | 2 | 20 |
| 28_20 | 20 | 2 | 2 | 22 |

| | | | | |
|------|---|---|---|----|
| 37_1 | 1 | 1 | 1 | 2 |
| 38_1 | 1 | 1 | 1 | 0 |
| 42_1 | 1 | 1 | 1 | 6 |
| 44_1 | 1 | 1 | 1 | 0 |
| 46_1 | 1 | 1 | 1 | 6 |
| 53_1 | 1 | 1 | 1 | 6 |
| 56_1 | 1 | 1 | 1 | 0 |
| 58_1 | 1 | 1 | 2 | 21 |
| 64_1 | 1 | 1 | 1 | 2 |
| 7_1 | 1 | 1 | 1 | 0 |
| 70_1 | 1 | 1 | 1 | 6 |
| 73_1 | 1 | 1 | 1 | 4 |
| 74_1 | 1 | 1 | 1 | 2 |
| 75_1 | 1 | 1 | 1 | 2 |
| 76_1 | 1 | 1 | 1 | 2 |
| 77_1 | 1 | 1 | 1 | 4 |
| 78_1 | 1 | 1 | 1 | 6 |
| 79_1 | 1 | 1 | 1 | 3 |
| 80_1 | 1 | 1 | 1 | 5 |
| 81_1 | 1 | 1 | 1 | 0 |
| 9_1 | 1 | 1 | 1 | 0 |
| 1_2 | 2 | 1 | 1 | 0 |
| 11_2 | 2 | 1 | 1 | 0 |
| 20_2 | 2 | 1 | 1 | 19 |
| 26_2 | 2 | 1 | 1 | 3 |
| 27_2 | 2 | 1 | 1 | 8 |
| 31_2 | 2 | 1 | 1 | 2 |
| 33_2 | 2 | 1 | 1 | 0 |

| | | | | |
|-------|----|---|---|----|
| 42_10 | 10 | 1 | 1 | 16 |
| 43_10 | 10 | 1 | 1 | 14 |
| 46_10 | 10 | 1 | 1 | 8 |
| 48_10 | 10 | 1 | 1 | 7 |
| 49_10 | 10 | 1 | 1 | 11 |
| 50_10 | 10 | 1 | 2 | 21 |
| 52_10 | 10 | 1 | 2 | 20 |
| 53_10 | 10 | 1 | 1 | 12 |
| 54_10 | 10 | 1 | 1 | 17 |
| 56_10 | 10 | 1 | 1 | 10 |
| 58_10 | 10 | 1 | 1 | 18 |
| 60_10 | 10 | 1 | 1 | 9 |
| 61_10 | 10 | 1 | 2 | 22 |
| 64_10 | 10 | 1 | 2 | 26 |
| 65_10 | 10 | 1 | 1 | 15 |
| 66_10 | 10 | 1 | 1 | 21 |
| 68_10 | 10 | 1 | 1 | 13 |
| 68_10 | 10 | 1 | 1 | 4 |
| 69_10 | 10 | 1 | 1 | 19 |
| 71_10 | 10 | 1 | 1 | 15 |
| 74_10 | 10 | 1 | 1 | 8 |
| 75_10 | 10 | 1 | 1 | 10 |
| 76_10 | 10 | 1 | 1 | 10 |
| 77_10 | 10 | 1 | 1 | 11 |
| 78_10 | 10 | 1 | 1 | 19 |
| 79_10 | 10 | 1 | 1 | 10 |
| 80_10 | 10 | 1 | 1 | 15 |
| 81_10 | 10 | 1 | 1 | 14 |

| | | | | |
|-------|----|---|---|----|
| 29_20 | 20 | 2 | 2 | 21 |
| 3_20 | 20 | 2 | 2 | 22 |
| 30_20 | 20 | 2 | 1 | 20 |
| 32_20 | 20 | 2 | 1 | 13 |
| 36_20 | 20 | 2 | 1 | 22 |
| 41_20 | 20 | 2 | 1 | 13 |
| 42_20 | 20 | 2 | 2 | 22 |
| 46_20 | 20 | 2 | 2 | 25 |
| 47_20 | 20 | 2 | 1 | 15 |
| 52_20 | 20 | 2 | 2 | 24 |
| 60_20 | 20 | 2 | 2 | 28 |
| 63_20 | 20 | 2 | 2 | 23 |
| 82_20 | 20 | 2 | 2 | 26 |
| 12_21 | 21 | 2 | 1 | 20 |
| 13_21 | 21 | 2 | 2 | 12 |
| 2_21 | 21 | 2 | 2 | 22 |
| 23_21 | 21 | 2 | 2 | 27 |
| 33_21 | 21 | 2 | 2 | 15 |
| 34_21 | 21 | 2 | 2 | 21 |
| 35_21 | 21 | 2 | 2 | 21 |
| 38_21 | 21 | 2 | 2 | 19 |
| 4_21 | 21 | 2 | 2 | 23 |
| 40_21 | 21 | 2 | 2 | 26 |
| 41_21 | 21 | 2 | 1 | 14 |
| 44_21 | 21 | 2 | 2 | 23 |
| 67_21 | 21 | 2 | 1 | 17 |
| 72_21 | 21 | 2 | 2 | 18 |
| 8_21 | 21 | 2 | 2 | 17 |

| | | | | |
|------|---|---|---|----|
| 34_2 | 2 | 1 | 1 | 6 |
| 37_2 | 2 | 1 | 1 | 6 |
| 39_2 | 2 | 1 | 1 | 3 |
| 40_2 | 2 | 1 | 1 | 5 |
| 41_2 | 2 | 1 | 1 | 0 |
| 46_2 | 2 | 1 | 1 | 3 |
| 51_2 | 2 | 1 | 1 | 3 |
| 52_2 | 2 | 1 | 1 | 6 |
| 53_2 | 2 | 1 | 1 | 7 |
| 54_2 | 2 | 1 | 2 | 25 |
| 56_2 | 2 | 1 | 1 | 4 |
| 58_2 | 2 | 1 | 1 | 5 |
| 59_2 | 2 | 1 | 1 | 10 |
| 59_2 | 2 | 1 | 1 | 8 |
| 60_2 | 2 | 1 | 1 | 2 |
| 63_2 | 2 | 1 | 1 | 2 |
| 65_2 | 2 | 1 | 1 | 1 |
| 65_2 | 2 | 1 | 1 | 1 |
| 66_2 | 2 | 1 | 1 | 2 |
| 66_2 | 2 | 1 | 1 | 10 |
| 69_2 | 2 | 1 | 1 | 6 |
| 70_2 | 2 | 1 | 1 | 5 |
| 72_2 | 2 | 1 | 1 | 1 |
| 73_2 | 2 | 1 | 1 | 7 |
| 74_2 | 2 | 1 | 1 | 7 |
| 75_2 | 2 | 1 | 1 | 0 |
| 76_2 | 2 | 1 | 1 | 4 |
| 77_2 | 2 | 1 | 1 | 5 |

| | | | | |
|-------|----|---|---|----|
| 11_11 | 11 | 1 | 1 | 14 |
| 18_11 | 11 | 1 | 2 | 22 |
| 20_11 | 11 | 1 | 1 | 19 |
| 21_11 | 11 | 1 | 2 | 14 |
| 22_11 | 11 | 1 | 1 | 13 |
| 26_11 | 11 | 1 | 1 | 18 |
| 27_11 | 11 | 1 | 1 | 10 |
| 29_11 | 11 | 1 | 1 | 17 |
| 31_11 | 11 | 1 | 1 | 22 |
| 34_11 | 11 | 1 | 2 | 23 |
| 36_11 | 11 | 1 | 1 | 10 |
| 37_11 | 11 | 1 | 1 | 11 |
| 38_11 | 11 | 1 | 1 | 15 |
| 39_11 | 11 | 1 | 1 | 10 |
| 47_11 | 11 | 1 | 1 | 14 |
| 48_11 | 11 | 1 | 1 | 7 |
| 53_11 | 11 | 1 | 1 | 6 |
| 54_11 | 11 | 1 | 2 | 19 |
| 60_11 | 11 | 1 | 1 | 15 |
| 65_11 | 11 | 1 | 1 | 22 |
| 66_11 | 11 | 1 | 1 | 19 |
| 68_11 | 11 | 1 | 1 | 19 |
| 69_11 | 11 | 1 | 1 | 7 |
| 72_11 | 11 | 1 | 1 | 13 |
| 73_11 | 11 | 1 | 1 | 11 |
| 74_11 | 11 | 1 | 1 | 7 |
| 75_11 | 11 | 1 | 1 | 13 |
| 76_11 | 11 | 1 | 1 | 10 |

| | | | | |
|-------|----|---|---|----|
| 82_21 | 21 | 2 | 2 | 26 |
| 1_22 | 22 | 2 | 2 | 33 |
| 14_22 | 22 | 2 | 2 | 17 |
| 17_22 | 22 | 2 | 2 | 26 |
| 18_22 | 22 | 2 | 1 | 11 |
| 20_22 | 22 | 2 | 2 | 28 |
| 23_22 | 22 | 2 | 2 | 22 |
| 25_22 | 22 | 2 | 1 | 16 |
| 27_22 | 22 | 2 | 2 | 22 |
| 29_22 | 22 | 2 | 2 | 27 |
| 50_22 | 22 | 2 | 2 | 22 |
| 55_22 | 22 | 2 | 1 | 13 |
| 63_22 | 22 | 2 | 2 | 25 |
| 7_22 | 22 | 2 | 2 | 21 |
| 71_22 | 22 | 2 | 1 | 12 |
| 82_22 | 22 | 2 | 2 | 27 |
| 9_22 | 22 | 2 | 1 | 14 |
| 9_22 | 22 | 2 | 1 | 14 |
| 12_23 | 23 | 2 | 2 | 21 |
| 13_23 | 23 | 2 | 1 | 8 |
| 19_23 | 23 | 2 | 2 | 20 |
| 2_23 | 23 | 2 | 2 | 16 |
| 21_23 | 23 | 2 | 2 | 29 |
| 22_23 | 23 | 2 | 1 | 14 |
| 24_23 | 23 | 2 | 2 | 26 |
| 25_23 | 23 | 2 | 1 | 16 |
| 29_23 | 23 | 2 | 2 | 27 |
| 3_23 | 23 | 2 | 2 | 28 |

| | | | | |
|------|---|---|---|----|
| 78_2 | 2 | 1 | 1 | 10 |
| 79_2 | 2 | 1 | 1 | 4 |
| 80_2 | 2 | 1 | 1 | 2 |
| 81_2 | 2 | 1 | 1 | 9 |
| 14_3 | 3 | 1 | 1 | 0 |
| 15_3 | 3 | 1 | 1 | 3 |
| 16_3 | 3 | 1 | 1 | 3 |
| 19_3 | 3 | 1 | 1 | 13 |
| 2_3 | 3 | 1 | 1 | 12 |
| 21_3 | 3 | 1 | 1 | 7 |
| 23_3 | 3 | 1 | 1 | 6 |
| 25_3 | 3 | 1 | 1 | 7 |
| 31_3 | 3 | 1 | 1 | 4 |
| 35_3 | 3 | 1 | 1 | 5 |
| 36_3 | 3 | 1 | 1 | 6 |
| 38_3 | 3 | 1 | 1 | 1 |
| 40_3 | 3 | 1 | 1 | 19 |
| 40_3 | 3 | 1 | 1 | 10 |
| 43_3 | 3 | 1 | 1 | 0 |
| 44_3 | 3 | 1 | 1 | 0 |
| 45_3 | 3 | 1 | 1 | 5 |
| 50_3 | 3 | 1 | 1 | 0 |
| 53_3 | 3 | 1 | 1 | 4 |
| 56_3 | 3 | 1 | 1 | 6 |
| 58_3 | 3 | 1 | 1 | 13 |
| 59_3 | 3 | 1 | 1 | 12 |
| 62_3 | 3 | 1 | 1 | 9 |
| 64_3 | 3 | 1 | 1 | 3 |

| | | | | |
|-------|----|---|---|----|
| 77_11 | 11 | 1 | 1 | 12 |
| 78_11 | 11 | 1 | 1 | 18 |
| 79_11 | 11 | 1 | 1 | 6 |
| 81_11 | 11 | 1 | 1 | 20 |
| 9_11 | 11 | 1 | 2 | 18 |
| 10_12 | 12 | 1 | 1 | 0 |
| 12_12 | 12 | 1 | 1 | 6 |
| 14_12 | 12 | 1 | 1 | 7 |
| 15_12 | 12 | 1 | 1 | 11 |
| 16_12 | 12 | 1 | 1 | 16 |
| 17_12 | 12 | 1 | 1 | 15 |
| 19_12 | 12 | 1 | 2 | 24 |
| 2_12 | 12 | 1 | 1 | 19 |
| 25_12 | 12 | 1 | 2 | 20 |
| 31_12 | 12 | 1 | 1 | 22 |
| 35_12 | 12 | 1 | 1 | 6 |
| 40_12 | 12 | 1 | 2 | 23 |
| 42_12 | 12 | 1 | 1 | 16 |
| 45_12 | 12 | 1 | 1 | 14 |
| 46_12 | 12 | 1 | 1 | 14 |
| 47_12 | 12 | 1 | 1 | 14 |
| 49_12 | 12 | 1 | 1 | 24 |
| 51_12 | 12 | 1 | 2 | 20 |
| 53_12 | 12 | 1 | 1 | 13 |
| 54_12 | 12 | 1 | 1 | 15 |
| 55_12 | 12 | 1 | 1 | 12 |
| 56_12 | 12 | 1 | 1 | 7 |
| 57_12 | 12 | 1 | 1 | 5 |

| | | | | |
|-------|----|---|---|----|
| 30_23 | 23 | 2 | 2 | 24 |
| 35_23 | 23 | 2 | 2 | 22 |
| 35_23 | 23 | 2 | 2 | 24 |
| 38_23 | 23 | 2 | 2 | 28 |
| 43_23 | 23 | 2 | 2 | 17 |
| 47_23 | 23 | 2 | 1 | 19 |
| 55_23 | 23 | 2 | 1 | 21 |
| 57_23 | 23 | 2 | 2 | 21 |
| 67_23 | 23 | 2 | 2 | 26 |
| 7_23 | 23 | 2 | 2 | 18 |
| 71_23 | 23 | 2 | 1 | 14 |
| 82_23 | 23 | 2 | 2 | 25 |
| 12_24 | 24 | 2 | 2 | 19 |
| 20_24 | 24 | 2 | 2 | 23 |
| 32_24 | 24 | 2 | 2 | 22 |
| 41_24 | 24 | 2 | 1 | 20 |
| 42_24 | 24 | 2 | 2 | 21 |
| 5_24 | 24 | 2 | 2 | 19 |
| 51_24 | 24 | 2 | 2 | 27 |
| 6_24 | 24 | 2 | 2 | 27 |
| 71_24 | 24 | 2 | 2 | 23 |
| 12_25 | 25 | 2 | 1 | 19 |
| 13_25 | 25 | 2 | 2 | 21 |
| 18_25 | 25 | 2 | 2 | 22 |
| 22_25 | 25 | 2 | 1 | 23 |
| 23_25 | 25 | 2 | 2 | 24 |
| 24_25 | 25 | 2 | 2 | 25 |
| 27_25 | 25 | 2 | 1 | 17 |

| | | | | |
|------|---|---|---|----|
| 65_3 | 3 | 1 | 1 | 2 |
| 65_3 | 3 | 1 | 1 | 6 |
| 66_3 | 3 | 1 | 1 | 1 |
| 68_3 | 3 | 1 | 1 | 5 |
| 69_3 | 3 | 1 | 1 | 0 |
| 70_3 | 3 | 1 | 1 | 6 |
| 73_3 | 3 | 1 | 1 | 2 |
| 74_3 | 3 | 1 | 1 | 1 |
| 75_3 | 3 | 1 | 1 | 4 |
| 76_3 | 3 | 1 | 1 | 3 |
| 77_3 | 3 | 1 | 1 | 7 |
| 78_3 | 3 | 1 | 1 | 6 |
| 79_3 | 3 | 1 | 1 | 9 |
| 8_3 | 3 | 1 | 1 | 0 |
| 80_3 | 3 | 1 | 1 | 8 |
| 81_3 | 3 | 1 | 1 | 7 |
| 82_3 | 3 | 1 | 1 | 5 |
| 9_3 | 3 | 1 | 1 | 6 |
| 10_4 | 4 | 1 | 1 | 6 |
| 12_4 | 4 | 1 | 2 | 21 |
| 15_4 | 4 | 1 | 1 | 8 |
| 16_4 | 4 | 1 | 1 | 0 |
| 2_4 | 4 | 1 | 1 | 12 |
| 20_4 | 4 | 1 | 1 | 3 |
| 26_4 | 4 | 1 | 1 | 8 |
| 29_4 | 4 | 1 | 2 | 22 |
| 30_4 | 4 | 1 | 1 | 18 |
| 31_4 | 4 | 1 | 1 | 1 |

| | | | | |
|-------|----|---|---|----|
| 59_12 | 12 | 1 | 1 | 18 |
| 60_12 | 12 | 1 | 2 | 15 |
| 65_12 | 12 | 1 | 1 | 10 |
| 68_12 | 12 | 1 | 1 | 11 |
| 70_12 | 12 | 1 | 1 | 9 |
| 73_12 | 12 | 1 | 1 | 10 |
| 74_12 | 12 | 1 | 1 | 7 |
| 76_12 | 12 | 1 | 1 | 8 |
| 77_12 | 12 | 1 | 1 | 12 |
| 78_12 | 12 | 1 | 1 | 19 |
| 79_12 | 12 | 1 | 1 | 16 |
| 8_12 | 12 | 1 | 2 | 23 |
| 80_12 | 12 | 1 | 2 | 24 |
| 81_12 | 12 | 1 | 1 | 17 |
| 11_13 | 13 | 1 | 1 | 18 |
| 20_13 | 13 | 1 | 2 | 24 |
| 26_13 | 13 | 1 | 1 | 11 |
| 27_13 | 13 | 1 | 1 | 14 |
| 29_13 | 13 | 1 | 1 | 12 |
| 32_13 | 13 | 1 | 1 | 18 |
| 34_13 | 13 | 1 | 2 | 23 |
| 36_13 | 13 | 1 | 1 | 18 |
| 37_13 | 13 | 1 | 1 | 8 |
| 38_13 | 13 | 1 | 1 | 6 |
| 39_13 | 13 | 1 | 1 | 12 |
| 41_13 | 13 | 1 | 1 | 6 |
| 43_13 | 13 | 1 | 1 | 11 |
| 44_13 | 13 | 1 | 2 | 22 |

| | | | | |
|-------|----|---|---|----|
| 3_25 | 25 | 2 | 2 | 31 |
| 33_25 | 25 | 2 | 1 | 11 |
| 34_25 | 25 | 2 | 2 | 27 |
| 44_25 | 25 | 2 | 2 | 22 |
| 45_25 | 25 | 2 | 2 | 26 |
| 57_25 | 25 | 2 | 2 | 24 |
| 61_25 | 25 | 2 | 2 | 26 |
| 63_25 | 25 | 2 | 2 | 25 |
| 72_25 | 25 | 2 | 2 | 13 |
| 82_25 | 25 | 2 | 2 | 28 |
| 12_26 | 26 | 2 | 2 | 26 |
| 17_26 | 26 | 2 | 2 | 30 |
| 2_26 | 26 | 2 | 2 | 23 |
| 20_26 | 26 | 2 | 2 | 23 |
| 22_26 | 26 | 2 | 2 | 23 |
| 28_26 | 26 | 2 | 1 | 18 |
| 30_26 | 26 | 2 | 2 | 25 |
| 4_26 | 26 | 2 | 2 | 21 |
| 61_26 | 26 | 2 | 2 | 23 |
| 67_26 | 26 | 2 | 1 | 15 |
| 7_26 | 26 | 2 | 1 | 12 |
| 11_27 | 27 | 2 | 2 | 26 |
| 12_27 | 27 | 2 | 2 | 21 |
| 19_27 | 27 | 2 | 1 | 14 |
| 21_27 | 27 | 2 | 2 | 26 |
| 22_27 | 27 | 2 | 2 | 23 |
| 43_27 | 27 | 2 | 2 | 29 |
| 47_27 | 27 | 2 | 2 | 18 |

| | | | | |
|------|---|---|---|----|
| 34_4 | 4 | 1 | 1 | 10 |
| 37_4 | 4 | 1 | 1 | 11 |
| 38_4 | 4 | 1 | 1 | 14 |
| 41_4 | 4 | 1 | 1 | 1 |
| 42_4 | 4 | 1 | 1 | 12 |
| 43_4 | 4 | 1 | 1 | 10 |
| 46_4 | 4 | 1 | 1 | 5 |
| 49_4 | 4 | 1 | 1 | 7 |
| 52_4 | 4 | 1 | 1 | 2 |
| 53_4 | 4 | 1 | 1 | 5 |
| 54_4 | 4 | 1 | 2 | 21 |
| 55_4 | 4 | 1 | 1 | 13 |
| 56_4 | 4 | 1 | 1 | 4 |
| 58_4 | 4 | 1 | 1 | 18 |
| 59_4 | 4 | 1 | 2 | 20 |
| 60_4 | 4 | 1 | 1 | 16 |
| 61_4 | 4 | 1 | 1 | 2 |
| 63_4 | 4 | 1 | 1 | 8 |
| 64_4 | 4 | 1 | 2 | 19 |
| 65_4 | 4 | 1 | 1 | 5 |
| 66_4 | 4 | 1 | 1 | 6 |
| 67_4 | 4 | 1 | 1 | 6 |
| 68_4 | 4 | 1 | 1 | 7 |
| 69_4 | 4 | 1 | 1 | 10 |
| 73_4 | 4 | 1 | 1 | 6 |
| 74_4 | 4 | 1 | 1 | 0 |
| 76_4 | 4 | 1 | 1 | 6 |
| 77_4 | 4 | 1 | 1 | 2 |

| | | | | |
|-------|----|---|---|----|
| 47_13 | 13 | 1 | 1 | 9 |
| 52_13 | 13 | 1 | 2 | 23 |
| 53_13 | 13 | 1 | 1 | 12 |
| 54_13 | 13 | 1 | 1 | 10 |
| 58_13 | 13 | 1 | 1 | 20 |
| 65_13 | 13 | 1 | 2 | 23 |
| 68_13 | 13 | 1 | 2 | 23 |
| 69_13 | 13 | 1 | 2 | 18 |
| 72_13 | 13 | 1 | 1 | 13 |
| 73_13 | 13 | 1 | 1 | 9 |
| 74_13 | 13 | 1 | 1 | 8 |
| 76_13 | 13 | 1 | 1 | 8 |
| 77_13 | 13 | 1 | 1 | 14 |
| 78_13 | 13 | 1 | 2 | 20 |
| 79_13 | 13 | 1 | 1 | 18 |
| 8_13 | 13 | 1 | 2 | 23 |
| 80_13 | 13 | 1 | 2 | 23 |
| 9_13 | 13 | 1 | 1 | 11 |
| 1_14 | 14 | 1 | 2 | 22 |
| 11_14 | 14 | 1 | 1 | 20 |
| 12_14 | 14 | 1 | 1 | 9 |
| 14_14 | 14 | 1 | 1 | 12 |
| 15_14 | 14 | 1 | 1 | 12 |
| 16_14 | 14 | 1 | 2 | 23 |
| 22_14 | 14 | 1 | 2 | 27 |
| 23_14 | 14 | 1 | 1 | 19 |
| 28_14 | 14 | 1 | 1 | 20 |
| 31_14 | 14 | 1 | 1 | 21 |

| | | | | |
|-------|----|---|---|----|
| 48_27 | 27 | 2 | 2 | 24 |
| 71_27 | 27 | 2 | 1 | 10 |
| 72_27 | 27 | 2 | 1 | 8 |
| 82_27 | 27 | 2 | 2 | 26 |
| 1_28 | 28 | 2 | 2 | 31 |
| 18_28 | 28 | 2 | 1 | 7 |
| 22_28 | 28 | 2 | 2 | 24 |
| 24_28 | 28 | 2 | 2 | 31 |
| 25_28 | 28 | 2 | 2 | 24 |
| 28_28 | 28 | 2 | 2 | 18 |
| 32_28 | 28 | 2 | 2 | 22 |
| 4_28 | 28 | 2 | 2 | 26 |
| 42_28 | 28 | 2 | 2 | 24 |
| 45_28 | 28 | 2 | 2 | 25 |
| 6_28 | 28 | 2 | 2 | 28 |
| 67_28 | 28 | 2 | 2 | 24 |
| 1_29 | 29 | 2 | 2 | 32 |
| 17_29 | 29 | 2 | 2 | 22 |
| 18_29 | 29 | 2 | 2 | 26 |
| 2_29 | 29 | 2 | 2 | 25 |
| 23_29 | 29 | 2 | 2 | 19 |
| 29_29 | 29 | 2 | 2 | 24 |
| 61_29 | 29 | 2 | 2 | 24 |
| 72_29 | 29 | 2 | 2 | 22 |
| 8_29 | 29 | 2 | 2 | 14 |
| 11_30 | 30 | 2 | 2 | 24 |
| 12_30 | 30 | 2 | 2 | 12 |
| 13_30 | 30 | 2 | 2 | 30 |

| | | | | |
|------|---|---|---|----|
| 78_4 | 4 | 1 | 1 | 8 |
| 79_4 | 4 | 1 | 1 | 2 |
| 80_4 | 4 | 1 | 1 | 9 |
| 81_4 | 4 | 1 | 2 | 12 |
| 1_5 | 5 | 1 | 1 | 7 |
| 10_5 | 5 | 1 | 1 | 4 |
| 11_5 | 5 | 1 | 1 | 7 |
| 15_5 | 5 | 1 | 1 | 7 |
| 16_5 | 5 | 1 | 1 | 4 |
| 17_5 | 5 | 1 | 1 | 12 |
| 19_5 | 5 | 1 | 1 | 19 |
| 2_5 | 5 | 1 | 1 | 17 |
| 21_5 | 5 | 1 | 1 | 11 |
| 23_5 | 5 | 1 | 1 | 20 |
| 24_5 | 5 | 1 | 1 | 5 |
| 29_5 | 5 | 1 | 1 | 15 |
| 30_5 | 5 | 1 | 1 | 11 |
| 33_5 | 5 | 1 | 1 | 7 |
| 35_5 | 5 | 1 | 1 | 2 |
| 36_5 | 5 | 1 | 1 | 9 |
| 38_5 | 5 | 1 | 1 | 11 |
| 39_5 | 5 | 1 | 1 | 13 |
| 40_5 | 5 | 1 | 1 | 9 |
| 42_5 | 5 | 1 | 1 | 1 |
| 43_5 | 5 | 1 | 1 | 0 |
| 44_5 | 5 | 1 | 1 | 17 |
| 47_5 | 5 | 1 | 1 | 18 |
| 49_5 | 5 | 1 | 1 | 8 |

| | | | | |
|-------|----|---|---|----|
| 33_14 | 14 | 1 | 1 | 16 |
| 35_14 | 14 | 1 | 1 | 14 |
| 38_14 | 14 | 1 | 1 | 11 |
| 40_14 | 14 | 1 | 1 | 21 |
| 42_14 | 14 | 1 | 2 | 20 |
| 46_14 | 14 | 1 | 2 | 23 |
| 50_14 | 14 | 1 | 2 | 25 |
| 51_14 | 14 | 1 | 1 | 20 |
| 52_14 | 14 | 1 | 2 | 25 |
| 55_14 | 14 | 1 | 1 | 14 |
| 59_14 | 14 | 1 | 2 | 23 |
| 67_14 | 14 | 1 | 1 | 19 |
| 68_14 | 14 | 1 | 1 | 9 |
| 70_14 | 14 | 1 | 1 | 11 |
| 72_14 | 14 | 1 | 2 | 14 |
| 73_14 | 14 | 1 | 1 | 18 |
| 74_14 | 14 | 1 | 1 | 21 |
| 76_14 | 14 | 1 | 1 | 18 |
| 77_14 | 14 | 1 | 1 | 15 |
| 78_14 | 14 | 1 | 1 | 15 |
| 80_14 | 14 | 1 | 1 | 21 |
| 9_14 | 14 | 1 | 1 | 8 |
| 10_15 | 15 | 1 | 1 | 10 |
| 11_15 | 15 | 1 | 1 | 15 |
| 15_15 | 15 | 1 | 1 | 15 |
| 17_15 | 15 | 1 | 2 | 24 |
| 19_15 | 15 | 1 | 1 | 16 |
| 2_15 | 15 | 1 | 1 | 17 |

| | | | | |
|-------|----|---|---|----|
| 14_30 | 30 | 2 | 1 | 10 |
| 19_30 | 30 | 2 | 1 | 11 |
| 20_30 | 30 | 2 | 2 | 24 |
| 21_30 | 30 | 2 | 2 | 22 |
| 22_30 | 30 | 2 | 1 | 17 |
| 24_30 | 30 | 2 | 2 | 24 |
| 27_30 | 30 | 2 | 1 | 21 |
| 33_30 | 30 | 2 | 2 | 21 |
| 34_30 | 30 | 2 | 2 | 26 |
| 4_30 | 30 | 2 | 1 | 9 |
| 48_30 | 30 | 2 | 2 | 24 |
| 5_30 | 30 | 2 | 2 | 27 |
| 61_30 | 30 | 2 | 2 | 25 |
| 62_30 | 30 | 2 | 2 | 27 |
| 67_30 | 30 | 2 | 2 | 25 |
| 8_30 | 30 | 2 | 2 | 21 |
| 2_31 | 31 | 2 | 1 | 19 |
| 29_31 | 31 | 2 | 2 | 28 |
| 5_31 | 31 | 2 | 2 | 28 |
| 6_31 | 31 | 2 | 2 | 29 |
| 8_31 | 31 | 2 | 2 | 21 |
| 82_31 | 31 | 2 | 2 | 27 |
| 12_32 | 32 | 2 | 1 | 18 |
| 17_32 | 32 | 2 | 2 | 16 |
| 45_32 | 32 | 2 | 2 | 26 |
| 61_32 | 32 | 2 | 2 | 28 |
| 1_33 | 33 | 2 | 2 | 29 |
| 18_33 | 33 | 2 | 1 | 17 |

| | | | | |
|------|---|---|---|----|
| 51_5 | 5 | 1 | 1 | 9 |
| 55_5 | 5 | 1 | 1 | 7 |
| 57_5 | 5 | 1 | 1 | 11 |
| 58_5 | 5 | 1 | 2 | 21 |
| 60_5 | 5 | 1 | 1 | 5 |
| 69_5 | 5 | 1 | 1 | 6 |
| 70_5 | 5 | 1 | 1 | 8 |
| 73_5 | 5 | 1 | 1 | 7 |
| 74_5 | 5 | 1 | 1 | 4 |
| 75_5 | 5 | 1 | 1 | 10 |
| 76_5 | 5 | 1 | 1 | 7 |
| 78_5 | 5 | 1 | 1 | 4 |
| 79_5 | 5 | 1 | 1 | 1 |
| 80_5 | 5 | 1 | 1 | 10 |
| 81_5 | 5 | 1 | 1 | 8 |
| 9_5 | 5 | 1 | 1 | 4 |
| 10_6 | 6 | 1 | 1 | 4 |
| 18_6 | 6 | 1 | 1 | 10 |
| 21_6 | 6 | 1 | 1 | 9 |
| 26_6 | 6 | 1 | 1 | 17 |
| 31_6 | 6 | 1 | 1 | 12 |
| 32_6 | 6 | 1 | 1 | 7 |
| 36_6 | 6 | 1 | 1 | 15 |
| 37_6 | 6 | 1 | 1 | 6 |
| 40_6 | 6 | 1 | 1 | 12 |
| 41_6 | 6 | 1 | 1 | 8 |
| 42_6 | 6 | 1 | 1 | 3 |
| 45_6 | 6 | 1 | 1 | 5 |

| | | | | |
|-------|----|---|---|----|
| 25_15 | 15 | 1 | 2 | 25 |
| 26_15 | 15 | 1 | 1 | 9 |
| 31_15 | 15 | 1 | 2 | 27 |
| 32_15 | 15 | 1 | 2 | 24 |
| 34_15 | 15 | 1 | 2 | 26 |
| 36_15 | 15 | 1 | 1 | 17 |
| 39_15 | 15 | 1 | 1 | 14 |
| 43_15 | 15 | 1 | 1 | 17 |
| 44_15 | 15 | 1 | 2 | 18 |
| 47_15 | 15 | 1 | 1 | 17 |
| 48_15 | 15 | 1 | 2 | 23 |
| 49_15 | 15 | 1 | 1 | 21 |
| 51_15 | 15 | 1 | 1 | 12 |
| 53_15 | 15 | 1 | 2 | 21 |
| 56_15 | 15 | 1 | 2 | 22 |
| 58_15 | 15 | 1 | 2 | 21 |
| 61_15 | 15 | 1 | 1 | 19 |
| 62_15 | 15 | 1 | 2 | 25 |
| 64_15 | 15 | 1 | 1 | 13 |
| 73_15 | 15 | 1 | 1 | 21 |
| 74_15 | 15 | 1 | 1 | 17 |
| 76_15 | 15 | 1 | 1 | 21 |
| 77_15 | 15 | 1 | 1 | 15 |
| 78_15 | 15 | 1 | 1 | 21 |
| 1_16 | 16 | 1 | 2 | 23 |
| 10_16 | 16 | 1 | 1 | 14 |
| 13_16 | 16 | 1 | 1 | 11 |
| 14_16 | 16 | 1 | 1 | 11 |

| | | | | |
|-------|----|---|---|----|
| 29_33 | 33 | 2 | 2 | 24 |
| 32_33 | 33 | 2 | 1 | 16 |
| 47_33 | 33 | 2 | 2 | 12 |
| 48_33 | 33 | 2 | 1 | 13 |
| 63_33 | 33 | 2 | 2 | 30 |
| 67_33 | 33 | 2 | 1 | 20 |
| 8_33 | 33 | 2 | 2 | 20 |
| 11_34 | 34 | 2 | 2 | 25 |
| 12_34 | 34 | 2 | 1 | 5 |
| 13_34 | 34 | 2 | 1 | 19 |
| 18_34 | 34 | 2 | 2 | 16 |
| 25_34 | 34 | 2 | 2 | 24 |
| 28_34 | 34 | 2 | 2 | 16 |
| 38_34 | 34 | 2 | 2 | 22 |
| 72_34 | 34 | 2 | 2 | 28 |
| 21_35 | 35 | 2 | 2 | 25 |
| 28_35 | 35 | 2 | 2 | 25 |
| 3_35 | 35 | 2 | 2 | 28 |
| 32_35 | 35 | 2 | 2 | 22 |
| 33_35 | 35 | 2 | 2 | 21 |
| 34_35 | 35 | 2 | 2 | 21 |
| 39_35 | 35 | 2 | 1 | 14 |
| 5_35 | 35 | 2 | 2 | 28 |
| 62_35 | 35 | 2 | 2 | 25 |
| 71_35 | 35 | 2 | 2 | 25 |
| 8_35 | 35 | 2 | 2 | 19 |
| 12_36 | 36 | 2 | 1 | 15 |
| 14_36 | 36 | 2 | 2 | 21 |

| | | | | |
|------|---|---|---|----|
| 46_6 | 6 | 1 | 1 | 11 |
| 47_6 | 6 | 1 | 1 | 15 |
| 49_6 | 6 | 1 | 1 | 3 |
| 50_6 | 6 | 1 | 1 | 8 |
| 53_6 | 6 | 1 | 1 | 10 |
| 54_6 | 6 | 1 | 1 | 13 |
| 55_6 | 6 | 1 | 1 | 8 |
| 56_6 | 6 | 1 | 1 | 10 |
| 57_6 | 6 | 1 | 1 | 10 |
| 58_6 | 6 | 1 | 1 | 16 |
| 59_6 | 6 | 1 | 1 | 10 |
| 60_6 | 6 | 1 | 1 | 2 |
| 61_6 | 6 | 1 | 2 | 20 |
| 65_6 | 6 | 1 | 1 | 9 |
| 65_6 | 6 | 1 | 1 | 6 |
| 66_6 | 6 | 1 | 1 | 7 |
| 66_6 | 6 | 1 | 1 | 9 |
| 69_6 | 6 | 1 | 1 | 10 |
| 70_6 | 6 | 1 | 1 | 4 |
| 73_6 | 6 | 1 | 1 | 7 |
| 74_6 | 6 | 1 | 1 | 3 |
| 75_6 | 6 | 1 | 1 | 5 |
| 76_6 | 6 | 1 | 1 | 7 |
| 77_6 | 6 | 1 | 1 | 9 |
| 78_6 | 6 | 1 | 1 | 21 |
| 79_6 | 6 | 1 | 1 | 11 |
| 8_6 | 6 | 1 | 1 | 9 |
| 80_6 | 6 | 1 | 1 | 10 |

| | | | | |
|-------|----|---|---|----|
| 16_16 | 16 | 1 | 1 | 16 |
| 18_16 | 16 | 1 | 2 | 26 |
| 2_16 | 16 | 1 | 2 | 23 |
| 20_16 | 16 | 1 | 1 | 15 |
| 21_16 | 16 | 1 | 2 | 25 |
| 22_16 | 16 | 1 | 2 | 24 |
| 23_16 | 16 | 1 | 2 | 27 |
| 27_16 | 16 | 1 | 2 | 21 |
| 28_16 | 16 | 1 | 1 | 13 |
| 29_16 | 16 | 1 | 2 | 27 |
| 30_16 | 16 | 1 | 2 | 25 |
| 31_16 | 16 | 1 | 2 | 22 |
| 34_16 | 16 | 1 | 2 | 27 |
| 35_16 | 16 | 1 | 1 | 16 |
| 39_16 | 16 | 1 | 2 | 17 |
| 40_16 | 16 | 1 | 2 | 25 |
| 46_16 | 16 | 1 | 1 | 21 |
| 48_16 | 16 | 1 | 2 | 23 |
| 49_16 | 16 | 1 | 2 | 24 |
| 50_16 | 16 | 1 | 2 | 14 |
| 51_16 | 16 | 1 | 2 | 21 |
| 52_16 | 16 | 1 | 2 | 28 |
| 54_16 | 16 | 1 | 2 | 24 |
| 57_16 | 16 | 1 | 2 | 22 |
| 59_16 | 16 | 1 | 1 | 19 |
| 62_16 | 16 | 1 | 1 | 12 |
| 73_16 | 16 | 1 | 1 | 11 |
| 76_16 | 16 | 1 | 1 | 12 |

| | | | | |
|-------|----|---|---|----|
| 17_36 | 36 | 2 | 2 | 29 |
| 18_36 | 36 | 2 | 2 | 22 |
| 2_36 | 36 | 2 | 2 | 23 |
| 20_36 | 36 | 2 | 2 | 21 |
| 27_36 | 36 | 2 | 1 | 19 |
| 6_36 | 36 | 2 | 2 | 32 |
| 28_37 | 37 | 2 | 1 | 16 |
| 4_37 | 37 | 2 | 2 | 19 |
| 7_37 | 37 | 2 | 2 | 21 |
| 17_38 | 38 | 2 | 2 | 27 |
| 2_38 | 38 | 2 | 2 | 17 |
| 3_38 | 38 | 2 | 2 | 25 |
| 62_38 | 38 | 2 | 2 | 25 |
| 7_38 | 38 | 2 | 2 | 22 |
| 21_39 | 39 | 2 | 2 | 25 |
| 25_39 | 39 | 2 | 2 | 20 |
| 33_39 | 39 | 2 | 1 | 17 |
| 34_39 | 39 | 2 | 2 | 24 |
| 67_39 | 39 | 2 | 1 | 16 |
| 7_39 | 39 | 2 | 2 | 22 |
| 1_40 | 40 | 2 | 1 | 23 |
| 11_40 | 40 | 2 | 2 | 26 |
| 14_40 | 40 | 2 | 1 | 14 |
| 32_40 | 40 | 2 | 2 | 25 |
| 4_40 | 40 | 2 | 2 | 24 |
| 45_40 | 40 | 2 | 2 | 21 |
| 5_40 | 40 | 2 | 2 | 18 |
| 6_40 | 40 | 2 | 2 | 30 |

| | | | | |
|------|---|---|---|----|
| 81_6 | 6 | 1 | 1 | 16 |
| 10_7 | 7 | 1 | 1 | 7 |
| 10_7 | 7 | 1 | 1 | 2 |
| 11_7 | 7 | 1 | 1 | 6 |
| 12_7 | 7 | 1 | 1 | 7 |
| 15_7 | 7 | 1 | 1 | 11 |
| 16_7 | 7 | 1 | 1 | 11 |
| 17_7 | 7 | 1 | 1 | 5 |
| 19_7 | 7 | 1 | 1 | 14 |
| 2_7 | 7 | 1 | 2 | 16 |
| 22_7 | 7 | 1 | 1 | 10 |
| 23_7 | 7 | 1 | 1 | 12 |
| 24_7 | 7 | 1 | 1 | 19 |
| 25_7 | 7 | 1 | 1 | 11 |
| 26_7 | 7 | 1 | 1 | 8 |
| 30_7 | 7 | 1 | 1 | 17 |
| 31_7 | 7 | 1 | 1 | 11 |
| 35_7 | 7 | 1 | 1 | 7 |
| 39_7 | 7 | 1 | 1 | 11 |
| 40_7 | 7 | 1 | 1 | 9 |
| 44_7 | 7 | 1 | 1 | 13 |
| 49_7 | 7 | 1 | 1 | 12 |
| 52_7 | 7 | 1 | 1 | 15 |
| 57_7 | 7 | 1 | 1 | 11 |
| 59_7 | 7 | 1 | 1 | 11 |
| 60_7 | 7 | 1 | 2 | 22 |
| 61_7 | 7 | 1 | 1 | 10 |
| 65_7 | 7 | 1 | 1 | 9 |

| | | | | |
|-------|----|---|---|----|
| 77_16 | 16 | 1 | 1 | 11 |
| 8_16 | 16 | 1 | 2 | 22 |
| 82_16 | 16 | 1 | 2 | 26 |
| 9_16 | 16 | 1 | 1 | 10 |
| 9_16 | 16 | 1 | 1 | 14 |
| 11_17 | 17 | 1 | 1 | 18 |
| 15_17 | 17 | 1 | 1 | 16 |
| 16_17 | 17 | 1 | 2 | 24 |
| 17_17 | 17 | 1 | 1 | 30 |
| 24_17 | 17 | 1 | 2 | 24 |
| 26_17 | 17 | 1 | 1 | 16 |
| 30_17 | 17 | 1 | 2 | 27 |
| 36_17 | 17 | 1 | 1 | 21 |
| 37_17 | 17 | 1 | 1 | 18 |
| 38_17 | 17 | 1 | 1 | 18 |
| 39_17 | 17 | 1 | 2 | 23 |
| 43_17 | 17 | 1 | 2 | 19 |
| 44_17 | 17 | 1 | 2 | 17 |
| 45_17 | 17 | 1 | 2 | 22 |
| 46_17 | 17 | 1 | 1 | 16 |
| 48_17 | 17 | 1 | 1 | 16 |
| 49_17 | 17 | 1 | 2 | 20 |
| 51_17 | 17 | 1 | 2 | 20 |
| 52_17 | 17 | 1 | 2 | 26 |
| 54_17 | 17 | 1 | 2 | 23 |
| 57_17 | 17 | 1 | 2 | 26 |
| 58_17 | 17 | 1 | 1 | 11 |
| 60_17 | 17 | 1 | 2 | 25 |

| | | | | |
|-------|----|---|---|----|
| 71_40 | 40 | 2 | 2 | 22 |
| 13_41 | 41 | 2 | 1 | 14 |
| 27_41 | 41 | 2 | 2 | 19 |
| 28_41 | 41 | 2 | 1 | 15 |
| 62_41 | 41 | 2 | 2 | 22 |
| 72_41 | 41 | 2 | 2 | 22 |
| 8_41 | 41 | 2 | 2 | 22 |
| 11_42 | 42 | 2 | 2 | 25 |
| 14_42 | 42 | 2 | 1 | 16 |
| 17_42 | 42 | 2 | 2 | 32 |
| 6_42 | 42 | 2 | 2 | 30 |
| 71_42 | 42 | 2 | 1 | 17 |
| 1_43 | 43 | 2 | 2 | 30 |
| 1_43 | 43 | 2 | 2 | 33 |
| 45_43 | 43 | 2 | 2 | 27 |
| 71_43 | 43 | 2 | 1 | 12 |
| 13_44 | 44 | 2 | 2 | 31 |
| 33_44 | 44 | 2 | 2 | 21 |
| 34_44 | 44 | 2 | 2 | 22 |
| 71_44 | 44 | 2 | 2 | 23 |
| 39_45 | 45 | 2 | 2 | 25 |
| 47_45 | 45 | 2 | 2 | 26 |
| 5_45 | 45 | 2 | 2 | 23 |
| 62_45 | 45 | 2 | 1 | 14 |
| 7_45 | 45 | 2 | 2 | 15 |
| 71_45 | 45 | 2 | 2 | 20 |
| 72_45 | 45 | 2 | 1 | 15 |
| 28_46 | 46 | 2 | 1 | 17 |

| | | | | |
|------|---|---|---|----|
| 65_7 | 7 | 1 | 1 | 11 |
| 66_7 | 7 | 1 | 1 | 10 |
| 69_7 | 7 | 1 | 1 | 5 |
| 70_7 | 7 | 1 | 1 | 6 |
| 72_7 | 7 | 1 | 1 | 7 |
| 73_7 | 7 | 1 | 1 | 7 |
| 74_7 | 7 | 1 | 1 | 12 |
| 75_7 | 7 | 1 | 1 | 5 |
| 76_7 | 7 | 1 | 1 | 6 |
| 77_7 | 7 | 1 | 1 | 16 |
| 78_7 | 7 | 1 | 2 | 25 |
| 79_7 | 7 | 1 | 1 | 12 |
| 80_7 | 7 | 1 | 1 | 13 |
| 81_7 | 7 | 1 | 1 | 10 |
| 1_8 | 8 | 1 | 1 | 11 |
| 13_8 | 8 | 1 | 1 | 16 |
| 16_8 | 8 | 1 | 1 | 8 |
| 20_8 | 8 | 1 | 1 | 4 |
| 32_8 | 8 | 1 | 1 | 6 |
| 35_8 | 8 | 1 | 2 | 16 |
| 36_8 | 8 | 1 | 1 | 10 |
| 37_8 | 8 | 1 | 1 | 6 |
| 38_8 | 8 | 1 | 1 | 7 |
| 42_8 | 8 | 1 | 1 | 16 |
| 45_8 | 8 | 1 | 1 | 10 |
| 46_8 | 8 | 1 | 1 | 19 |
| 49_8 | 8 | 1 | 1 | 16 |
| 51_8 | 8 | 1 | 1 | 10 |

| | | | | |
|-------|----|---|---|----|
| 61_17 | 17 | 1 | 2 | 21 |
| 67_17 | 17 | 1 | 1 | 10 |
| 72_17 | 17 | 1 | 1 | 12 |
| 76_17 | 17 | 1 | 1 | 15 |
| 8_17 | 17 | 1 | 2 | 18 |
| 1_18 | 18 | 2 | 2 | 25 |
| 10_18 | 18 | 2 | 1 | 9 |
| 12_18 | 18 | 2 | 1 | 11 |
| 13_18 | 18 | 2 | 1 | 22 |
| 14_18 | 18 | 2 | 1 | 16 |
| 16_18 | 18 | 2 | 2 | 26 |
| 18_18 | 18 | 2 | 2 | 18 |
| 19_18 | 18 | 2 | 2 | 21 |
| 2_18 | 18 | 2 | 2 | 26 |
| 20_18 | 18 | 2 | 2 | 22 |
| 21_18 | 18 | 2 | 2 | 23 |
| 22_18 | 18 | 2 | 1 | 17 |
| 23_18 | 18 | 2 | 2 | 13 |
| 24_18 | 18 | 2 | 2 | 28 |
| 25_18 | 18 | 2 | 1 | 16 |
| 26_18 | 18 | 2 | 2 | 21 |
| 27_18 | 18 | 2 | 2 | 22 |
| 28_18 | 18 | 2 | 1 | 14 |
| 3_18 | 18 | 2 | 2 | 30 |
| 30_18 | 18 | 2 | 1 | 21 |
| 32_18 | 18 | 2 | 2 | 24 |
| 33_18 | 18 | 2 | 2 | 21 |
| 34_18 | 18 | 2 | 2 | 20 |

| | | | | |
|-------|----|---|---|----|
| 48_46 | 46 | 2 | 1 | 18 |
| 6_46 | 46 | 2 | 2 | 29 |
| 3_47 | 47 | 2 | 2 | 33 |
| 62_47 | 47 | 2 | 1 | 21 |
| 4_48 | 48 | 2 | 2 | 26 |
| 45_48 | 48 | 2 | 2 | 17 |
| 5_48 | 48 | 2 | 1 | 22 |
| 3_49 | 49 | 2 | 2 | 30 |
| 48_49 | 49 | 2 | 2 | 19 |
| 5_49 | 49 | 2 | 2 | 21 |
| 39_50 | 50 | 2 | 2 | 25 |
| 48_50 | 50 | 2 | 2 | 20 |
| 3_51 | 51 | 2 | 2 | 25 |
| 4_51 | 51 | 2 | 2 | 21 |
| 6_51 | 51 | 2 | 2 | 29 |
| 39_52 | 52 | 2 | 2 | 22 |
| 48_52 | 52 | 2 | 2 | 28 |
| 5_52 | 52 | 2 | 2 | 23 |
| 4_53 | 53 | 2 | 2 | 26 |
| 62_53 | 53 | 2 | 1 | 20 |
| 48_54 | 54 | 2 | 2 | 23 |
| 62_54 | 54 | 2 | 2 | 20 |
| 47_55 | 55 | 2 | 2 | 24 |
| 6_55 | 55 | 2 | 2 | 28 |
| 3_58 | 58 | 2 | 2 | 29 |
| 3_60 | 60 | 2 | 2 | 21 |
| 3_61 | 61 | 2 | 2 | 24 |
| 5_61 | 61 | 2 | 2 | 31 |

| | | | | |
|------|---|---|---|----|
| 53_8 | 8 | 1 | 1 | 12 |
| 55_8 | 8 | 1 | 1 | 3 |
| 60_8 | 8 | 1 | 1 | 13 |
| 63_8 | 8 | 1 | 1 | 12 |
| 65_8 | 8 | 1 | 1 | 11 |

| | | | | |
|-------|----|---|---|----|
| 35_18 | 18 | 2 | 2 | 20 |
| 36_18 | 18 | 2 | 2 | 21 |
| 37_18 | 18 | 2 | 1 | 18 |
| 42_18 | 18 | 2 | 2 | 16 |
| 44_18 | 18 | 2 | 2 | 23 |

| | | | | |
|------|----|---|---|----|
| 6_61 | 61 | 2 | 2 | 26 |
| 4_62 | 62 | 2 | 2 | 22 |
| 4_63 | 63 | 2 | 2 | 27 |
| 6_67 | 67 | 2 | 2 | 29 |
| 6_69 | 69 | 2 | 2 | 33 |

APPENDIX B Anthropometric model results for Fg-net database

| Image ID | Actual Age | Estimated Age |
|----------|------------|---------------|
| 9_0 | 0 | 3 |
| 13_0 | 0 | 3 |
| 15_0 | 0 | 3 |
| 19_0 | 0 | 3 |
| 22_0 | 0 | 3 |
| 23_0 | 0 | 3 |
| 24_0 | 0 | 3 |
| 25_0 | 0 | 4 |
| 26_0 | 0 | 3 |
| 30_0 | 0 | 8 |
| 31_0 | 0 | 3 |
| 35_0 | 0 | 4 |
| 36_0 | 0 | 5 |
| 37_0 | 0 | 3 |
| 38_0 | 0 | 2 |
| 40_0 | 0 | 10 |
| 41_0 | 0 | 3 |
| 42_0 | 0 | 3 |
| 43_0 | 0 | 3 |
| 46_0 | 0 | 3 |
| 48_0 | 0 | 4 |
| 50_0 | 0 | 3 |
| 51_0 | 0 | 3 |

| Image ID | Actual Age | Estimated Age |
|----------|------------|---------------|
| 54_6 | 6 | 8 |
| 55_6 | 6 | 17 |
| 56_6 | 6 | 11 |
| 57_6 | 6 | 9 |
| 58_6 | 6 | 14 |
| 59_6 | 6 | 11 |
| 60_6 | 6 | 0 |
| 61_6 | 6 | 12 |
| 65_6 | 6 | 9 |
| 65_6 | 6 | 6 |
| 66_6 | 6 | 4 |
| 66_6 | 6 | 13 |
| 69_6 | 6 | 13 |
| 70_6 | 6 | 5 |
| 73_6 | 6 | 7 |
| 74_6 | 6 | 6 |
| 75_6 | 6 | 4 |
| 76_6 | 6 | 5 |
| 77_6 | 6 | 5 |
| 78_6 | 6 | 22 |
| 79_6 | 6 | 6 |
| 80_6 | 6 | 5 |
| 81_6 | 6 | 9 |

| Image ID | Actual Age | Estimated Age |
|----------|------------|---------------|
| 65_13 | 13 | 31 |
| 68_13 | 13 | 22 |
| 69_13 | 13 | 21 |
| 72_13 | 13 | 23 |
| 73_13 | 13 | 17 |
| 74_13 | 13 | 11 |
| 76_13 | 13 | 9 |
| 77_13 | 13 | 11 |
| 78_13 | 13 | 25 |
| 79_13 | 13 | 15 |
| 80_13 | 13 | 26 |
| 1_14 | 14 | 21 |
| 9_14 | 14 | 10 |
| 11_14 | 14 | 18 |
| 12_14 | 14 | 9 |
| 14_14 | 14 | 16 |
| 15_14 | 14 | 9 |
| 16_14 | 14 | 26 |
| 22_14 | 14 | 24 |
| 23_14 | 14 | 20 |
| 28_14 | 14 | 20 |
| 31_14 | 14 | 21 |
| 33_14 | 14 | 8 |

| Image ID | Actual Age | Estimated Age |
|----------|------------|---------------|
| 18_22 | 22 | 16 |
| 20_22 | 22 | 22 |
| 23_22 | 22 | 24 |
| 25_22 | 22 | 16 |
| 27_22 | 22 | 24 |
| 29_22 | 22 | 23 |
| 50_22 | 22 | 21 |
| 55_22 | 22 | 12 |
| 63_22 | 22 | 17 |
| 71_22 | 22 | 15 |
| 82_22 | 22 | 29 |
| 2_23 | 23 | 27 |
| 3_23 | 23 | 35 |
| 7_23 | 23 | 13 |
| 12_23 | 23 | 35 |
| 13_23 | 23 | 13 |
| 19_23 | 23 | 26 |
| 21_23 | 23 | 26 |
| 22_23 | 23 | 18 |
| 24_23 | 23 | 24 |
| 25_23 | 23 | 21 |
| 29_23 | 23 | 24 |
| 30_23 | 23 | 22 |

| | | |
|------|---|----|
| 53_0 | 0 | 8 |
| 54_0 | 0 | 6 |
| 57_0 | 0 | 3 |
| 58_0 | 0 | 14 |
| 63_0 | 0 | 5 |
| 66_0 | 0 | 3 |
| 68_0 | 0 | 4 |
| 69_0 | 0 | 3 |
| 70_0 | 0 | 3 |
| 71_0 | 0 | 8 |
| 73_0 | 0 | 3 |
| 74_0 | 0 | 3 |
| 75_0 | 0 | 3 |
| 76_0 | 0 | 3 |
| 77_0 | 0 | 3 |
| 78_0 | 0 | 3 |
| 79_0 | 0 | 3 |
| 80_0 | 0 | 4 |
| 81_0 | 0 | 3 |
| 82_0 | 0 | 3 |
| 7_1 | 1 | 3 |
| 9_1 | 1 | 3 |
| 10_1 | 1 | 3 |
| 15_1 | 1 | 3 |
| 16_1 | 1 | 5 |
| 29_1 | 1 | 13 |
| 35_1 | 1 | 3 |
| 36_1 | 1 | 5 |

| | | |
|------|---|----|
| 2_7 | 7 | 10 |
| 10_7 | 7 | 5 |
| 10_7 | 7 | 5 |
| 11_7 | 7 | 9 |
| 12_7 | 7 | 5 |
| 15_7 | 7 | 8 |
| 16_7 | 7 | 15 |
| 17_7 | 7 | 7 |
| 19_7 | 7 | 14 |
| 22_7 | 7 | 18 |
| 23_7 | 7 | 19 |
| 24_7 | 7 | 9 |
| 25_7 | 7 | 14 |
| 26_7 | 7 | 15 |
| 30_7 | 7 | 17 |
| 31_7 | 7 | 13 |
| 35_7 | 7 | 12 |
| 39_7 | 7 | 20 |
| 40_7 | 7 | 9 |
| 44_7 | 7 | 22 |
| 49_7 | 7 | 14 |
| 52_7 | 7 | 22 |
| 57_7 | 7 | 19 |
| 59_7 | 7 | 20 |
| 60_7 | 7 | 23 |
| 61_7 | 7 | 10 |
| 65_7 | 7 | 8 |
| 65_7 | 7 | 11 |

| | | |
|-------|----|----|
| 35_14 | 14 | 17 |
| 38_14 | 14 | 23 |
| 40_14 | 14 | 18 |
| 42_14 | 14 | 18 |
| 46_14 | 14 | 21 |
| 50_14 | 14 | 28 |
| 51_14 | 14 | 22 |
| 52_14 | 14 | 29 |
| 55_14 | 14 | 22 |
| 59_14 | 14 | 25 |
| 67_14 | 14 | 22 |
| 68_14 | 14 | 9 |
| 70_14 | 14 | 19 |
| 72_14 | 14 | 17 |
| 73_14 | 14 | 22 |
| 74_14 | 14 | 22 |
| 76_14 | 14 | 16 |
| 77_14 | 14 | 18 |
| 78_14 | 14 | 10 |
| 80_14 | 14 | 21 |
| 2_15 | 15 | 19 |
| 10_15 | 15 | 18 |
| 11_15 | 15 | 20 |
| 15_15 | 15 | 18 |
| 17_15 | 15 | 24 |
| 19_15 | 15 | 18 |
| 25_15 | 15 | 19 |
| 26_15 | 15 | 16 |

| | | |
|-------|----|----|
| 35_23 | 23 | 28 |
| 35_23 | 23 | 23 |
| 38_23 | 23 | 19 |
| 43_23 | 23 | 26 |
| 47_23 | 23 | 10 |
| 55_23 | 23 | 24 |
| 57_23 | 23 | 17 |
| 67_23 | 23 | 23 |
| 71_23 | 23 | 19 |
| 82_23 | 23 | 22 |
| 5_24 | 24 | 19 |
| 6_24 | 24 | 26 |
| 12_24 | 24 | 23 |
| 20_24 | 24 | 23 |
| 32_24 | 24 | 16 |
| 41_24 | 24 | 19 |
| 42_24 | 24 | 26 |
| 51_24 | 24 | 30 |
| 71_24 | 24 | 19 |
| 3_25 | 25 | 35 |
| 12_25 | 25 | 21 |
| 13_25 | 25 | 20 |
| 18_25 | 25 | 26 |
| 22_25 | 25 | 16 |
| 23_25 | 25 | 22 |
| 24_25 | 25 | 25 |
| 27_25 | 25 | 28 |
| 33_25 | 25 | 8 |

| | | |
|------|---|----|
| 37_1 | 1 | 4 |
| 38_1 | 1 | 8 |
| 42_1 | 1 | 3 |
| 44_1 | 1 | 3 |
| 46_1 | 1 | 15 |
| 53_1 | 1 | 8 |
| 56_1 | 1 | 3 |
| 58_1 | 1 | 22 |
| 64_1 | 1 | 4 |
| 70_1 | 1 | 4 |
| 73_1 | 1 | 4 |
| 74_1 | 1 | 3 |
| 75_1 | 1 | 4 |
| 76_1 | 1 | 3 |
| 77_1 | 1 | 3 |
| 78_1 | 1 | 3 |
| 79_1 | 1 | 8 |
| 80_1 | 1 | 4 |
| 81_1 | 1 | 3 |
| 1_2 | 2 | 3 |
| 11_2 | 2 | 3 |
| 20_2 | 2 | 8 |
| 26_2 | 2 | 5 |
| 27_2 | 2 | 14 |
| 31_2 | 2 | 9 |
| 33_2 | 2 | 3 |
| 34_2 | 2 | 3 |
| 37_2 | 2 | 2 |

| | | |
|------|---|----|
| 66_7 | 7 | 22 |
| 69_7 | 7 | 6 |
| 70_7 | 7 | 14 |
| 72_7 | 7 | 11 |
| 73_7 | 7 | 5 |
| 74_7 | 7 | 8 |
| 75_7 | 7 | 7 |
| 76_7 | 7 | 4 |
| 77_7 | 7 | 14 |
| 78_7 | 7 | 20 |
| 79_7 | 7 | 10 |
| 80_7 | 7 | 13 |
| 81_7 | 7 | 8 |
| 1_8 | 8 | 7 |
| 8_8 | 8 | 13 |
| 13_8 | 8 | 6 |
| 16_8 | 8 | 7 |
| 20_8 | 8 | 4 |
| 32_8 | 8 | 9 |
| 35_8 | 8 | 13 |
| 36_8 | 8 | 18 |
| 37_8 | 8 | 5 |
| 38_8 | 8 | 10 |
| 42_8 | 8 | 22 |
| 45_8 | 8 | 6 |
| 46_8 | 8 | 18 |
| 49_8 | 8 | 17 |
| 51_8 | 8 | 13 |

| | | |
|-------|----|----|
| 31_15 | 15 | 22 |
| 32_15 | 15 | 15 |
| 34_15 | 15 | 24 |
| 36_15 | 15 | 14 |
| 39_15 | 15 | 14 |
| 43_15 | 15 | 19 |
| 44_15 | 15 | 23 |
| 47_15 | 15 | 10 |
| 48_15 | 15 | 23 |
| 49_15 | 15 | 21 |
| 51_15 | 15 | 16 |
| 53_15 | 15 | 22 |
| 56_15 | 15 | 21 |
| 58_15 | 15 | 16 |
| 61_15 | 15 | 20 |
| 62_15 | 15 | 23 |
| 64_15 | 15 | 22 |
| 73_15 | 15 | 12 |
| 74_15 | 15 | 26 |
| 76_15 | 15 | 23 |
| 77_15 | 15 | 21 |
| 78_15 | 15 | 20 |
| 1_16 | 16 | 22 |
| 2_16 | 16 | 25 |
| 8_16 | 16 | 19 |
| 9_16 | 16 | 8 |
| 9_16 | 16 | 12 |
| 10_16 | 16 | 21 |

| | | |
|-------|----|----|
| 34_25 | 25 | 28 |
| 44_25 | 25 | 24 |
| 45_25 | 25 | 26 |
| 57_25 | 25 | 19 |
| 61_25 | 25 | 16 |
| 63_25 | 25 | 20 |
| 72_25 | 25 | 21 |
| 82_25 | 25 | 26 |
| 2_26 | 26 | 25 |
| 4_26 | 26 | 25 |
| 7_26 | 26 | 16 |
| 12_26 | 26 | 22 |
| 17_26 | 26 | 22 |
| 20_26 | 26 | 26 |
| 22_26 | 26 | 21 |
| 28_26 | 26 | 23 |
| 30_26 | 26 | 23 |
| 61_26 | 26 | 20 |
| 67_26 | 26 | 19 |
| 11_27 | 27 | 28 |
| 12_27 | 27 | 18 |
| 19_27 | 27 | 25 |
| 21_27 | 27 | 23 |
| 22_27 | 27 | 23 |
| 43_27 | 27 | 24 |
| 47_27 | 27 | 9 |
| 48_27 | 27 | 21 |
| 71_27 | 27 | 11 |

| | | |
|------|---|----|
| 39_2 | 2 | 8 |
| 40_2 | 2 | 9 |
| 41_2 | 2 | 3 |
| 46_2 | 2 | 7 |
| 51_2 | 2 | 7 |
| 52_2 | 2 | 4 |
| 53_2 | 2 | 5 |
| 54_2 | 2 | 27 |
| 56_2 | 2 | 5 |
| 58_2 | 2 | 7 |
| 59_2 | 2 | 15 |
| 59_2 | 2 | 10 |
| 60_2 | 2 | 8 |
| 63_2 | 2 | 6 |
| 65_2 | 2 | 3 |
| 65_2 | 2 | 3 |
| 66_2 | 2 | 5 |
| 66_2 | 2 | 10 |
| 69_2 | 2 | 12 |
| 70_2 | 2 | 4 |
| 72_2 | 2 | 7 |
| 73_2 | 2 | 8 |
| 74_2 | 2 | 5 |
| 75_2 | 2 | 4 |
| 76_2 | 2 | 3 |
| 77_2 | 2 | 3 |
| 78_2 | 2 | 11 |
| 79_2 | 2 | 7 |

| | | |
|------|---|----|
| 53_8 | 8 | 20 |
| 55_8 | 8 | 5 |
| 60_8 | 8 | 19 |
| 63_8 | 8 | 22 |
| 65_8 | 8 | 7 |
| 66_8 | 8 | 13 |
| 70_8 | 8 | 3 |
| 73_8 | 8 | 7 |
| 74_8 | 8 | 7 |
| 75_8 | 8 | 8 |
| 76_8 | 8 | 4 |
| 77_8 | 8 | 7 |
| 78_8 | 8 | 17 |
| 79_8 | 8 | 6 |
| 80_8 | 8 | 17 |
| 81_8 | 8 | 11 |
| 9_9 | 9 | 5 |
| 10_9 | 9 | 19 |
| 15_9 | 9 | 18 |
| 23_9 | 9 | 17 |
| 31_9 | 9 | 21 |
| 35_9 | 9 | 18 |
| 37_9 | 9 | 15 |
| 40_9 | 9 | 15 |
| 41_9 | 9 | 15 |
| 47_9 | 9 | 13 |
| 48_9 | 9 | 15 |
| 54_9 | 9 | 28 |

| | | |
|-------|----|----|
| 13_16 | 16 | 18 |
| 14_16 | 16 | 21 |
| 16_16 | 16 | 23 |
| 18_16 | 16 | 26 |
| 20_16 | 16 | 19 |
| 21_16 | 16 | 24 |
| 22_16 | 16 | 22 |
| 23_16 | 16 | 19 |
| 27_16 | 16 | 27 |
| 28_16 | 16 | 12 |
| 29_16 | 16 | 17 |
| 30_16 | 16 | 25 |
| 31_16 | 16 | 20 |
| 34_16 | 16 | 24 |
| 35_16 | 16 | 12 |
| 39_16 | 16 | 22 |
| 40_16 | 16 | 23 |
| 46_16 | 16 | 24 |
| 48_16 | 16 | 25 |
| 49_16 | 16 | 22 |
| 50_16 | 16 | 15 |
| 51_16 | 16 | 21 |
| 52_16 | 16 | 26 |
| 54_16 | 16 | 25 |
| 57_16 | 16 | 22 |
| 59_16 | 16 | 19 |
| 62_16 | 16 | 5 |
| 73_16 | 16 | 20 |

| | | |
|-------|----|----|
| 72_27 | 27 | 18 |
| 82_27 | 27 | 25 |
| 1_28 | 28 | 28 |
| 4_28 | 28 | 23 |
| 6_28 | 28 | 23 |
| 18_28 | 28 | 4 |
| 22_28 | 28 | 19 |
| 24_28 | 28 | 24 |
| 25_28 | 28 | 20 |
| 28_28 | 28 | 16 |
| 32_28 | 28 | 20 |
| 42_28 | 28 | 25 |
| 45_28 | 28 | 28 |
| 67_28 | 28 | 18 |
| 1_29 | 29 | 32 |
| 2_29 | 29 | 28 |
| 8_29 | 29 | 32 |
| 17_29 | 29 | 17 |
| 18_29 | 29 | 27 |
| 23_29 | 29 | 25 |
| 29_29 | 29 | 28 |
| 61_29 | 29 | 19 |
| 72_29 | 29 | 29 |
| 4_30 | 30 | 12 |
| 5_30 | 30 | 24 |
| 8_30 | 30 | 26 |
| 11_30 | 30 | 24 |
| 12_30 | 30 | 22 |

| | | |
|------|---|----|
| 80_2 | 2 | 4 |
| 81_2 | 2 | 10 |
| 2_3 | 3 | 12 |
| 8_3 | 3 | 3 |
| 9_3 | 3 | 5 |
| 14_3 | 3 | 3 |
| 15_3 | 3 | 4 |
| 16_3 | 3 | 9 |
| 19_3 | 3 | 3 |
| 21_3 | 3 | 5 |
| 23_3 | 3 | 3 |
| 25_3 | 3 | 12 |
| 31_3 | 3 | 5 |
| 35_3 | 3 | 3 |
| 36_3 | 3 | 6 |
| 38_3 | 3 | 8 |
| 40_3 | 3 | 19 |
| 40_3 | 3 | 14 |
| 43_3 | 3 | 5 |
| 44_3 | 3 | 5 |
| 45_3 | 3 | 4 |
| 50_3 | 3 | 6 |
| 53_3 | 3 | 6 |
| 56_3 | 3 | 6 |
| 58_3 | 3 | 18 |
| 59_3 | 3 | 13 |
| 62_3 | 3 | 12 |
| 64_3 | 3 | 8 |

| | | |
|-------|----|----|
| 63_9 | 9 | 23 |
| 65_9 | 9 | 9 |
| 66_9 | 9 | 23 |
| 68_9 | 9 | 8 |
| 69_9 | 9 | 20 |
| 70_9 | 9 | 11 |
| 73_9 | 9 | 8 |
| 74_9 | 9 | 8 |
| 76_9 | 9 | 8 |
| 77_9 | 9 | 13 |
| 78_9 | 9 | 14 |
| 79_9 | 9 | 10 |
| 80_9 | 9 | 11 |
| 1_10 | 10 | 15 |
| 10_10 | 10 | 3 |
| 15_10 | 10 | 10 |
| 16_10 | 10 | 11 |
| 24_10 | 10 | 22 |
| 29_10 | 10 | 13 |
| 30_10 | 10 | 15 |
| 32_10 | 10 | 15 |
| 33_10 | 10 | 13 |
| 38_10 | 10 | 14 |
| 39_10 | 10 | 14 |
| 40_10 | 10 | 20 |
| 42_10 | 10 | 22 |
| 43_10 | 10 | 17 |
| 46_10 | 10 | 9 |

| | | |
|-------|----|----|
| 76_16 | 16 | 13 |
| 77_16 | 16 | 20 |
| 82_16 | 16 | 22 |
| 8_17 | 17 | 16 |
| 11_17 | 17 | 15 |
| 15_17 | 17 | 24 |
| 16_17 | 17 | 24 |
| 17_17 | 17 | 18 |
| 24_17 | 17 | 23 |
| 26_17 | 17 | 17 |
| 30_17 | 17 | 20 |
| 36_17 | 17 | 18 |
| 37_17 | 17 | 18 |
| 38_17 | 17 | 22 |
| 39_17 | 17 | 25 |
| 43_17 | 17 | 13 |
| 44_17 | 17 | 20 |
| 45_17 | 17 | 23 |
| 46_17 | 17 | 23 |
| 48_17 | 17 | 15 |
| 49_17 | 17 | 20 |
| 51_17 | 17 | 21 |
| 52_17 | 17 | 26 |
| 54_17 | 17 | 20 |
| 57_17 | 17 | 20 |
| 58_17 | 17 | 17 |
| 60_17 | 17 | 13 |
| 61_17 | 17 | 21 |

| | | |
|-------|----|----|
| 13_30 | 30 | 24 |
| 14_30 | 30 | 20 |
| 19_30 | 30 | 15 |
| 20_30 | 30 | 28 |
| 21_30 | 30 | 23 |
| 22_30 | 30 | 10 |
| 24_30 | 30 | 26 |
| 27_30 | 30 | 26 |
| 33_30 | 30 | 22 |
| 34_30 | 30 | 30 |
| 48_30 | 30 | 19 |
| 61_30 | 30 | 22 |
| 62_30 | 30 | 31 |
| 67_30 | 30 | 24 |
| 2_31 | 31 | 25 |
| 5_31 | 31 | 25 |
| 6_31 | 31 | 23 |
| 8_31 | 31 | 23 |
| 29_31 | 31 | 22 |
| 82_31 | 31 | 30 |
| 12_32 | 32 | 17 |
| 17_32 | 32 | 19 |
| 45_32 | 32 | 26 |
| 61_32 | 32 | 14 |
| 1_33 | 33 | 26 |
| 8_33 | 33 | 19 |
| 18_33 | 33 | 12 |
| 29_33 | 33 | 22 |

| | | |
|------|---|----|
| 65_3 | 3 | 4 |
| 65_3 | 3 | 6 |
| 66_3 | 3 | 6 |
| 68_3 | 3 | 4 |
| 69_3 | 3 | 5 |
| 70_3 | 3 | 4 |
| 73_3 | 3 | 5 |
| 74_3 | 3 | 8 |
| 75_3 | 3 | 5 |
| 76_3 | 3 | 3 |
| 77_3 | 3 | 4 |
| 78_3 | 3 | 4 |
| 79_3 | 3 | 4 |
| 80_3 | 3 | 3 |
| 81_3 | 3 | 5 |
| 82_3 | 3 | 5 |
| 2_4 | 4 | 18 |
| 10_4 | 4 | 4 |
| 12_4 | 4 | 15 |
| 15_4 | 4 | 5 |
| 16_4 | 4 | 1 |
| 20_4 | 4 | 4 |
| 26_4 | 4 | 9 |
| 29_4 | 4 | 21 |
| 30_4 | 4 | 24 |
| 31_4 | 4 | 4 |
| 34_4 | 4 | 4 |
| 37_4 | 4 | 8 |

| | | |
|-------|----|----|
| 48_10 | 10 | 11 |
| 49_10 | 10 | 18 |
| 50_10 | 10 | 27 |
| 52_10 | 10 | 22 |
| 53_10 | 10 | 20 |
| 54_10 | 10 | 14 |
| 56_10 | 10 | 20 |
| 58_10 | 10 | 19 |
| 60_10 | 10 | 7 |
| 61_10 | 10 | 34 |
| 64_10 | 10 | 25 |
| 65_10 | 10 | 22 |
| 66_10 | 10 | 19 |
| 68_10 | 10 | 11 |
| 68_10 | 10 | 6 |
| 69_10 | 10 | 24 |
| 71_10 | 10 | 23 |
| 74_10 | 10 | 12 |
| 75_10 | 10 | 14 |
| 76_10 | 10 | 6 |
| 77_10 | 10 | 11 |
| 78_10 | 10 | 24 |
| 79_10 | 10 | 12 |
| 80_10 | 10 | 7 |
| 81_10 | 10 | 19 |
| 9_11 | 11 | 4 |
| 11_11 | 11 | 11 |
| 18_11 | 11 | 24 |

| | | |
|-------|----|----|
| 67_17 | 17 | 19 |
| 72_17 | 17 | 19 |
| 76_17 | 17 | 16 |
| 1_18 | 18 | 24 |
| 2_18 | 18 | 22 |
| 3_18 | 18 | 30 |
| 5_18 | 18 | 24 |
| 7_18 | 18 | 17 |
| 8_18 | 18 | 23 |
| 9_18 | 18 | 16 |
| 10_18 | 18 | 7 |
| 12_18 | 18 | 13 |
| 13_18 | 18 | 17 |
| 14_18 | 18 | 22 |
| 16_18 | 18 | 25 |
| 18_18 | 18 | 17 |
| 19_18 | 18 | 25 |
| 20_18 | 18 | 19 |
| 21_18 | 18 | 23 |
| 22_18 | 18 | 11 |
| 23_18 | 18 | 13 |
| 24_18 | 18 | 22 |
| 25_18 | 18 | 11 |
| 26_18 | 18 | 26 |
| 27_18 | 18 | 23 |
| 28_18 | 18 | 14 |
| 30_18 | 18 | 22 |
| 32_18 | 18 | 12 |

| | | |
|-------|----|----|
| 32_33 | 33 | 21 |
| 47_33 | 33 | 20 |
| 48_33 | 33 | 10 |
| 63_33 | 33 | 21 |
| 67_33 | 33 | 22 |
| 11_34 | 34 | 26 |
| 12_34 | 34 | 15 |
| 13_34 | 34 | 16 |
| 18_34 | 34 | 17 |
| 25_34 | 34 | 20 |
| 28_34 | 34 | 17 |
| 38_34 | 34 | 23 |
| 72_34 | 34 | 28 |
| 3_35 | 35 | 36 |
| 5_35 | 35 | 23 |
| 8_35 | 35 | 21 |
| 21_35 | 35 | 23 |
| 28_35 | 35 | 32 |
| 32_35 | 35 | 19 |
| 33_35 | 35 | 23 |
| 34_35 | 35 | 23 |
| 39_35 | 35 | 16 |
| 62_35 | 35 | 30 |
| 71_35 | 35 | 27 |
| 2_36 | 36 | 28 |
| 6_36 | 36 | 32 |
| 12_36 | 36 | 16 |
| 14_36 | 36 | 26 |

| | | |
|------|---|----|
| 38_4 | 4 | 13 |
| 41_4 | 4 | 7 |
| 42_4 | 4 | 15 |
| 43_4 | 4 | 22 |
| 46_4 | 4 | 12 |
| 49_4 | 4 | 11 |
| 52_4 | 4 | 8 |
| 53_4 | 4 | 14 |
| 54_4 | 4 | 21 |
| 55_4 | 4 | 6 |
| 56_4 | 4 | 8 |
| 58_4 | 4 | 22 |
| 59_4 | 4 | 19 |
| 60_4 | 4 | 20 |
| 61_4 | 4 | 4 |
| 63_4 | 4 | 5 |
| 64_4 | 4 | 20 |
| 65_4 | 4 | 3 |
| 66_4 | 4 | 9 |
| 67_4 | 4 | 7 |
| 68_4 | 4 | 5 |
| 69_4 | 4 | 7 |
| 73_4 | 4 | 6 |
| 74_4 | 4 | 3 |
| 76_4 | 4 | 5 |
| 77_4 | 4 | 4 |
| 78_4 | 4 | 18 |
| 79_4 | 4 | 7 |

| | | |
|-------|----|----|
| 20_11 | 11 | 28 |
| 21_11 | 11 | 20 |
| 22_11 | 11 | 9 |
| 26_11 | 11 | 17 |
| 27_11 | 11 | 15 |
| 29_11 | 11 | 23 |
| 31_11 | 11 | 22 |
| 34_11 | 11 | 22 |
| 36_11 | 11 | 8 |
| 37_11 | 11 | 18 |
| 38_11 | 11 | 19 |
| 39_11 | 11 | 16 |
| 47_11 | 11 | 16 |
| 48_11 | 11 | 6 |
| 53_11 | 11 | 13 |
| 54_11 | 11 | 19 |
| 60_11 | 11 | 20 |
| 65_11 | 11 | 14 |
| 66_11 | 11 | 15 |
| 68_11 | 11 | 21 |
| 69_11 | 11 | 15 |
| 72_11 | 11 | 11 |
| 73_11 | 11 | 20 |
| 74_11 | 11 | 13 |
| 75_11 | 11 | 14 |
| 76_11 | 11 | 13 |
| 77_11 | 11 | 6 |
| 78_11 | 11 | 23 |

| | | |
|-------|----|----|
| 33_18 | 18 | 21 |
| 34_18 | 18 | 22 |
| 35_18 | 18 | 22 |
| 36_18 | 18 | 20 |
| 37_18 | 18 | 11 |
| 42_18 | 18 | 21 |
| 44_18 | 18 | 24 |
| 45_18 | 18 | 24 |
| 46_18 | 18 | 17 |
| 47_18 | 18 | 17 |
| 48_18 | 18 | 19 |
| 50_18 | 18 | 25 |
| 51_18 | 18 | 28 |
| 52_18 | 18 | 25 |
| 53_18 | 18 | 25 |
| 54_18 | 18 | 21 |
| 57_18 | 18 | 17 |
| 61_18 | 18 | 20 |
| 62_18 | 18 | 22 |
| 63_18 | 18 | 22 |
| 71_18 | 18 | 13 |
| 82_18 | 18 | 25 |
| 1_19 | 19 | 24 |
| 4_19 | 19 | 22 |
| 13_19 | 19 | 18 |
| 15_19 | 19 | 19 |
| 16_19 | 19 | 22 |
| 17_19 | 19 | 21 |

| | | |
|-------|----|----|
| 17_36 | 36 | 25 |
| 18_36 | 36 | 20 |
| 20_36 | 36 | 21 |
| 27_36 | 36 | 25 |
| 4_37 | 37 | 26 |
| 7_37 | 37 | 21 |
| 28_37 | 37 | 15 |
| 2_38 | 38 | 20 |
| 3_38 | 38 | 36 |
| 7_38 | 38 | 19 |
| 17_38 | 38 | 23 |
| 62_38 | 38 | 20 |
| 7_39 | 39 | 19 |
| 21_39 | 39 | 24 |
| 25_39 | 39 | 21 |
| 33_39 | 39 | 15 |
| 34_39 | 39 | 32 |
| 67_39 | 39 | 18 |
| 1_40 | 40 | 27 |
| 4_40 | 40 | 27 |
| 5_40 | 40 | 16 |
| 6_40 | 40 | 24 |
| 11_40 | 40 | 22 |
| 14_40 | 40 | 31 |
| 32_40 | 40 | 24 |
| 45_40 | 40 | 33 |
| 71_40 | 40 | 28 |
| 8_41 | 41 | 22 |

| | | |
|------|---|----|
| 80_4 | 4 | 9 |
| 81_4 | 4 | 13 |
| 1_5 | 5 | 4 |
| 2_5 | 5 | 12 |
| 9_5 | 5 | 5 |
| 10_5 | 5 | 4 |
| 11_5 | 5 | 6 |
| 15_5 | 5 | 4 |
| 16_5 | 5 | 10 |
| 17_5 | 5 | 14 |
| 19_5 | 5 | 19 |
| 21_5 | 5 | 7 |
| 23_5 | 5 | 19 |
| 24_5 | 5 | 5 |
| 29_5 | 5 | 15 |
| 30_5 | 5 | 16 |
| 33_5 | 5 | 5 |
| 35_5 | 5 | 9 |
| 36_5 | 5 | 17 |
| 38_5 | 5 | 14 |
| 39_5 | 5 | 15 |
| 40_5 | 5 | 22 |
| 42_5 | 5 | 8 |
| 43_5 | 5 | 3 |
| 44_5 | 5 | 23 |
| 47_5 | 5 | 17 |
| 49_5 | 5 | 4 |
| 51_5 | 5 | 6 |

| | | |
|-------|----|----|
| 79_11 | 11 | 11 |
| 81_11 | 11 | 25 |
| 2_12 | 12 | 20 |
| 8_12 | 12 | 20 |
| 10_12 | 12 | 12 |
| 12_12 | 12 | 15 |
| 14_12 | 12 | 18 |
| 15_12 | 12 | 10 |
| 16_12 | 12 | 20 |
| 17_12 | 12 | 17 |
| 19_12 | 12 | 21 |
| 25_12 | 12 | 23 |
| 31_12 | 12 | 20 |
| 35_12 | 12 | 5 |
| 40_12 | 12 | 23 |
| 42_12 | 12 | 22 |
| 45_12 | 12 | 15 |
| 46_12 | 12 | 21 |
| 47_12 | 12 | 6 |
| 49_12 | 12 | 21 |
| 51_12 | 12 | 19 |
| 53_12 | 12 | 21 |
| 54_12 | 12 | 20 |
| 55_12 | 12 | 21 |
| 56_12 | 12 | 8 |
| 57_12 | 12 | 12 |
| 59_12 | 12 | 15 |
| 60_12 | 12 | 14 |

| | | |
|-------|----|----|
| 24_19 | 19 | 23 |
| 25_19 | 19 | 22 |
| 26_19 | 19 | 26 |
| 31_19 | 19 | 24 |
| 36_19 | 19 | 21 |
| 37_19 | 19 | 16 |
| 39_19 | 19 | 18 |
| 40_19 | 19 | 23 |
| 41_19 | 19 | 11 |
| 43_19 | 19 | 21 |
| 45_19 | 19 | 20 |
| 52_19 | 19 | 23 |
| 54_19 | 19 | 28 |
| 60_19 | 19 | 18 |
| 61_19 | 19 | 14 |
| 64_19 | 19 | 24 |
| 72_19 | 19 | 22 |
| 2_20 | 20 | 24 |
| 3_20 | 20 | 30 |
| 11_20 | 20 | 23 |
| 20_20 | 20 | 11 |
| 21_20 | 20 | 22 |
| 22_20 | 20 | 7 |
| 27_20 | 20 | 27 |
| 28_20 | 20 | 18 |
| 29_20 | 20 | 26 |
| 30_20 | 20 | 20 |
| 32_20 | 20 | 16 |

| | | |
|-------|----|----|
| 13_41 | 41 | 18 |
| 27_41 | 41 | 24 |
| 28_41 | 41 | 21 |
| 62_41 | 41 | 26 |
| 72_41 | 41 | 27 |
| 6_42 | 42 | 14 |
| 11_42 | 42 | 32 |
| 14_42 | 42 | 23 |
| 17_42 | 42 | 22 |
| 71_42 | 42 | 21 |
| 1_43 | 43 | 27 |
| 1_43 | 43 | 26 |
| 45_43 | 43 | 26 |
| 71_43 | 43 | 16 |
| 13_44 | 44 | 26 |
| 33_44 | 44 | 16 |
| 34_44 | 44 | 24 |
| 71_44 | 44 | 21 |
| 5_45 | 45 | 23 |
| 7_45 | 45 | 17 |
| 39_45 | 45 | 23 |
| 47_45 | 45 | 15 |
| 62_45 | 45 | 21 |
| 71_45 | 45 | 22 |
| 72_45 | 45 | 34 |
| 6_46 | 46 | 26 |
| 28_46 | 46 | 18 |
| 48_46 | 46 | 19 |

| | | |
|------|---|----|
| 55_5 | 5 | 19 |
| 57_5 | 5 | 12 |
| 58_5 | 5 | 20 |
| 60_5 | 5 | 10 |
| 69_5 | 5 | 6 |
| 70_5 | 5 | 11 |
| 73_5 | 5 | 5 |
| 74_5 | 5 | 4 |
| 75_5 | 5 | 5 |
| 76_5 | 5 | 4 |
| 78_5 | 5 | 5 |
| 79_5 | 5 | 6 |
| 80_5 | 5 | 6 |
| 81_5 | 5 | 5 |
| 8_6 | 6 | 10 |
| 10_6 | 6 | 4 |
| 18_6 | 6 | 9 |
| 21_6 | 6 | 13 |
| 26_6 | 6 | 18 |
| 31_6 | 6 | 23 |
| 32_6 | 6 | 6 |
| 36_6 | 6 | 13 |
| 37_6 | 6 | 5 |
| 40_6 | 6 | 16 |
| 41_6 | 6 | 7 |
| 42_6 | 6 | 7 |
| 45_6 | 6 | 11 |
| 46_6 | 6 | 13 |

| | | |
|-------|----|----|
| 65_12 | 12 | 14 |
| 68_12 | 12 | 15 |
| 70_12 | 12 | 12 |
| 73_12 | 12 | 19 |
| 74_12 | 12 | 16 |
| 76_12 | 12 | 7 |
| 77_12 | 12 | 17 |
| 78_12 | 12 | 16 |
| 79_12 | 12 | 12 |
| 80_12 | 12 | 18 |
| 81_12 | 12 | 13 |
| 8_13 | 13 | 22 |
| 9_13 | 13 | 17 |
| 11_13 | 13 | 19 |
| 20_13 | 13 | 15 |
| 26_13 | 13 | 19 |
| 27_13 | 13 | 21 |
| 29_13 | 13 | 15 |
| 32_13 | 13 | 10 |
| 34_13 | 13 | 28 |
| 36_13 | 13 | 22 |
| 37_13 | 13 | 6 |
| 38_13 | 13 | 11 |
| 39_13 | 13 | 16 |
| 41_13 | 13 | 11 |
| 43_13 | 13 | 12 |
| 44_13 | 13 | 22 |
| 47_13 | 13 | 9 |

| | | |
|-------|----|----|
| 36_20 | 20 | 22 |
| 41_20 | 20 | 19 |
| 42_20 | 20 | 22 |
| 46_20 | 20 | 20 |
| 47_20 | 20 | 20 |
| 52_20 | 20 | 25 |
| 60_20 | 20 | 15 |
| 63_20 | 20 | 22 |
| 82_20 | 20 | 22 |
| 2_21 | 21 | 27 |
| 4_21 | 21 | 17 |
| 8_21 | 21 | 24 |
| 12_21 | 21 | 22 |
| 13_21 | 21 | 8 |
| 23_21 | 21 | 23 |
| 33_21 | 21 | 17 |
| 34_21 | 21 | 23 |
| 35_21 | 21 | 22 |
| 38_21 | 21 | 23 |
| 40_21 | 21 | 23 |
| 41_21 | 21 | 18 |
| 44_21 | 21 | 18 |
| 67_21 | 21 | 21 |
| 72_21 | 21 | 28 |
| 82_21 | 21 | 19 |
| 1_22 | 22 | 21 |
| 7_22 | 22 | 23 |
| 9_22 | 22 | 16 |

| | | |
|-------|----|----|
| 3_47 | 47 | 21 |
| 62_47 | 47 | 18 |
| 4_48 | 48 | 25 |
| 5_48 | 48 | 21 |
| 45_48 | 48 | 20 |
| 3_49 | 49 | 28 |
| 5_49 | 49 | 28 |
| 48_49 | 49 | 18 |
| 39_50 | 50 | 25 |
| 48_50 | 50 | 14 |
| 3_51 | 51 | 30 |
| 4_51 | 51 | 25 |
| 6_51 | 51 | 26 |
| 5_52 | 52 | 22 |
| 39_52 | 52 | 20 |
| 48_52 | 52 | 24 |
| 4_53 | 53 | 27 |
| 62_53 | 53 | 18 |
| 48_54 | 54 | 13 |
| 62_54 | 54 | 17 |
| 6_55 | 55 | 32 |
| 47_55 | 55 | 19 |
| 3_58 | 58 | 25 |
| 3_60 | 60 | 30 |
| 3_61 | 61 | 35 |
| 5_61 | 61 | 20 |
| 6_61 | 61 | 16 |
| 4_62 | 62 | 20 |

| | | |
|------|---|----|
| 47_6 | 6 | 14 |
| 49_6 | 6 | 4 |
| 50_6 | 6 | 18 |
| 53_6 | 6 | 20 |

| | | |
|-------|----|----|
| 52_13 | 13 | 22 |
| 53_13 | 13 | 19 |
| 54_13 | 13 | 4 |
| 58_13 | 13 | 15 |

| | | |
|-------|----|----|
| 9_22 | 22 | 10 |
| 14_22 | 22 | 24 |
| 17_22 | 22 | 18 |
| | | |

| | | |
|------|----|----|
| 4_63 | 63 | 26 |
| 6_67 | 67 | 25 |
| 6_69 | 69 | 31 |
| | | |

APPENDIX C New algorithm results for Private database

| Image ID | Actual Age | Estimated Age |
|----------|------------|---------------|
| 006_00 | 0 | 2 |
| 010_00 | 0 | 3 |
| 142_00 | 0 | 2 |
| 144_00 | 0 | 3 |
| 175_00 | 0 | 2 |
| 177_00 | 0 | 3 |
| 178_00 | 0 | 11 |
| 179_00 | 0 | 6 |
| 206_00 | 0 | 4 |
| 210_00 | 0 | 1 |
| 249_00 | 0 | 2 |
| 005_01 | 1 | 5 |
| 011_01 | 1 | 4 |
| 012_01 | 1 | 4 |
| 021_01 | 1 | 0 |
| 025_01 | 1 | 2 |
| 026_01 | 1 | 3 |
| 044_01 | 1 | 5 |
| 048_01 | 1 | 2 |
| 049_01 | 1 | 1 |
| 052_01 | 1 | 3 |
| 053_01 | 1 | 6 |

| Image ID | Actual Age | Estimated Age |
|----------|------------|---------------|
| 138_05 | 5 | 14 |
| 141_05 | 5 | 3 |
| 150_05 | 5 | 10 |
| 151_05 | 5 | 9 |
| 167_05 | 5 | 11 |
| 169_05 | 5 | 5 |
| 172_05 | 5 | 14 |
| 175_05 | 5 | 12 |
| 176_05 | 5 | 9 |
| 178_05 | 5 | 8 |
| 185_05 | 5 | 6 |
| 199_05 | 5 | 10 |
| 200_05 | 5 | 4 |
| 202_05 | 5 | 7 |
| 234_05 | 5 | 8 |
| 247_05 | 5 | 5 |
| 251_05 | 5 | 12 |
| 252_05 | 5 | 3 |
| 003_06 | 6 | 10 |
| 006_06 | 6 | 8 |
| 007_06 | 6 | 6 |
| 009_06 | 6 | 8 |

| Image ID | Actual Age | Estimated Age |
|----------|------------|---------------|
| 134_10 | 10 | 13 |
| 135_10 | 10 | 14 |
| 138_10 | 10 | 15 |
| 140_10 | 10 | 13 |
| 143_10 | 10 | 9 |
| 144_10 | 10 | 14 |
| 154_10 | 10 | 16 |
| 164_10 | 10 | 8 |
| 166_10 | 10 | 8 |
| 175_10 | 10 | 10 |
| 177_10 | 10 | 14 |
| 180_10 | 10 | 16 |
| 184_10 | 10 | 8 |
| 189_10 | 10 | 17 |
| 199_10 | 10 | 11 |
| 200_10 | 10 | 12 |
| 206_10 | 10 | 10 |
| 209_10 | 10 | 12 |
| 210_10 | 10 | 12 |
| 215_10 | 10 | 15 |
| 224_10 | 10 | 9 |
| 235_10 | 10 | 13 |

| Image ID | Actual Age | Estimated Age |
|----------|------------|---------------|
| 147_16 | 16 | 17 |
| 151_16 | 16 | 17 |
| 157_16 | 16 | 14 |
| 165_16 | 16 | 12 |
| 167_16 | 16 | 16 |
| 170_16 | 16 | 15 |
| 172_16 | 16 | 16 |
| 179_16 | 16 | 13 |
| 183_16 | 16 | 17 |
| 189_16 | 16 | 16 |
| 202_16 | 16 | 12 |
| 203_16 | 16 | 16 |
| 207_16 | 16 | 16 |
| 209_16 | 16 | 17 |
| 222_16 | 16 | 12 |
| 225_16 | 16 | 13 |
| 229_16 | 16 | 12 |
| 234_16 | 16 | 18 |
| 239_16 | 16 | 8 |
| 242_16 | 16 | 7 |
| 244_16 | 16 | 15 |
| 248_16 | 16 | 15 |

| | | |
|--------|---|---|
| 055_01 | 1 | 2 |
| 058_01 | 1 | 3 |
| 069_01 | 1 | 4 |
| 071_01 | 1 | 1 |
| 075_01 | 1 | 5 |
| 077_01 | 1 | 4 |
| 078_01 | 1 | 2 |
| 090_01 | 1 | 2 |
| 099_01 | 1 | 3 |
| 102_01 | 1 | 2 |
| 103_01 | 1 | 2 |
| 104_01 | 1 | 6 |
| 114_01 | 1 | 4 |
| 115_01 | 1 | 2 |
| 119_01 | 1 | 5 |
| 120_01 | 1 | 1 |
| 121_01 | 1 | 2 |
| 123_01 | 1 | 1 |
| 124_01 | 1 | 3 |
| 132_01 | 1 | 2 |
| 137_01 | 1 | 2 |
| 138_01 | 1 | 5 |
| 144_01 | 1 | 3 |
| 164_01 | 1 | 3 |
| 168_01 | 1 | 2 |
| 169_01 | 1 | 2 |
| 172_01 | 1 | 4 |
| 174_01 | 1 | 2 |

| | | |
|--------|---|----|
| 013_06 | 6 | 8 |
| 021_06 | 6 | 11 |
| 025_06 | 6 | 3 |
| 040_06 | 6 | 15 |
| 043_06 | 6 | 12 |
| 048_06 | 6 | 13 |
| 049_06 | 6 | 15 |
| 056_06 | 6 | 12 |
| 063_06 | 6 | 12 |
| 065_06 | 6 | 7 |
| 085_06 | 6 | 8 |
| 086_06 | 6 | 9 |
| 103_06 | 6 | 8 |
| 112_06 | 6 | 9 |
| 127_06 | 6 | 2 |
| 144_06 | 6 | 7 |
| 145_06 | 6 | 9 |
| 149_06 | 6 | 2 |
| 150_06 | 6 | 9 |
| 158_06 | 6 | 5 |
| 177_06 | 6 | 14 |
| 178_06 | 6 | 16 |
| 187_06 | 6 | 10 |
| 191_06 | 6 | 9 |
| 192_06 | 6 | 4 |
| 194_06 | 6 | 2 |
| 201_06 | 6 | 10 |
| 210_06 | 6 | 4 |

| | | |
|--------|----|----|
| 239_10 | 10 | 4 |
| 240_10 | 10 | 12 |
| 242_10 | 10 | 15 |
| 243_10 | 10 | 8 |
| 251_10 | 10 | 10 |
| 252_10 | 10 | 14 |
| 008_11 | 11 | 8 |
| 039_11 | 11 | 11 |
| 050_11 | 11 | 12 |
| 060_11 | 11 | 8 |
| 071_11 | 11 | 14 |
| 072_11 | 11 | 9 |
| 086_11 | 11 | 15 |
| 119_11 | 11 | 11 |
| 130_11 | 11 | 17 |
| 132_11 | 11 | 10 |
| 136_11 | 11 | 16 |
| 142_11 | 11 | 15 |
| 149_11 | 11 | 15 |
| 150_11 | 11 | 15 |
| 155_11 | 11 | 8 |
| 157_11 | 11 | 12 |
| 165_11 | 11 | 10 |
| 173_11 | 11 | 4 |
| 177_11 | 11 | 9 |
| 185_11 | 11 | 8 |
| 213_11 | 11 | 17 |
| 214_11 | 11 | 12 |

| | | |
|--------|----|----|
| 252_16 | 16 | 15 |
| 002_17 | 17 | 11 |
| 007_17 | 17 | 11 |
| 024_17 | 17 | 16 |
| 028_17 | 17 | 17 |
| 032_17 | 17 | 17 |
| 036_17 | 17 | 12 |
| 050_17 | 17 | 16 |
| 051_17 | 17 | 15 |
| 053_17 | 17 | 14 |
| 074_17 | 17 | 11 |
| 081_17 | 17 | 17 |
| 082_17 | 17 | 14 |
| 098_17 | 17 | 16 |
| 103_17 | 17 | 14 |
| 118_17 | 17 | 14 |
| 127_17 | 17 | 11 |
| 129_17 | 17 | 13 |
| 134_17 | 17 | 14 |
| 139_17 | 17 | 11 |
| 142_17 | 17 | 17 |
| 144_17 | 17 | 17 |
| 149_17 | 17 | 17 |
| 187_17 | 17 | 17 |
| 212_17 | 17 | 17 |
| 224_17 | 17 | 10 |
| 225_17 | 17 | 7 |
| 228_17 | 17 | 15 |

| | | |
|--------|---|----|
| 181_01 | 1 | 8 |
| 187_01 | 1 | 4 |
| 189_01 | 1 | 5 |
| 198_01 | 1 | 2 |
| 201_01 | 1 | 3 |
| 202_01 | 1 | 2 |
| 203_01 | 1 | 2 |
| 208_01 | 1 | 10 |
| 210_01 | 1 | 0 |
| 218_01 | 1 | 8 |
| 234_01 | 1 | 2 |
| 237_01 | 1 | 2 |
| 239_01 | 1 | 6 |
| 251_01 | 1 | 2 |
| 252_01 | 1 | 6 |
| 003_02 | 2 | 8 |
| 009_02 | 2 | 8 |
| 019_02 | 2 | 2 |
| 020_02 | 2 | 7 |
| 022_02 | 2 | 2 |
| 023_02 | 2 | 2 |
| 025_02 | 2 | 2 |
| 028_02 | 2 | 8 |
| 029_02 | 2 | 2 |
| 032_02 | 2 | 10 |
| 036_02 | 2 | 4 |
| 037_02 | 2 | 2 |
| 042_02 | 2 | 3 |

| | | |
|--------|---|----|
| 211_06 | 6 | 7 |
| 224_06 | 6 | 2 |
| 226_06 | 6 | 4 |
| 241_06 | 6 | 4 |
| 242_06 | 6 | 3 |
| 245_06 | 6 | 5 |
| 250_06 | 6 | 5 |
| 253_06 | 6 | 8 |
| 001_07 | 7 | 17 |
| 002_07 | 7 | 7 |
| 014_07 | 7 | 7 |
| 022_07 | 7 | 9 |
| 026_07 | 7 | 17 |
| 027_07 | 7 | 9 |
| 034_07 | 7 | 7 |
| 035_07 | 7 | 10 |
| 039_07 | 7 | 5 |
| 042_07 | 7 | 16 |
| 048_07 | 7 | 12 |
| 055_07 | 7 | 10 |
| 057_07 | 7 | 9 |
| 066_07 | 7 | 16 |
| 070_07 | 7 | 7 |
| 072_07 | 7 | 11 |
| 073_07 | 7 | 12 |
| 076_07 | 7 | 17 |
| 084_07 | 7 | 12 |
| 091_07 | 7 | 6 |

| | | |
|--------|----|----|
| 228_11 | 11 | 14 |
| 229_11 | 11 | 16 |
| 236_11 | 11 | 5 |
| 237_11 | 11 | 12 |
| 002_12 | 12 | 15 |
| 003_12 | 12 | 8 |
| 027_12 | 12 | 15 |
| 041_12 | 12 | 14 |
| 049_12 | 12 | 13 |
| 052_12 | 12 | 10 |
| 068_12 | 12 | 9 |
| 073_12 | 12 | 16 |
| 074_12 | 12 | 14 |
| 082_12 | 12 | 12 |
| 095_12 | 12 | 15 |
| 105_12 | 12 | 12 |
| 117_12 | 12 | 13 |
| 123_12 | 12 | 8 |
| 124_12 | 12 | 17 |
| 139_12 | 12 | 10 |
| 148_12 | 12 | 17 |
| 160_12 | 12 | 13 |
| 162_12 | 12 | 17 |
| 170_12 | 12 | 10 |
| 174_12 | 12 | 15 |
| 195_12 | 12 | 12 |
| 208_12 | 12 | 17 |
| 212_12 | 12 | 12 |

| | | |
|--------|----|----|
| 235_17 | 17 | 12 |
| 252_17 | 17 | 17 |
| 005_18 | 18 | 16 |
| 006_18 | 18 | 15 |
| 021_18 | 18 | 13 |
| 023_18 | 18 | 11 |
| 024_18 | 18 | 17 |
| 028_18 | 18 | 18 |
| 030_18 | 18 | 16 |
| 039_18 | 18 | 13 |
| 041_18 | 18 | 14 |
| 043_18 | 18 | 14 |
| 046_18 | 18 | 15 |
| 049_18 | 18 | 16 |
| 052_18 | 18 | 14 |
| 059_18 | 18 | 14 |
| 066_18 | 18 | 18 |
| 070_18 | 18 | 16 |
| 071_18 | 18 | 12 |
| 078_18 | 18 | 17 |
| 079_18 | 18 | 17 |
| 090_18 | 18 | 12 |
| 091_18 | 18 | 12 |
| 098_18 | 18 | 15 |
| 116_18 | 18 | 16 |
| 120_18 | 18 | 13 |
| 126_18 | 18 | 11 |
| 131_18 | 18 | 9 |

| | | |
|--------|---|----|
| 047_02 | 2 | 1 |
| 049_02 | 2 | 6 |
| 059_02 | 2 | 3 |
| 065_02 | 2 | 2 |
| 067_02 | 2 | 6 |
| 081_02 | 2 | 4 |
| 084_02 | 2 | 3 |
| 086_02 | 2 | 5 |
| 097_02 | 2 | 3 |
| 102_02 | 2 | 5 |
| 109_02 | 2 | 3 |
| 111_02 | 2 | 2 |
| 112_02 | 2 | 10 |
| 113_02 | 2 | 4 |
| 117_02 | 2 | 11 |
| 118_02 | 2 | 2 |
| 128_02 | 2 | 6 |
| 129_02 | 2 | 5 |
| 130_02 | 2 | 9 |
| 143_02 | 2 | 4 |
| 148_02 | 2 | 3 |
| 149_02 | 2 | 2 |
| 157_02 | 2 | 2 |
| 176_02 | 2 | 4 |
| 179_02 | 2 | 1 |
| 192_02 | 2 | 2 |
| 200_02 | 2 | 5 |
| 203_02 | 2 | 2 |

| | | |
|--------|---|----|
| 092_07 | 7 | 13 |
| 094_07 | 7 | 9 |
| 095_07 | 7 | 10 |
| 097_07 | 7 | 15 |
| 114_07 | 7 | 13 |
| 115_07 | 7 | 12 |
| 126_07 | 7 | 5 |
| 132_07 | 7 | 7 |
| 137_07 | 7 | 13 |
| 140_07 | 7 | 11 |
| 142_07 | 7 | 11 |
| 144_07 | 7 | 6 |
| 152_07 | 7 | 3 |
| 154_07 | 7 | 10 |
| 157_07 | 7 | 5 |
| 159_07 | 7 | 8 |
| 161_07 | 7 | 12 |
| 164_07 | 7 | 10 |
| 165_07 | 7 | 7 |
| 177_07 | 7 | 8 |
| 181_07 | 7 | 3 |
| 183_07 | 7 | 6 |
| 184_07 | 7 | 5 |
| 195_07 | 7 | 10 |
| 196_07 | 7 | 10 |
| 200_07 | 7 | 2 |
| 201_07 | 7 | 11 |
| 205_07 | 7 | 15 |

| | | |
|--------|----|----|
| 238_12 | 12 | 16 |
| 241_12 | 12 | 14 |
| 244_12 | 12 | 17 |
| 250_12 | 12 | 11 |
| 009_13 | 13 | 15 |
| 028_13 | 13 | 16 |
| 032_13 | 13 | 17 |
| 049_13 | 13 | 11 |
| 051_13 | 13 | 14 |
| 078_13 | 13 | 15 |
| 114_13 | 13 | 17 |
| 115_13 | 13 | 15 |
| 127_13 | 13 | 10 |
| 175_13 | 13 | 12 |
| 177_13 | 13 | 13 |
| 182_13 | 13 | 13 |
| 202_13 | 13 | 11 |
| 206_13 | 13 | 14 |
| 207_13 | 13 | 10 |
| 007_14 | 14 | 8 |
| 024_14 | 14 | 7 |
| 035_14 | 14 | 16 |
| 036_14 | 14 | 16 |
| 038_14 | 14 | 11 |
| 043_14 | 14 | 14 |
| 049_14 | 14 | 16 |
| 061_14 | 14 | 11 |
| 069_14 | 14 | 14 |

| | | |
|--------|----|----|
| 132_18 | 18 | 7 |
| 141_18 | 18 | 12 |
| 155_18 | 18 | 17 |
| 157_18 | 18 | 17 |
| 158_18 | 18 | 13 |
| 159_18 | 18 | 14 |
| 165_18 | 18 | 16 |
| 166_18 | 18 | 15 |
| 168_18 | 18 | 10 |
| 176_18 | 18 | 17 |
| 177_18 | 18 | 12 |
| 179_18 | 18 | 11 |
| 182_18 | 18 | 16 |
| 184_18 | 18 | 17 |
| 185_18 | 18 | 10 |
| 191_18 | 18 | 7 |
| 204_18 | 18 | 17 |
| 209_18 | 18 | 15 |
| 213_18 | 18 | 17 |
| 222_18 | 18 | 16 |
| 226_18 | 18 | 15 |
| 229_18 | 18 | 11 |
| 237_18 | 18 | 15 |
| 241_18 | 18 | 12 |
| 017_19 | 19 | 16 |
| 020_19 | 19 | 13 |
| 023_19 | 19 | 12 |
| 024_19 | 19 | 17 |

| | | |
|--------|---|----|
| 207_02 | 2 | 7 |
| 215_02 | 2 | 4 |
| 224_02 | 2 | 2 |
| 225_02 | 2 | 1 |
| 233_02 | 2 | 2 |
| 241_02 | 2 | 2 |
| 243_02 | 2 | 2 |
| 246_02 | 2 | 2 |
| 247_02 | 2 | 4 |
| 253_02 | 2 | 3 |
| 009_03 | 3 | 11 |
| 014_03 | 3 | 2 |
| 023_03 | 3 | 2 |
| 031_03 | 3 | 4 |
| 039_03 | 3 | 8 |
| 040_03 | 3 | 6 |
| 043_03 | 3 | 6 |
| 049_03 | 3 | 6 |
| 054_03 | 3 | 8 |
| 064_03 | 3 | 2 |
| 066_03 | 3 | 6 |
| 070_03 | 3 | 2 |
| 072_03 | 3 | 5 |
| 073_03 | 3 | 0 |
| 075_03 | 3 | 5 |
| 076_03 | 3 | 11 |
| 086_03 | 3 | 8 |
| 092_03 | 3 | 10 |

| | | |
|--------|---|----|
| 206_07 | 7 | 11 |
| 207_07 | 7 | 16 |
| 208_07 | 7 | 16 |
| 209_07 | 7 | 6 |
| 215_07 | 7 | 7 |
| 218_07 | 7 | 5 |
| 229_07 | 7 | 9 |
| 236_07 | 7 | 11 |
| 238_07 | 7 | 14 |
| 239_07 | 7 | 9 |
| 249_07 | 7 | 8 |
| 003_08 | 8 | 7 |
| 019_08 | 8 | 2 |
| 024_08 | 8 | 3 |
| 048_08 | 8 | 14 |
| 049_08 | 8 | 14 |
| 050_08 | 8 | 9 |
| 052_08 | 8 | 13 |
| 068_08 | 8 | 14 |
| 069_08 | 8 | 13 |
| 081_08 | 8 | 7 |
| 089_08 | 8 | 8 |
| 099_08 | 8 | 9 |
| 115_08 | 8 | 9 |
| 117_08 | 8 | 13 |
| 120_08 | 8 | 8 |
| 121_08 | 8 | 8 |
| 135_08 | 8 | 15 |

| | | |
|--------|----|----|
| 071_14 | 14 | 12 |
| 072_14 | 14 | 15 |
| 085_14 | 14 | 14 |
| 096_14 | 14 | 15 |
| 104_14 | 14 | 16 |
| 106_14 | 14 | 14 |
| 123_14 | 14 | 10 |
| 130_14 | 14 | 14 |
| 133_14 | 14 | 16 |
| 134_14 | 14 | 13 |
| 135_14 | 14 | 15 |
| 136_14 | 14 | 15 |
| 141_14 | 14 | 13 |
| 147_14 | 14 | 16 |
| 151_14 | 14 | 11 |
| 158_14 | 14 | 14 |
| 159_14 | 14 | 6 |
| 166_14 | 14 | 13 |
| 177_14 | 14 | 17 |
| 181_14 | 14 | 12 |
| 184_14 | 14 | 15 |
| 194_14 | 14 | 17 |
| 197_14 | 14 | 14 |
| 203_14 | 14 | 16 |
| 205_14 | 14 | 17 |
| 210_14 | 14 | 17 |
| 211_14 | 14 | 15 |
| 212_14 | 14 | 15 |

| | | |
|--------|----|----|
| 034_19 | 19 | 18 |
| 042_19 | 19 | 18 |
| 048_19 | 19 | 12 |
| 049_19 | 19 | 17 |
| 064_19 | 19 | 7 |
| 068_19 | 19 | 15 |
| 072_19 | 19 | 17 |
| 075_19 | 19 | 17 |
| 082_19 | 19 | 17 |
| 085_19 | 19 | 15 |
| 089_19 | 19 | 11 |
| 093_19 | 19 | 14 |
| 096_19 | 19 | 13 |
| 097_19 | 19 | 14 |
| 099_19 | 19 | 13 |
| 100_19 | 19 | 13 |
| 103_19 | 19 | 13 |
| 125_19 | 19 | 16 |
| 130_19 | 19 | 17 |
| 136_19 | 19 | 17 |
| 144_19 | 19 | 15 |
| 150_19 | 19 | 14 |
| 154_19 | 19 | 15 |
| 162_19 | 19 | 17 |
| 167_19 | 19 | 12 |
| 170_19 | 19 | 15 |
| 171_19 | 19 | 11 |
| 173_19 | 19 | 16 |

| | | |
|--------|---|----|
| 093_03 | 3 | 2 |
| 094_03 | 3 | 2 |
| 095_03 | 3 | 2 |
| 099_03 | 3 | 3 |
| 114_03 | 3 | 3 |
| 125_03 | 3 | 6 |
| 133_03 | 3 | 7 |
| 136_03 | 3 | 4 |
| 140_03 | 3 | 6 |
| 144_03 | 3 | 2 |
| 147_03 | 3 | 2 |
| 150_03 | 3 | 6 |
| 151_03 | 3 | 6 |
| 152_03 | 3 | 5 |
| 154_03 | 3 | 13 |
| 158_03 | 3 | 5 |
| 165_03 | 3 | 5 |
| 166_03 | 3 | 2 |
| 169_03 | 3 | 9 |
| 170_03 | 3 | 7 |
| 200_03 | 3 | 2 |
| 203_03 | 3 | 15 |
| 212_03 | 3 | 5 |
| 213_03 | 3 | 9 |
| 229_03 | 3 | 6 |
| 236_03 | 3 | 4 |
| 240_03 | 3 | 5 |
| 244_03 | 3 | 5 |

| | | |
|--------|---|----|
| 139_08 | 8 | 7 |
| 144_08 | 8 | 15 |
| 153_08 | 8 | 10 |
| 156_08 | 8 | 7 |
| 160_08 | 8 | 12 |
| 174_08 | 8 | 15 |
| 177_08 | 8 | 11 |
| 178_08 | 8 | 12 |
| 189_08 | 8 | 13 |
| 205_08 | 8 | 14 |
| 212_08 | 8 | 12 |
| 222_08 | 8 | 14 |
| 227_08 | 8 | 10 |
| 243_08 | 8 | 7 |
| 004_09 | 9 | 10 |
| 005_09 | 9 | 15 |
| 006_09 | 9 | 11 |
| 013_09 | 9 | 13 |
| 018_09 | 9 | 10 |
| 023_09 | 9 | 11 |
| 025_09 | 9 | 9 |
| 026_09 | 9 | 15 |
| 031_09 | 9 | 11 |
| 036_09 | 9 | 9 |
| 038_09 | 9 | 9 |
| 043_09 | 9 | 12 |
| 044_09 | 9 | 11 |
| 048_09 | 9 | 13 |

| | | |
|--------|----|----|
| 213_14 | 14 | 17 |
| 218_14 | 14 | 12 |
| 219_14 | 14 | 14 |
| 224_14 | 14 | 7 |
| 019_15 | 15 | 14 |
| 023_15 | 15 | 14 |
| 024_15 | 15 | 13 |
| 028_15 | 15 | 15 |
| 044_15 | 15 | 10 |
| 048_15 | 15 | 17 |
| 053_15 | 15 | 10 |
| 054_15 | 15 | 15 |
| 058_15 | 15 | 16 |
| 062_15 | 15 | 2 |
| 063_15 | 15 | 16 |
| 064_15 | 15 | 10 |
| 066_15 | 15 | 17 |
| 073_15 | 15 | 15 |
| 090_15 | 15 | 16 |
| 092_15 | 15 | 15 |
| 093_15 | 15 | 13 |
| 095_15 | 15 | 15 |
| 099_15 | 15 | 13 |
| 129_15 | 15 | 15 |
| 131_15 | 15 | 10 |
| 132_15 | 15 | 15 |
| 138_15 | 15 | 18 |
| 152_15 | 15 | 11 |

| | | |
|--------|----|----|
| 181_19 | 19 | 10 |
| 188_19 | 19 | 17 |
| 194_19 | 19 | 13 |
| 210_19 | 19 | 15 |
| 214_19 | 19 | 13 |
| 223_19 | 19 | 16 |
| 225_19 | 19 | 11 |
| 234_19 | 19 | 11 |
| 239_19 | 19 | 14 |
| 248_19 | 19 | 14 |
| 250_19 | 19 | 8 |
| 003_20 | 20 | 17 |
| 004_20 | 20 | 17 |
| 011_20 | 20 | 14 |
| 015_20 | 20 | 6 |
| 023_20 | 20 | 14 |
| 024_20 | 20 | 14 |
| 025_20 | 20 | 15 |
| 028_20 | 20 | 18 |
| 037_20 | 20 | 18 |
| 038_20 | 20 | 16 |
| 040_20 | 20 | 14 |
| 045_20 | 20 | 15 |
| 047_20 | 20 | 15 |
| 048_20 | 20 | 15 |
| 052_20 | 20 | 12 |
| 054_20 | 20 | 17 |
| 056_20 | 20 | 16 |

| | | |
|--------|---|----|
| 254_03 | 3 | 9 |
| 002_04 | 4 | 3 |
| 004_04 | 4 | 12 |
| 008_04 | 4 | 8 |
| 023_04 | 4 | 6 |
| 035_04 | 4 | 4 |
| 039_04 | 4 | 7 |
| 041_04 | 4 | 3 |
| 044_04 | 4 | 9 |
| 046_04 | 4 | 5 |
| 048_04 | 4 | 9 |
| 052_04 | 4 | 9 |
| 055_04 | 4 | 9 |
| 068_04 | 4 | 4 |
| 114_04 | 4 | 2 |
| 115_04 | 4 | 5 |
| 121_04 | 4 | 3 |
| 126_04 | 4 | 9 |
| 153_04 | 4 | 9 |
| 160_04 | 4 | 8 |
| 161_04 | 4 | 5 |
| 197_04 | 4 | 10 |
| 209_04 | 4 | 2 |
| 219_04 | 4 | 8 |
| 230_04 | 4 | 5 |
| 238_04 | 4 | 9 |
| 005_05 | 5 | 13 |
| 010_05 | 5 | 12 |

| | | |
|--------|---|----|
| 049_09 | 9 | 13 |
| 078_09 | 9 | 14 |
| 086_09 | 9 | 11 |
| 131_09 | 9 | 8 |
| 141_09 | 9 | 10 |
| 144_09 | 9 | 12 |
| 150_09 | 9 | 16 |
| 151_09 | 9 | 12 |
| 158_09 | 9 | 11 |
| 159_09 | 9 | 9 |
| 171_09 | 9 | 12 |
| 173_09 | 9 | 9 |
| 177_09 | 9 | 10 |
| 178_09 | 9 | 10 |
| 181_09 | 9 | 8 |
| 182_09 | 9 | 8 |
| 188_09 | 9 | 12 |
| 202_09 | 9 | 10 |
| 209_09 | 9 | 11 |
| 211_09 | 9 | 8 |
| 218_09 | 9 | 3 |
| 219_09 | 9 | 13 |
| 226_09 | 9 | 11 |
| 234_09 | 9 | 11 |
| 245_09 | 9 | 9 |
| 246_09 | 9 | 8 |
| 247_09 | 9 | 15 |
| 248_09 | 9 | 11 |

| | | |
|--------|----|----|
| 153_15 | 15 | 11 |
| 155_15 | 15 | 12 |
| 162_15 | 15 | 14 |
| 164_15 | 15 | 13 |
| 168_15 | 15 | 10 |
| 169_15 | 15 | 15 |
| 180_15 | 15 | 13 |
| 185_15 | 15 | 12 |
| 188_15 | 15 | 14 |
| 200_15 | 15 | 16 |
| 208_15 | 15 | 17 |
| 209_15 | 15 | 12 |
| 228_15 | 15 | 12 |
| 236_15 | 15 | 17 |
| 238_15 | 15 | 17 |
| 241_15 | 15 | 11 |
| 243_15 | 15 | 11 |
| 245_15 | 15 | 17 |
| 251_15 | 15 | 13 |
| 003_16 | 16 | 13 |
| 004_16 | 16 | 17 |
| 005_16 | 16 | 17 |
| 006_16 | 16 | 15 |
| 013_16 | 16 | 16 |
| 015_16 | 16 | 9 |
| 016_16 | 16 | 13 |
| 017_16 | 16 | 14 |
| 018_16 | 16 | 14 |

| | | |
|--------|----|----|
| 065_20 | 20 | 10 |
| 067_20 | 20 | 14 |
| 069_20 | 20 | 15 |
| 077_20 | 20 | 11 |
| 083_20 | 20 | 15 |
| 087_20 | 20 | 16 |
| 090_20 | 20 | 16 |
| 092_20 | 20 | 17 |
| 094_20 | 20 | 17 |
| 095_20 | 20 | 14 |
| 099_20 | 20 | 17 |
| 105_20 | 20 | 16 |
| 122_20 | 20 | 15 |
| 123_20 | 20 | 12 |
| 135_20 | 20 | 16 |
| 137_20 | 20 | 16 |
| 144_20 | 20 | 14 |
| 145_20 | 20 | 11 |
| 147_20 | 20 | 16 |
| 149_20 | 20 | 18 |
| 151_20 | 20 | 14 |
| 152_20 | 20 | 10 |
| 163_20 | 20 | 16 |
| 164_20 | 20 | 13 |
| 169_20 | 20 | 14 |
| 178_20 | 20 | 16 |
| 180_20 | 20 | 11 |
| 183_20 | 20 | 16 |

| | | |
|--------|---|----|
| 011_05 | 5 | 7 |
| 018_05 | 5 | 7 |
| 023_05 | 5 | 10 |
| 025_05 | 5 | 10 |
| 028_05 | 5 | 13 |
| 032_05 | 5 | 12 |
| 036_05 | 5 | 4 |
| 042_05 | 5 | 9 |
| 048_05 | 5 | 9 |
| 049_05 | 5 | 13 |
| 052_05 | 5 | 3 |
| 059_05 | 5 | 13 |
| 064_05 | 5 | 7 |
| 067_05 | 5 | 12 |
| 074_05 | 5 | 11 |
| 077_05 | 5 | 6 |
| 080_05 | 5 | 4 |
| 086_05 | 5 | 4 |
| 113_05 | 5 | 10 |
| 118_05 | 5 | 12 |
| 122_05 | 5 | 8 |
| 123_05 | 5 | 2 |
| 124_05 | 5 | 13 |
| 125_05 | 5 | 9 |
| 129_05 | 5 | 8 |
| 130_05 | 5 | 10 |
| 133_05 | 5 | 5 |

| | | |
|--------|----|----|
| 249_09 | 9 | 5 |
| 001_10 | 10 | 13 |
| 009_10 | 10 | 11 |
| 017_10 | 10 | 10 |
| 019_10 | 10 | 4 |
| 021_10 | 10 | 12 |
| 028_10 | 10 | 15 |
| 034_10 | 10 | 11 |
| 038_10 | 10 | 11 |
| 049_10 | 10 | 15 |
| 054_10 | 10 | 16 |
| 058_10 | 10 | 11 |
| 059_10 | 10 | 13 |
| 063_10 | 10 | 17 |
| 064_10 | 10 | 6 |
| 066_10 | 10 | 14 |
| 067_10 | 10 | 15 |
| 070_10 | 10 | 8 |
| 077_10 | 10 | 4 |
| 079_10 | 10 | 9 |
| 084_10 | 10 | 16 |
| 094_10 | 10 | 11 |
| 113_10 | 10 | 10 |
| 116_10 | 10 | 12 |
| 125_10 | 10 | 14 |
| 129_10 | 10 | 11 |
| 133_10 | 10 | 15 |

| | | |
|--------|----|----|
| 021_16 | 16 | 13 |
| 025_16 | 16 | 8 |
| 026_16 | 16 | 12 |
| 027_16 | 16 | 18 |
| 030_16 | 16 | 11 |
| 034_16 | 16 | 15 |
| 037_16 | 16 | 17 |
| 045_16 | 16 | 10 |
| 052_16 | 16 | 15 |
| 068_16 | 16 | 13 |
| 069_16 | 16 | 13 |
| 076_16 | 16 | 17 |
| 077_16 | 16 | 13 |
| 082_16 | 16 | 17 |
| 083_16 | 16 | 14 |
| 101_16 | 16 | 17 |
| 115_16 | 16 | 17 |
| 116_16 | 16 | 17 |
| 118_16 | 16 | 15 |
| 124_16 | 16 | 17 |
| 125_16 | 16 | 18 |
| 126_16 | 16 | 8 |
| 130_16 | 16 | 16 |
| 137_16 | 16 | 17 |
| 139_16 | 16 | 12 |
| 140_16 | 16 | 14 |
| 143_16 | 16 | 18 |

| | | |
|--------|----|----|
| 189_20 | 20 | 15 |
| 190_20 | 20 | 14 |
| 201_20 | 20 | 17 |
| 205_20 | 20 | 17 |
| 208_20 | 20 | 17 |
| 209_20 | 20 | 16 |
| 215_20 | 20 | 16 |
| 216_20 | 20 | 14 |
| 220_20 | 20 | 11 |
| 230_20 | 20 | 13 |
| 232_20 | 20 | 16 |
| 238_20 | 20 | 17 |
| 240_20 | 20 | 17 |
| 241_20 | 20 | 11 |
| 242_20 | 20 | 13 |
| 243_20 | 20 | 14 |
| 244_20 | 20 | 15 |
| 247_20 | 20 | 17 |
| 252_20 | 20 | 16 |
| 253_20 | 20 | 14 |
| 197_21 | 21 | 14 |
| 028_22 | 22 | 16 |
| 086_22 | 22 | 15 |
| 195_22 | 22 | 14 |
| 004_25 | 25 | 15 |
| 182_25 | 25 | 16 |
| | | |

Curriculum Vitae

Petra Grd was born on February 14th 1986 in Kutina. She finished elementary and high school in Kutina and graduated from the Faculty of Organization and Informatics in 2009, where she finished her PhD in 2015. Since 2009 she has been working at the Faculty of organization and informatics as a research assistant on the project "Methods of evaluation of biometric characteristics" and as a teaching assistant at for the courses "Selected Topics in Biometrics" and "State and Administrative Information Systems" at the undergraduate level, "Internet Security" on graduate level, and "Business use of biometric technology" and "Business information systems of state administration". Her research interests are related to biometrics, specifically face biometrics and facial aging. Other than research and teaching, she was the secretary of the Disciplinary Tribunal and the Association of associates, a member of various committees, and a member of the Student council. She has published several scientific papers and participated in conferences and summer schools at home and abroad.

List of Publications

Book chapters

1. Grd, Petra; Bača, Miroslav: ebXML in Practice: A Systematic Literature Review // *Frontiers in ICT: Towards Web 3.0* / Levnajič, Zoran (ur.). Frankfurt: Peter Lang International Academic Publishers, 2014. pp. 53-66.
2. Bača, Miroslav; Grd, Petra; Fotak, Tomislav: Basic Principles and Trends in Hand Geometry and Hand Shape Biometrics // *New trends and developments in biometrics* / Yang, Jucheng; Xie, Shan Juan (ur.). Rijeka: InTech, 2012. pp. 77-99.
3. Schatten, Markus; Bača, Miroslav; Koruga, Petra: The transportation paths routing semantic description // *Transactions on transport systems telematics & safety* / Piecha, Jan; Wegrzyn, Tomasz (ur.). Gliwice: Silesian University of Technology, 2011. pp. 11-19.

Scientific papers in CC journals

1. Ševa, Jurica; Schatten, Markus; Grd, Petra: Open Directory Project based universal taxonomy for Personalization of Online (Re)sources. // *Expert systems with applications*. 42 (2015), 17–18; 6306-6314 (članak, znanstveni). priložen text radaURL link to work

Scientific papers in journals

1. Schatten, Markus; Grd, Petra; Konecki, Mladen; Kudelić, Robert: Towards a Formal Conceptualization of Organizational Design Techniques for Large Scale Multi Agent Systems. // *Procedia Technology*. 15 (2014); pp. 577-586
2. Grd, Petra: Introduction to Human Age Estimation Using Face Images. // *Research papers Faculty of Materials Science and Technology Slovak University of Technology in Trnava. Special Number* (2013); pp. 35-41
3. Fotak, Tomislav; Bača, Miroslav; Koruga, Petra: Handwritten signature identification using basic concepts of graph theory. // *WSEAS Transactions on Signal Processing*. 7 (2011); pp. 117-129

Scientific papers in conference proceedings

1. Bača, Miroslav; Fotak, Tomislav; Grd, Petra: Handwritten signature authentication using statistical measure of basic on-line signature characteristics // International Conference on Information Technologies and Information Society / Zoran Levnajić (ur.). Novo Mesto: FIS, 20. pp. 47-52
2. Delić, Alen; Grd, Petra; Gregurec, Iva: Analysis of Communication of Croatian Faculties through Facebook - Part I // Proceedings of the ITI 2013 35th International Conference on Information Technology Interfaces / Luzar-Stiffler, Vesna; Jarec, Iva (ur.). Zagreb, 2013. pp. 43-48
3. Bača, Miroslav; Koruga, Petra; Fotak, Tomislav: Building a framework for the development of biometric forensics // MIPRO 2012 Proceedings / Biljanović, Petar (ur.). Rijeka: Croatian Society for Information and Communication Technology, Electronics and Microelectronics, 2012. pp. 1904-1906
4. Fotak, Tomislav; Grd, Petra; Bača Miroslav: Trends in Hand Geometry Biometrics // Central European Conference on Information and Intelligent Systems 23rd International Conference / Hunjak, Tihomir ; Lovrenčić Sandra ; Tomičić Igor (ur.). Varaždin: Faculty of organization and informatics, 2012. pp. 319-324
5. Gregurec, Iva; Grd, Petra: Search Engine Optimization (SEO): Website analysis of selected faculties in Croatia // Central European Conference on Information and Intelligent Systems 23rd International Conference / Hunjak, Tihomir ; Lovrenčić Sandra ; Tomičić Igor (ur.). Varaždin: Faculty of organization and informatics, 2012. pp. 211-218
6. Koruga, Petra; Bača, Miroslav: Communication of political parties on Twitter: Comparison of political parties in Serbia, Croatia, Slovenia and BiH // 2012 SYMORG Inovative management and business performance / Jakšić, Maja Levi; Barjaktarović Rakočević, Slađana (ur.). Beograd: Faculty of Organizational Sciences, 2012. pp. 408-416
7. Koruga, Petra; Bača, Miroslav; Fotak, Tomislav: Knowledge Visualization in Biometric Face Recognition on Two-dimensional Images // Proceedings of the ITI 2012 34th International Conference on Information Technology Interfaces / Luzar-Stiffler, Vesna; Jarec, Iva; Bekic, Zoran (ur.). Zagreb, 2012. pp. 349-353

8. Bača, Miroslav; Koruga, Petra; Fotak, Tomislav: Basic on-line handwritten signature features for personal biometric authentication // 34th international convention on information and communication technology, electronics and microelectronics / Čišić Dragan ; Hutinski Željko ; Baranović Mirta ; Mauher Mladen ; Ordanić Lea (ur.). Opatija: MIPRO, 2011. pp. 116-121
9. Fotak, Tomislav; Koruga, Petra; Bača, Miroslav: On-line Handwritten Signature Identification: The Basics // Proceedings of the 22nd Central European Conference on Information and Intelligent Systems / Hunjak, Tihomir; Lovrenčić, Sandra (ur.). Varaždin, 2011. pp. 139-145
10. Koruga, Petra; Bača, Miroslav; Fotak, Tomislav: Comparison of Communication of Political Parties over the Internet in Slovenia and Croatia // Proceedings of International Conference on Information Society / Mertik, Matej (ur.). Novo Mesto: Faculty of Information Studies, 2011. pp. 31-36
11. Koruga, Petra; Bača, Miroslav; Schatten, Markus: Analysis of Craniofacial Morphology Changes during Aging and their Connection with Facial Age Estimation // Proceedings of the ITI 2011 33rd International Conference on INFORMATION TECHNOLOGY INTERFACES / Luzar-Stiffler, Vesna; Jarec, Iva; Bekic, Zoran (ur.). Zagreb, 2011. pp. 481-485
12. Koruga, Petra; Ševa, Jurica; Bača Miroslav: Application of Modified Anthropometric Model in Facial Age Estimation // Proceedings of the 53rd International Symposium ELMAR-2011 / Božek, Jelena; Grgić, Mislav (ur.). Zadar: Croatian Society Electronics in Marine, 2011. pp. 17-20
13. Koruga, Petra; Ševa, Jurica; Bača, Miroslav: A Review of Face Recognition Algorithms and Their Application in Age Estimation // Proceedings of the 22nd Central European Conference on Information and Intelligent Systems / Hunjak, Tihomir; Lovrenčić, Sandra (ur.). Varaždin: FOI, 2011. pp. 127-132
14. Koruga, Petra; Bača, Miroslav: Analysis of B-tree data structure and its usage in computer forensics // Proceedings of the 21st Central European Conference on Information and Intelligent Systems / Aurer, Boris; Bača, Miroslav; Schatten, Markus (ur.). Varaždin: Fakultet Organizacije i Informatike, 2010. pp. 423-428